


Flow sensor with integrated backflow prevention

SBY11BF0BPKG/US



1: 1" NPT



Application

Media	Liquids; water; glycol solutions; oils; coolants	
Medium temperature	[°C]	0...85
Pressure rating	[bar]	25

Electrical data

Operating voltage	[V]	10...30 DC; (to SELV/PELV)
Current consumption	[mA]	< 15
Protection class		III
Reverse polarity protection		yes

Outputs

Total number of outputs		1
Output signal		switching signal
Electrical design		PNP
Number of digital outputs		1
Output function		normally open
Max. voltage drop switching output DC	[V]	2.5
Permanent current rating of switching output DC	[mA]	100
Short-circuit protection		yes
Overload protection		yes

Accuracy / deviations

Repeatability		1
---------------	--	---



Flow sensor with integrated backflow prevention

SBY11BF0BPKG/US

	[% of the final value]	
Hysteresis	[gpm]	0,8...1,58
Measuring error		± 5
	[% of the final value]	

Response times

Response time	[s]	< 0.01
---------------	-----	--------

Operating conditions

Ambient temperature	[°C]	0...60
Storage temperature	[°C]	-15...80
Protection		IP 65; IP 67

Tests / approvals

EMC	DIN EN 61000-6-2	
	DIN EN 61000-6-3	
Shock resistance	DIN EN 60068-2-27	20 g (11 ms)
Vibration resistance	DIN EN 60068-2-6	5 g (10...2000 Hz)
MTTF	[years]	3318

Mechanical data

Weight	[g]	709.6
Materials	brass chemically nickel-plated; PPS; aluminium anodised; PA	
Materials (wetted parts)	stainless steel (1.4310 / 301); stainless steel (1.4301 / 304); PBT; brass chemically nickel-plated; PP; PPS; Polyolefin; O-ring: FKM	
Process connection	1 NPT	
Switching cycles mechanical	10 million	

Displays / operating elements

Display	switching status	4 x LED, yellow
---------	------------------	-----------------

Accessories

Accessories (supplied)	Allen key
------------------------	-----------

Remarks

Remarks	Caution Do not turn the cap beyond the maximum value of the setting range. All data refer to water (20 °C).
Pack quantity	1 pcs.

Electrical connection

Connector: 1 x M12






Flow sensor with integrated backflow prevention

SBY11BF0BPKG/US

Connection




colours to DIN EN 60947-5-2

Core colours :

- BK = black
- BN = brown
- BU = blue

Diagrams and graphs

Pressure loss



dP Pressure loss
Q volumetric flow quantity