



Main

Range of product	Lexium SD2
Product or component type	Motion stepper drive
Device short name	SD218
Communication interface	CANopen

Complementary

Network number of phases	Single phase
[Us] rated supply voltage	24...48 V
Supply voltage type	DC
Supply voltage limits	12...48 V
Maximum motor phase current	3 A
Current consumption	<= 3.2 mA
Voltage state 0 guaranteed	0...0.8 V for general purpose I/O defined as inputs
Voltage state 1 guaranteed	2.2...24 V
Input current	1.75 mA - high level for general purpose I/O defined as inputs
Output current	600 mA - single channel, duty cycle = 0.8 for general purpose I/O defined as inputs 275 mA - four channels, continuous for general purpose I/O defined as inputs
Input voltage	0...24 V for general purpose I/O defined as inputs
Residual ripple	2 V at nominal voltage
Electrical connection	1 connector wire crimp 4 pins for motor interface 1 connector wire crimp 16 pins for supply voltage and multifunction interface 1 connector DB9 for fieldbus for CANopen interface
Transmission rate	10, 20, 50, 100, 125, 250, 800, 1000 kbauds
Type of cooling	Conduction Convection
Width	45 mm
Height	33 mm
Depth	59 mm
Marking	CE
Product weight	0.08 kg

Environment

Electromagnetic compatibility	Electrostatic discharge conforming to EN/IEC 61000-4-2 Immunity to radiated radio-electrical interference conforming to EN/IEC 61000-4-3 Immunity to electrical transients conforming to EN/IEC 61000-4-4 Voltage/current impulse conforming to EN/IEC 61000-4-5 Immunity to voltage dips conforming to EN/IEC 61000-4-11 Immunity to conducted RF disturbances conforming to EN/IEC 61000-4-6
Standards	EN 55011 group 1 class A EN 61000-3-3 EN 61000-3-2
Ambient air temperature for operation	0...50 °C without with flange motor mounted on a steel plate 300 x 300 x 10 mm 50...65 °C with power derating of 2.2 % per °C with flange motor mounted on a steel plate 300 x 300 x 10 mm
Ambient air temperature for storage	-25...70 °C
Relative humidity	15...85 % without condensation
Operating altitude	<= 1000 m without
IP degree of protection	IP20

Offer Sustainability

REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration

Contractual warranty

Warranty	18 months
----------	-----------

Dimensions

