

Main

Range of product	Modicon Premium
Product or component type	Junction box for 4 load cells


Complementary

Housing material	Aluminium alloy
Housing colour	Blue
Cable entry	Metal cable gland 4 3...5 mm load cell cable Metal cable gland 1 5...8 mm weighing indicator cable
Flame retardance	VO conforming to UL 94 M3 conforming to CSTB
Connections - terminals	Screw terminal <= 1.5 mm²
Product weight	1.5 kg

Environment

Product certifications	CSA ENCLOSURE 4 CSA ENCLOSURE 5
Protective treatment	TC TH
Ambient air temperature for operation	-20...50 °C
Ambient air temperature for storage	-30...60 °C
IP degree of protection	IP657 conforming to NF C 20-010 IP65 conforming to IEC 529
Class of protection against electric shock	Class II conforming to NF C 20-030 Class II conforming to IEC 536
Fire resistance	960 °C conforming to IEC 92 850 °C conforming to NF C 20-455
Resistance to chemical agents	Highly resistant

Dimensions



- (1) 2 fixing holes for Ø 4 mm / 0.16 in. screws and lead sealing.
- (2) 4 cable glands, capacity 5 mm / 0.20 in. max.
- (3) 1 cable gland, capacity 8 mm / 0.31 in. max.