Product datasheet Characteristics

SH30401P06A2000

servo motor SH3 040 0,21Nm,no key,single,no brake,90°conn,IP54/IP65,9k RPM





Main

| | | ī |
|---------------------------|-------------|-----|
| Range compatibility | PacDrive 3 | |
| Product or component type | Servo motor | - 1 |
| Device short name | SH3P | |

Complementary

| Maximum mechanical speed | 9000 rpm | |
|---------------------------|--|--|
| [Us] rated supply voltage | 115480 V | |
| Network number of phases | Three phase | |
| Continuous stall current | 1.12 A | |
| Continuous stall torque | 0.21 N.m at 115480 V three phase | |
| Continuous power | 220 W | |
| Peak stall torque | 0.8 N.m at 480 V three phase | |
| Nominal output power | 77 W at 115 V three phase 77 W at 230 V three phase 166 W at 400 V three phase 166 W at 480 V three phase | |
| Nominal torque | 0.176 N.m at 115 V three phase 0.176 N.m at 230 V three phase 0.184 N.m at 400 V three phase 0.184 N.m at 480 V three phase | |
| Nominal speed | 4000 rpm at 115 V three phase 4000 rpm at 230 V three phase 9000 rpm at 400 V three phase 9000 rpm at 480 V three phase | |
| Maximum current Irms | 4.7 A | |
| Shaft end | Smooth shaft | |
| Shaft diameter | 8 mm | |
| Shaft length | 25 mm | |
| IP degree of protection | IP54 shaft bushing without shaft seal ring: conforming to EN/IEC 60034-5 IP65 motor: conforming to EN/IEC 60034-5 | |

| Encoder type | Absolute single turn SinCos Hiperface |
|---------------------------------------|---------------------------------------|
| Speed feedback resolution | 16 periods |
| Holding brake | Without |
| Mounting support | International standard flange |
| Motor flange size | 40 mm |
| Torque constant | 0.19 N.m/A at 120 °C |
| Back emf constant | 13.6 V/krpm at 20 °C |
| Number of motor poles | 5 |
| Rotor inertia | 0.0232 kg.cm² |
| Stator resistance | 17.2 Ohm |
| Stator inductance | 14.6 mH |
| Type of cooling | Natural convection |
| Length | 73.4 mm |
| Centring collar diameter | 30 mm |
| Centring collar depth | 2.5 mm |
| Number of mounting holes | 4 |
| Mounting holes diameter | 4.5 mm |
| Circle diameter of the mounting holes | 46 mm |
| Product weight | 0.4 kg |

Offer Sustainability

| Sustainable offer status | Green Premium product | |
|----------------------------|---|--|
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration | |
| Mercury free | Yes | |
| RoHS exemption information | Yes | |
| China RoHS Regulation | China RoHS declaration | |
| Environmental Disclosure | Product Environmental Profile | |
| Circularity Profile | No need of specific recycling operations | |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins | |

Contractual warranty

| Warranty 18 months |
|--------------------|
|--------------------|