# Product datasheet Characteristics

# SH30401P17A2100

servo motor SH3 040 0,21Nm,key,multi,no brake,90°conn,IP65/IP65,9k RPM





#### Main

		<del>~</del>
Range compatibility	PacDrive 3	s o
Product or component type	Servo motor	
Device short name	SH3P	

#### Complementary

Maximum mechanical speed	9000 rpm	
[Us] rated supply voltage	115480 V	
Network number of phases	Three phase	
Continuous stall current	1.12 A	
Continuous stall torque	0.21 N.m at 115480 V three phase	
Continuous power	220 W	
Peak stall torque	0.8 N.m at 480 V three phase	
Nominal output power	77 W at 115 V three phase 77 W at 230 V three phase 166 W at 400 V three phase 166 W at 480 V three phase	
Nominal torque	0.176 N.m at 115 V three phase 0.176 N.m at 230 V three phase 0.184 N.m at 400 V three phase 0.184 N.m at 480 V three phase	
Nominal speed	4000 rpm at 115 V three phase 4000 rpm at 230 V three phase 9000 rpm at 400 V three phase 9000 rpm at 480 V three phase	
Maximum current Irms	4.7 A	
Shaft end	Parallel key	
Shaft diameter	8 mm	
Shaft length	25 mm	
IP degree of protection	IP65 motor: conforming to EN/IEC 60034-5 IP65 shaft bushing: conforming to EN/IEC 60034-5	

Encoder type	Absolute multiturn SinCos Hiperface
Speed feedback resolution	16 periods
Holding brake	Without
Mounting support	International standard flange
Motor flange size	40 mm
Torque constant	0.19 N.m/A at 120 °C
Back emf constant	13.6 V/krpm at 20 °C
Number of motor poles	5
Rotor inertia	0.0232 kg.cm²
Stator resistance	17.2 Ohm
Stator inductance	14.6 mH
Type of cooling	Natural convection
Length	73.4 mm
Centring collar diameter	30 mm
Centring collar depth	2.5 mm
Number of mounting holes	4
Mounting holes diameter	4.5 mm
Circle diameter of the mounting holes	46 mm
Product weight	0.4 kg

## Offer Sustainability

Sustainable offer status	Green Premium product  Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
EU RoHS Directive		
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	No need of specific recycling operations	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	

### Contractual warranty

Warranty 18 month	
-------------------	--