



Main

Range compatibility	PacDrive 3
Product or component type	Servo motor
Device short name	SH3.....P

Complementary

Maximum mechanical speed	4000 rpm
[Us] rated supply voltage	115...480 V
Network number of phases	Three phase
Continuous stall current	21.3 A
Continuous stall torque	33.4 N.m at 115...480 V three phase
Peak stall torque	131.9 N.m at 115...480 V three phase
Nominal output power	4190 W at 480 V three phase 5060 W at 400 V three phase 4130 W at 230 V three phase 2370 W at 115 V three phase
Nominal torque	11.1 N.m at 480 V three phase 16.1 N.m at 400 V three phase 26.3 N.m at 230 V three phase 30.2 N.m at 115 V three phase
Nominal speed	3600 rpm at 480 V three phase 3000 rpm at 400 V three phase 1500 rpm at 230 V three phase 750 rpm at 115 V three phase
Maximum current Irms	95.6 A
Shaft end	Smooth shaft
Shaft diameter	24 mm
Shaft length	50 mm
Key width	8 mm
IP degree of protection	IP65 (shaft bushing) conforming to EN/IEC 60034-5 IP65 (motor) conforming to EN/IEC 60034-5 IP54 (shaft bushing without shaft seal ring) conforming to EN/IEC 60034-5
Encoder type	Absolute single turn SinCos Hiperface
Speed feedback resolution	128 periods
Holding brake	With
Holding torque	36 N.m
Mounting support	International standard flange
Motor flange size	140 mm
Electrical connection	Rotatable right angled connector
Torque constant	1.57 N.m/A at -20...40 °C
Back emf constant	104 V/krpm at 20 °C

Number of motor poles	5
Rotor inertia	29.2 kg.cm ²
Stator resistance	0.28 Ohm at -20...40 °C
Stator inductance	5.945 mH at -20...40 °C
Maximum radial force Fr	1840 N at 3000 rpm 2110 N at 2000 rpm 2660 N at 1000 rpm
Maximum axial force Fa	300 N
Type of cooling	Natural convection
Length	420.5 mm
Centring collar diameter	130 mm
Centring collar depth	3.5 mm
Number of mounting holes	4
Mounting holes diameter	11 mm
Circle diameter of the mounting holes	165 mm
Product weight	27.8 kg

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1036 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available Download Product Environmental
Product end of life instructions	Need no specific recycling operations