



## Main

|                           |             |
|---------------------------|-------------|
| Range compatibility       | PacDrive 3  |
| Product or component type | Servo motor |
| Device short name         | SH3.....P   |

## Complementary

|                           |                                                                                                                                  |
|---------------------------|----------------------------------------------------------------------------------------------------------------------------------|
| Maximum mechanical speed  | 4000 rpm                                                                                                                         |
| [Us] rated supply voltage | 115...480 V                                                                                                                      |
| Network number of phases  | Three phase                                                                                                                      |
| Continuous stall current  | 21.3 A                                                                                                                           |
| Continuous stall torque   | 33.4 N.m at 115...480 V three phase                                                                                              |
| Peak stall torque         | 131.9 N.m at 115...480 V three phase                                                                                             |
| Nominal output power      | 4190 W at 480 V three phase<br>5060 W at 400 V three phase<br>4130 W at 230 V three phase<br>2370 W at 115 V three phase         |
| Nominal torque            | 11.1 N.m at 480 V three phase<br>16.1 N.m at 400 V three phase<br>26.3 N.m at 230 V three phase<br>30.2 N.m at 115 V three phase |
| Nominal speed             | 3600 rpm at 480 V three phase<br>3000 rpm at 400 V three phase<br>1500 rpm at 230 V three phase<br>750 rpm at 115 V three phase  |
| Maximum current Irms      | 95.6 A                                                                                                                           |
| Shaft end                 | Smooth shaft                                                                                                                     |
| Shaft diameter            | 24 mm                                                                                                                            |
| Shaft length              | 50 mm                                                                                                                            |
| Key width                 | 8 mm                                                                                                                             |
| IP degree of protection   | IP65 (shaft bushing) conforming to EN/IEC 60034-5<br>IP65 (motor) conforming to EN/IEC 60034-5                                   |
| Encoder type              | Absolute multiturn SinCos Hiperface                                                                                              |
| Speed feedback resolution | 128 periods                                                                                                                      |
| Holding brake             | Without                                                                                                                          |
| Holding torque            | 36 N.m                                                                                                                           |
| Mounting support          | International standard flange                                                                                                    |
| Motor flange size         | 140 mm                                                                                                                           |
| Electrical connection     | Rotatable right angled connector                                                                                                 |
| Torque constant           | 1.57 N.m/A at -20...40 °C                                                                                                        |
| Back emf constant         | 104 V/krpm at 20 °C                                                                                                              |

|                                       |                                                                |
|---------------------------------------|----------------------------------------------------------------|
| Number of motor poles                 | 5                                                              |
| Rotor inertia                         | 23.7 kg.cm <sup>2</sup>                                        |
| Stator resistance                     | 0.28 Ohm at -20...40 °C                                        |
| Stator inductance                     | 5.945 mH at -20...40 °C                                        |
| Maximum radial force Fr               | 1840 N at 3000 rpm<br>2110 N at 2000 rpm<br>2660 N at 1000 rpm |
| Maximum axial force Fa                | 300 N                                                          |
| Type of cooling                       | Natural convection                                             |
| Length                                | 382.5 mm                                                       |
| Centring collar diameter              | 130 mm                                                         |
| Centring collar depth                 | 3.5 mm                                                         |
| Number of mounting holes              | 4                                                              |
| Mounting holes diameter               | 11 mm                                                          |
| Circle diameter of the mounting holes | 165 mm                                                         |
| Product weight                        | 26 kg                                                          |

### Offer Sustainability

|                                  |                                                                                       |
|----------------------------------|---------------------------------------------------------------------------------------|
| Sustainable offer status         | Green Premium product                                                                 |
| RoHS (date code: YYWW)           | Compliant - since 1036 - <a href="#">Schneider Electric declaration of conformity</a> |
| REACH                            | Reference not containing SVHC above the threshold                                     |
| Product environmental profile    | Available <a href="#">Download Product Environmental</a>                              |
| Product end of life instructions | Need no specific recycling operations                                                 |