



Main

Range compatibility	PacDrive 3
Product or component type	Servo motor
Device short name	SH3.....P

Complementary

Maximum mechanical speed	3800 rpm
[Us] rated supply voltage	115...480 V
Network number of phases	Three phase
Continuous stall current	25.7 A
Continuous stall torque	64.9 N.m at 115...480 V three phase
Peak stall torque	220 N.m at 115...480 V three phase
Nominal output power	3230 W at 115 V three phase 5860 W at 230 V three phase 7980 W at 400 V three phase 7140 W at 480 V three phase
Nominal torque	61.6 N.m at 115 V three phase 56 N.m at 230 V three phase 38.1 N.m at 400 V three phase 28.4 N.m at 480 V three phase
Nominal speed	500 rpm at 115 V three phase 1000 rpm at 230 V three phase 2000 rpm at 400 V three phase 2400 rpm at 480 V three phase
Maximum current Irms	96.8 A
Shaft end	Smooth shaft
Shaft diameter	38 mm
Shaft length	80 mm
IP degree of protection	IP54 shaft bushing without shaft seal ring: conforming to EN/IEC 60034-5 IP65 motor: conforming to EN/IEC 60034-5

IP65 shaft bushing: conforming to EN/IEC 60034-5

Encoder type	Absolute single turn SinCos Hiperface
Speed feedback resolution	128 periods
Holding brake	Without
Mounting support	International standard flange
Motor flange size	205 mm
Torque constant	2.58 N.m/A at 120 °C
Back emf constant	161 V/krpm at 20 °C
Number of motor poles	5
Rotor inertia	129 kg.cm ²
Stator resistance	0.3 Ohm
Stator inductance	8.2 mH
Maximum radial force Fr	4200 N at 1000 rpm 3330 N at 2000 rpm 2910 N at 3000 rpm
Maximum axial force Fa	740 N
Type of cooling	Natural convection
Length	405 mm
Centring collar diameter	180 mm
Centring collar depth	4 mm
Number of mounting holes	4
Mounting holes diameter	14 mm
Circle diameter of the mounting holes	215 mm
Product weight	50 kg

Offer Sustainability

Sustainable offer status	Green Premium product
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------