



## Level sensors TDR level sensor

LFP0350-G1NMB



**Model Name** > LFP0350-G1NMB  
**Part No.** > 1057433



*Illustration may differ*

#### At a glance

- Level monitoring in hygienic applications
- Manually cutable monoprobe made from stainless steel 1.4404 up to 4,000 mm long with Ra 0.8 µm
- Process temperature up to 150 °C, process pressure up to 16 bar
- CIP/SIP resistant
- IP 67 and IP 69K enclosure rating
- Interchangeable hygienic process connections
- 3 in 1: combined display, analog output and binary output
- Analog output 4 mA ... 20 mA / 0 V ... 10 V, switchable, plus two binary outputs

#### Your benefits

- Robust design increases service life
- High flexibility due to cutable probe and interchangeable connection concept
- Cost savings due to multiple output signals: one system for both level detection and continuous level monitoring
- Time and cost savings due to low maintenance and quick commissioning
- No calibration or recalibration required for commissioning, thus saving time and costs



#### Features

|                      |                    |
|----------------------|--------------------|
| Medium:              | Fluids             |
| Measurement:         | Switch, Continuous |
| Probe length:        | 350 mm             |
| Process pressure:    | -1 bar ... 16 bar  |
| Process temperature: | -20 °C ... +150 °C |
| EHEDG approval:      | ✓                  |
| GOST approval:       | ✓                  |
| UL approval:         | ✓                  |
| RoHS certificate:    | ✓                  |
| IO-Link:             | ✓                  |
| 3-A:                 | -                  |

#### Performance

|                             |                                             |
|-----------------------------|---------------------------------------------|
| Resolution:                 | < 2 mm                                      |
| Accuracy of sensor element: | ± 5 mm                                      |
| Repeatability:              | ≤ 2 mm                                      |
| Dielectricity constant:     | ≥ 1.8 with coaxial tube, ≥ 5 for mono probe |

|                                     |                          |
|-------------------------------------|--------------------------|
| Inactive area at process connector: | 25 mm <sup>1)</sup>      |
| Inactive area at probe end:         | 10 mm <sup>2)</sup>      |
| Conductivity:                       | No limitation            |
| Response time:                      | < 400 ms <sup>3)</sup>   |
| MTTF:                               | 194.3 a (EN ISO 13849-1) |

<sup>1)</sup> With parameterized tank with water under reference conditions, otherwise 40 mm <sup>2)</sup> With water under reference conditions <sup>3)</sup> Depending on measuring mode (high speed < 400 ms, high accuracy < 2,800 ms).

## Mechanical data

|                     |                          |
|---------------------|--------------------------|
| Housing material:   | 303                      |
| Max.probe load:     | 6 Nm                     |
| Process connection: | G ¾ A                    |
| Wetted parts:       | 316L (Ra ≤ 0,8 µm), PEEK |
| Housing design:     | With PMMA viewing window |



## Electrical data

|                               |                                                                                                                     |
|-------------------------------|---------------------------------------------------------------------------------------------------------------------|
| Temperature drift:            | < 0.1 mm/K                                                                                                          |
| Enclosure rating:             | IP 67: EN 60529, IP 69K: EN 40050                                                                                   |
| Supply voltage:               | 12 V DC ... 30 V DC <sup>1)</sup>                                                                                   |
| Power consumption:            | ≤ 75 mA at 24 V DC without output load                                                                              |
| Protection class:             | III                                                                                                                 |
| Initialization time:          | ≤ 2 s                                                                                                               |
| Output load:                  | 0 V ... 10 V > 750 Ohm at Uv ≥ 14 V, 4 mA ... 20 mA < 400 Ohm at Uv > 12 V, 4 mA ... 20 mA < 500 Ohm at Uv > 13,5 V |
| Upper signal level:           | 20 mA ... 20.5 mA                                                                                                   |
| Lower signal level:           | 3.8 mA ... 4 mA                                                                                                     |
| Hysteresis:                   | Min. 2 mm, free adjustable                                                                                          |
| Output current:               | < 100 mA                                                                                                            |
| Signal voltage HIGH:          | Vs - 2 V                                                                                                            |
| Signal voltage LOW:           | ≤ 2 V                                                                                                               |
| Capacitive load:              | 100 nF                                                                                                              |
| Inductive load:               | < 1 H                                                                                                               |
| Connection type:              | Round connector M12 x 1, 5-pin                                                                                      |
| EMC:                          | EN 61326-1:2006, 2004/108/EG                                                                                        |
| Interference resistance:      | EN 61000-6-2:2005                                                                                                   |
| Interference emission:        | EN 61000-6-4:2007                                                                                                   |
| Single- and continuous shock: | EN 60068-2-27                                                                                                       |


<sup>1)</sup> All connections are polarity protected. All outputs are overload and short-circuit protected.

## Ambient data

|                                |                   |
|--------------------------------|-------------------|
| Ambient operating temperature: | -20 °C ... +60 °C |
| Ambient storage temperature:   | -40 °C ... +80 °C |



- [1] L+: Supply voltage, brown
- [2] QA: Analog current-voltage output, white
- [3] M: Ground, reference ground  
for current-voltage output, blue
- [4] C/Q1: Switching output 1,  
PNP/IO-Link-communication, black
- [5] Q2: Switching output 2, PNP/NPN, grey



**Australia**

Phone +61 3 9457 0600  
1800 33 48 02 – tollfree  
E-Mail sales@sick.com.au

**Belgium/Luxembourg**

Phone +32 (0)2 466 55 66  
E-Mail info@sick.be

**Brasil**

Phone +55 11 3215-4900  
E-Mail marketing@sick.com.br

**Canada**

Phone +1 905 771 14 44  
E-Mail information@sick.com

**Česká republika**

Phone +420 2 57 91 18 50  
E-Mail sick@sick.cz

**China**

Phone +86 4000 121 000  
E-Mail info.china@sick.net.cn  
Phone +852-2153 6300  
E-Mail ghk@sick.com.hk

**Danmark**

Phone +45 45 82 64 00  
E-Mail sick@sick.dk

**Deutschland**

Phone +49 211 5301-301  
E-Mail info@sick.de

**España**

Phone +34 93 480 31 00  
E-Mail info@sick.es

**France**

Phone +33 1 64 62 35 00  
E-Mail info@sick.fr

**Great Britain**

Phone +44 (0)1727 831121  
E-Mail info@sick.co.uk

**India**

Phone +91-22-4033 8333  
E-Mail info@sick-india.com

**Israel**

Phone +972-4-6881000  
E-Mail info@sick-sensors.com

**Italia**

Phone +39 02 27 43 41  
E-Mail info@sick.it

**Japan**

Phone +81 (0)3 5309 2112  
E-Mail support@sick.jp

**Magyarország**

Phone +36 1 371 2680  
E-Mail office@sick.hu

**Nederland**

Phone +31 (0)30 229 25 44  
E-Mail info@sick.nl

**Norge**

Phone +47 67 81 50 00  
E-Mail sick@sick.no

**Österreich**

Phone +43 (0)22 36 62 28 8-0  
E-Mail office@sick.at

**Polska**

Phone +48 22 837 40 50  
E-Mail info@sick.pl

**România**

Phone +40 356 171 120  
E-Mail office@sick.ro

**Russia**

Phone +7-495-775-05-30  
E-Mail info@sick.ru

**Schweiz**

Phone +41 41 619 29 39  
E-Mail contact@sick.ch

**Singapore**

Phone +65 6744 3732  
E-Mail sales.gsg@sick.com

**Slovenija**

Phone +386 (0)1-47 69 990  
E-Mail office@sick.si

**South Africa**

Phone +27 11 472 3733  
E-Mail info@sickautomation.co.za

**South Korea**

Phone +82 2 786 6321/4  
E-Mail info@sickkorea.net

**Suomi**

Phone +358-9-25 15 800  
E-Mail sick@sick.fi

**Sverige**

Phone +46 10 110 10 00  
E-Mail info@sick.se

**Taiwan**

Phone +886 2 2375-6288  
E-Mail sales@sick.com.tw

**Türkiye**

Phone +90 (216) 528 50 00  
E-Mail info@sick.com.tr

**United Arab Emirates**

Phone +971 (0) 4 88 65 878  
E-Mail info@sick.ae

**USA/México**

Phone +1(952) 941-6780  
1 (800) 325-7425 – tollfree  
E-Mail info@sickusa.com

More representatives and agencies  
at [www.sick.com](http://www.sick.com)