



Photoelectric sensors  
ZoneControl, Photoelectric proximity sensor,  
Background suppression

IRT-P212C63



**Model Name** > IRT-P212C63  
**Part No.** > 1063116

#### At a glance

- All-in-one ZoneControl solution: sensor, logic and actuator
- Single accumulation or single accumulation with sleep
- Ideal for pneumatic actuators or motor-driven rollers
- Daisy chain connection cable included for zone lengths of 1 m and 2 m
- Output options with flying leads, M12 or integrated valve
- Integrated with SICK's patented optical ASIC: SIRIC
- IP 65 housing for harsh wash down environments

#### Your benefits

- 30% lower current draw reduces the size of the power supply and yearly electric costs
- Next-generation SIRIC optical ASIC provides ambient light immunity, which eliminates false trips and ensures high productivity
- Variety of features and choices ensure application requirements are met
- Background suppression reduces mounting effort since no reflector is required
- Daisy chain connectivity ensures changes or additions to the system can be made quickly
- Sleep mode, which switches the rollers off after 9 s of inactivity, dramatically reduces power costs
- Mounting between the rollers prevents damage and sensor interference
- The all-in-one solution with sensor, logic and valve reduces wiring and programming costs



*Illustration may differ*



#### Features

|                                 |                                                        |
|---------------------------------|--------------------------------------------------------|
| Sensor/detection principle:     | Photoelectric proximity sensor, Background suppression |
| Dimensions (W x H x D):         | 20.6 mm x 99.2 mm x 48.9 mm                            |
| Sensing range:                  | 60 mm ... 900 mm                                       |
| Type of light:                  | Infrared light                                         |
| Light source:                   | LED <sup>1)</sup>                                      |
| Angle of dispersion:            | 7 °                                                    |
| Adjustment:                     | Potentiometer, 9 turns                                 |
| Light spot size (distance):     | Ø 20 mm (500 mm)                                       |
| Actuator:                       | Pneumatic, valve supplied separately                   |
| Max. number of sensors::        | Ca. 30, Ca. 50 <sup>2) 3)</sup>                        |
| Logical principle of operation: | Single accumulation                                    |
| Type of Release:                | Block (slug) release, Single release                   |


1) Average service life of 100,000 h at  $T_A = +25\text{ °C}$  2) When powerd from the end of the IR daisy chain 3) When powerd from center of the IR daisy chain

## Mechanics/electronics


|                                   |                                       |
|-----------------------------------|---------------------------------------|
| Supply voltage:                   | 10 V DC ... 30 V DC <sup>1)</sup>     |
| Ripple:                           | < 5 Vpp <sup>2)</sup>                 |
| Power consumption:                | < 20 mA <sup>3)</sup>                 |
| Output type:                      | PNP                                   |
| Output current I <sub>max</sub> : | ≤ 100 mA                              |
| Response time:                    | 2 ms                                  |
| Switching frequency:              | ± 250 Hz                              |
| Connection type:                  | Connector M12, 4-pin <sup>4)</sup>    |
| Circuit protection:::             | A, C, D <sup>5) 6) 7)</sup>           |
| Protection class:                 | III                                   |
| Weight:                           | 175 g                                 |
| Housing material:                 | ABS, Plastic                          |
| Enclosure rating:                 | IP 67                                 |
| Ambient operating temperature:    | -40 °C ... +60 °C                     |
| Ambient storage temperature:      | -40 °C ... +75 °C                     |
| Shock/vibration:                  | According to IEC 68                   |
| UL File No.:                      | NRKH.E189383 & NRKH7.E189383          |
| Signal voltage PNP HIGH/LOW:      | Approx. VS - 0.5 V / 0 V              |
| Connection type for daisy chain:  | Cable with receptacle, M12, 4-pin 2 m |
| Mode of operation solenoid valve: | HIGH to Drive                         |
| Connection type solenoid valve:   | Cable with 9.4 mm DIN valve connector |

1) Limit values 2) May not exceed or fall short of  $V_{S7}$  tolerances 3) Without load and valve deenergized 4) Do not bend below 0 °C 5)  $A = V_S$  connections reverse-polarity protected 6) C = interference suppression 7) D = outputs overcurrent and short-circuit protected


- [1] LED
- [2] Potentiometer
- [3] Mounting hole
- [4] Center of optical axis, sender
- [5] Center of optical axis, receiver
- [6] Connector M12, 4-pin



Characteristic curve




Sensing range diagram



Connection to conveyor

9.4 mm DIN cable, 300 mm



**Australia**

Phone +61 3 9457 0600  
1800 33 48 02 – tollfree  
E-Mail sales@sick.com.au

**Belgium/Luxembourg**

Phone +32 (0)2 466 55 66  
E-Mail info@sick.be

**Brasil**

Phone +55 11 3215-4900  
E-Mail marketing@sick.com.br

**Canada**

Phone +1 905 771 14 44  
E-Mail information@sick.com

**Česká republika**

Phone +420 2 57 91 18 50  
E-Mail sick@sick.cz

**China**

Phone +86 4000 121 000  
E-Mail info.china@sick.net.cn  
Phone +852-2153 6300  
E-Mail ghk@sick.com.hk

**Danmark**

Phone +45 45 82 64 00  
E-Mail sick@sick.dk

**Deutschland**

Phone +49 211 5301-301  
E-Mail info@sick.de

**España**

Phone +34 93 480 31 00  
E-Mail info@sick.es

**France**

Phone +33 1 64 62 35 00  
E-Mail info@sick.fr

**Great Britain**

Phone +44 (0)1727 831121  
E-Mail info@sick.co.uk

**India**

Phone +91-22-4033 8333  
E-Mail info@sick-india.com

**Israel**

Phone +972-4-6881000  
E-Mail info@sick-sensors.com

**Italia**

Phone +39 02 27 43 41  
E-Mail info@sick.it

**Japan**

Phone +81 (0)3 5309 2112  
E-Mail support@sick.jp

**Magyarország**

Phone +36 1 371 2680  
E-Mail office@sick.hu

**Nederland**

Phone +31 (0)30 229 25 44  
E-Mail info@sick.nl

**Norge**

Phone +47 67 81 50 00  
E-Mail sick@sick.no

**Österreich**

Phone +43 (0)22 36 62 28 8-0  
E-Mail office@sick.at

**Polska**

Phone +48 22 837 40 50  
E-Mail info@sick.pl

**România**

Phone +40 356 171 120  
E-Mail office@sick.ro

**Russia**

Phone +7-495-775-05-30  
E-Mail info@sick.ru

**Schweiz**

Phone +41 41 619 29 39  
E-Mail contact@sick.ch

**Singapore**

Phone +65 6744 3732  
E-Mail sales.gsg@sick.com

**Slovenija**

Phone +386 (0)1-47 69 990  
E-Mail office@sick.si

**South Africa**

Phone +27 11 472 3733  
E-Mail info@sickautomation.co.za

**South Korea**

Phone +82 2 786 6321/4  
E-Mail info@sickkorea.net

**Suomi**

Phone +358-9-25 15 800  
E-Mail sick@sick.fi

**Sverige**

Phone +46 10 110 10 00  
E-Mail info@sick.se

**Taiwan**

Phone +886 2 2375-6288  
E-Mail sales@sick.com.tw

**Türkiye**

Phone +90 (216) 528 50 00  
E-Mail info@sick.com.tr

**United Arab Emirates**

Phone +971 (0) 4 88 65 878  
E-Mail info@sick.ae

**USA/México**

Phone +1(952) 941-6780  
1 (800) 325-7425 – tollfree  
E-Mail info@sickusa.com

More representatives and agencies  
at [www.sick.com](http://www.sick.com)