



# MICS3-AAA40AZ1P01

microScan3

SAFETY LASER SCANNERS

**SICK**  
Sensor Intelligence.



### Ordering information

| Type               | Part no. |
|--------------------|----------|
| MICS3-AAAZ40AZ1P01 | 1075842  |

Other models and accessories → [www.sick.com/microScan3](http://www.sick.com/microScan3)



### Detailed technical data

#### Features

|                                                  |                                                      |
|--------------------------------------------------|------------------------------------------------------|
| <b>Protective field range</b>                    | 4 m                                                  |
| <b>Warning field range</b>                       | 40 m                                                 |
| <b>Number of simultaneously monitored fields</b> | ≤ 4 <sup>1) 2)</sup>                                 |
| <b>Number of fields</b>                          | 8 <sup>3)</sup>                                      |
| <b>Number of monitoring cases</b>                | 2                                                    |
| <b>Scanning angle</b>                            | 275 °                                                |
| <b>Resolution (can be configured)</b>            | 30 mm<br>40 mm<br>50 mm<br>70 mm<br>150 mm<br>200 mm |
| <b>Angular resolution</b>                        | 0.39 °                                               |
| <b>Response time</b>                             | ≥ 70 ms                                              |
| <b>Protective field supplement</b>               | 65 mm                                                |

<sup>1)</sup> Protection, warning or contour detection fields.

<sup>2)</sup> Please note the number of available OSSD pairs.

<sup>3)</sup> Please note the number of available inputs and OSSD pairs.

#### Safety-related parameters

|                                                                           |                                       |
|---------------------------------------------------------------------------|---------------------------------------|
| <b>Type</b>                                                               | Type 3 (IEC 61496)                    |
| <b>Safety integrity level</b>                                             | SIL2 (IEC 61508)<br>SILCL2 (EN 62061) |
| <b>Category</b>                                                           | Category 3 (EN ISO 13849)             |
| <b>Performance level</b>                                                  | PL d (EN ISO 13849)                   |
| <b>PFH<sub>D</sub> (mean probability of a dangerous failure per hour)</b> | 8.0 x 10 <sup>-8</sup> (EN ISO 13849) |

|                                           |                                        |
|-------------------------------------------|----------------------------------------|
| <b>T<sub>M</sub> (mission time)</b>       | 20 years (EN ISO 13849)                |
| <b>Safe state in the event of a fault</b> | At least one OSSD is in the OFF state. |

## Functions

|                                          |      |
|------------------------------------------|------|
| <b>Restart interlock</b>                 | ✓    |
| <b>External device monitoring (EDM)</b>  | ✓    |
| <b>Multiple sampling</b>                 | ✓    |
| <b>Monitoring case switching</b>         | ✓    |
| <b>Simultaneous monitoring</b>           | ✓    |
| <b>Static protective field switching</b> | ✓    |
| <b>Safe contour detection</b>            | ✓    |
| <b>Contour as a reference</b>            | ✓    |
| <b>Integrated configuration memory</b>   | ✓    |
| <b>Measured data output</b>              | None |

## Interfaces

|                                                |                                                                                                     |
|------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| <b>Connection type</b>                         | Male connector, M12, 8 pin, A-coded (common male connector for power supply and inputs and outputs) |
| <b>Universal I/Os</b>                          | 3                                                                                                   |
| <b>Outputs</b>                                 |                                                                                                     |
| OSSD pairs                                     | 1                                                                                                   |
| <b>Configuration method</b>                    | PC with Safety Designer (Configuration and Diagnostic Software)                                     |
| <b>Configuration and diagnostics interface</b> | USB 2.0, Mini-USB                                                                                   |
| <b>Display elements</b>                        | Graphic color display, LEDs                                                                         |

## Electrical data

|                                     |                                 |
|-------------------------------------|---------------------------------|
| <b>Protection class</b>             | III (EN 61140)                  |
| <b>Supply voltage V<sub>s</sub></b> | 24 V DC (16.8 V DC ... 30 V DC) |
| <b>Power consumption</b>            | 7 W (without output load)       |

## Mechanical data

|                                    |                                        |
|------------------------------------|----------------------------------------|
| <b>Dimensions (W x H x D)</b>      | 112 mm x 135 mm x 111 mm               |
| <b>Weight</b>                      | 1.15 kg                                |
| <b>Housing material</b>            | Aluminum                               |
| <b>Housing color</b>               | RAL 1021 (yellow), RAL 9005 (black)    |
| <b>Optics cover material</b>       | Polycarbonate                          |
| <b>Optics cover surface finish</b> | Outside with scratch-resistant coating |

## Ambient data

|                                      |                                                                                                                                       |
|--------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------|
| <b>Enclosure rating</b>              | IP65 (IEC 60529)                                                                                                                      |
| <b>Ambient light immunity</b>        | ≤ 3,000 lx (IEC 61496-3)                                                                                                              |
| <b>Ambient operating temperature</b> | -10 °C ... +50 °C                                                                                                                     |
| <b>Storage temperature</b>           | -25 °C ... +70 °C                                                                                                                     |
| <b>Vibration resistance</b>          | 0.35 mm, 10 Hz ... 60 Hz (IEC 60068-2-6, IEC 61496-1, IEC 61496-3)<br>5 g, 60 Hz ... 150 Hz (IEC 60068-2-6, IEC 61496-1, IEC 61496-3) |
| <b>Shock resistance</b>              |                                                                                                                                       |

|            |                  |                                               |
|------------|------------------|-----------------------------------------------|
|            | Continuous shock | 10 g, 16 ms (IEC 60068-2-27, IEC 61496-3)     |
| <b>EMC</b> |                  | IEC 61496-1<br>IEC 61000-6-2<br>IEC 61000-6-4 |


## Other information

|                             |                                              |
|-----------------------------|----------------------------------------------|
| <b>Type of light</b>        | Pulsed laser diode                           |
| <b>Wave length</b>          | 845 nm                                       |
| <b>Detectable remission</b> | 1.8% to several 1000%                        |
| <b>Laser class</b>          | 1M (21 CFR 1040.10 and 1040.11, IEC 60825-1) |

## Classifications

|                       |          |
|-----------------------|----------|
| <b>ECl@ss 5.0</b>     | 27272705 |
| <b>ECl@ss 5.1.4</b>   | 27272705 |
| <b>ECl@ss 6.0</b>     | 27272705 |
| <b>ECl@ss 6.2</b>     | 27272705 |
| <b>ECl@ss 7.0</b>     | 27272705 |
| <b>ECl@ss 8.0</b>     | 27272705 |
| <b>ECl@ss 8.1</b>     | 27272705 |
| <b>ECl@ss 9.0</b>     | 27272705 |
| <b>ECl@ss 10.0</b>    | 27272705 |
| <b>ECl@ss 11.0</b>    | 27272705 |
| <b>ETIM 5.0</b>       | EC002550 |
| <b>ETIM 6.0</b>       | EC002550 |
| <b>ETIM 7.0</b>       | EC002550 |
| <b>UNSPSC 16.0901</b> | 39121528 |


### Dimensional drawing (Dimensions in mm (inch))



- ① Mirror axis of rotation
- ② Scan plane
- ③ Required viewing slit

### Connection diagram

microScan3 Core I/O with restart interlock and external device monitoring at RLY3-OSSD1 safety relay



① Output circuits. These contacts must be incorporated into the control such that the dangerous state is brought to an end if the output circuit is open. For categories 4 and 3, they must be incorporated on two channels (x, y paths). Single-channel incorporation into the control (z path) is only possible with a single-channel control and taking the risk analysis into account.

Uni-I/O 1: configured as input reset

Uni-I/O 2: configured as input external device monitoring (EDM)

Uni-I/O 3: configured as output reset required

1)

|    |    |
|----|----|
| x  | y  |
| k1 | k2 |
| x  | y  |


---

|    |   |
|----|---|
| k1 | z |
| k2 | z |

Uni-I/O 1: configured as input reset  
Uni-I/O 2: configured as input external device monitoring (EDM)  
Uni-I/O 3: configured as output reset required

Other models and accessories → [www.sick.com/microScan3](http://www.sick.com/microScan3)

2021-03-04 11:56:02 | Product data sheet  
Subject to change without notice

|                                                                                    | Brief description                                                                                                                                                                                                                                                              | Type                                                    | Part no. |
|------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------|----------|
|   | 1 piece, mounting bracket, Stainless steel V2A (1.4301), powder-coated IGP-DURA face 5803A                                                                                                                                                                                     | Mounting kit 1a                                         | 2073851  |
|   | 1 piece, mounting bracket with protection of optics hood, Stainless steel V2A (1.4301), powder-coated IGP-DURA face 5803A                                                                                                                                                      | Mounting kit 1b                                         | 2074242  |
|   | 1 piece, alignment bracket, alignment with cross-wise axis and depth axis possible, distance between mounting surface and device: 22.3 mm, only in conjunction with mounting kit 1a (2073851) or 1b (2074242), Stainless steel V2A (1.4301), powder-coated IGP-DURA face 5803A | Mounting kit 2a                                         | 2073852  |
| Plug connectors and cables                                                         |                                                                                                                                                                                                                                                                                |                                                         |          |
|  | Head A: female connector, M12, 8-pin, straight, A-coded<br>Head B: Flying leads<br>Cable: Sensor/actuator cable, PUR, halogen-free, unshielded, 2 m                                                                                                                            | DOL-1208G02MD25KM1                                      | 2079314  |
|                                                                                    | Head A: female connector, M12, 8-pin, straight, A-coded<br>Head B: Flying leads<br>Cable: Sensor/actuator cable, PUR, halogen-free, unshielded, 5 m                                                                                                                            | DOL-1208G05MD25KM1                                      | 2079315  |
|                                                                                    | Head A: female connector, M12, 8-pin, straight, A-coded<br>Head B: Flying leads<br>Cable: Sensor/actuator cable, PUR, halogen-free, unshielded, 10 m                                                                                                                           | DOL-1208G10MD25KM1                                      | 2079316  |
|                                                                                    | Head A: female connector, M12, 8-pin, straight, A-coded<br>Head B: Flying leads<br>Cable: Sensor/actuator cable, PUR, halogen-free, unshielded, 20 m                                                                                                                           | DOL-1208G20MD25KM1                                      | 2092105  |
|                                                                                    | Head A: female connector, M12, 8-pin, straight, A-coded<br>Head B: Flying leads<br>Cable: Sensor/actuator cable, PUR, halogen-free, unshielded, 30 m                                                                                                                           | DOL-1208G30MD25KM1                                      | 2092106  |
|                                                                                    | Head A: male connector, USB-A, straight<br>Head B: male connector, Mini-USB, straight<br>Cable: USB, shielded, 3 m<br>For connecting the configuration connection to the USB interface on the PC                                                                               | Connection cable<br>(male connector-<br>male connector) | 6042517  |
|                                                                                    | Head A: male connector, USB-A, straight<br>Head B: male connector, Mini-USB, straight<br>Cable: USB, shielded, 5 m<br>For connecting the configuration connection to the USB interface on the PC                                                                               | Connection cable<br>(male connector-<br>male connector) | 6053566  |

## SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

**For us, that is “Sensor Intelligence.”**

## WORLDWIDE PRESENCE:

Contacts and other locations –[www.sick.com](http://www.sick.com)