



# ARS60-J1T00360

ARS60 SSI/Parallel

**ABSOLUTE ENCODERS**

**SICK**  
Sensor Intelligence.




Illustration may differ



## Ordering information

| Type           | Part no. |
|----------------|----------|
| ARS60-J1T00360 | 1213102  |

Other models and accessories → [www.sick.com/ARS60\\_SSI\\_Parallel](http://www.sick.com/ARS60_SSI_Parallel)

## Detailed technical data

## Performance

|                                                               |                                                                                      |
|---------------------------------------------------------------|--------------------------------------------------------------------------------------|
| <b>Number of steps per revolution (max. resolution)</b>       | 360                                                                                  |
| <b>Error limits G</b>                                         | 0.035° (binary number of steps) <sup>1)</sup><br>0.046° (non-binary number of steps) |
| <b>Repeatability standard deviation <math>\sigma_r</math></b> | 0.005° <sup>2)</sup>                                                                 |

<sup>1)</sup> In accordance with DIN ISO 1319-1, position of the upper and lower error limit depends on the installation situation, specified value refers to a symmetrical position, i.e. deviation in upper and lower direction is the same.

<sup>2)</sup> In accordance with DIN ISO 55350-13; 68.3% of the measured values are inside the specified area.

## Interfaces

|                                    |                                                                                                                                                                                      |
|------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Communication interface</b>     | Parallel data word                                                                                                                                                                   |
| <b>Initialization time</b>         | 80 ms <sup>1)</sup>                                                                                                                                                                  |
| <b>SSI</b>                         |                                                                                                                                                                                      |
| Code type                          | BCD                                                                                                                                                                                  |
| Code sequence parameter adjustable | CW (clockwise) increasing when viewing the clockwise rotating shaft<br>Increasing, when turning the shaft For clockwise rotation, looking in direction "A" (see dimensional drawing) |

<sup>1)</sup> Valid positional data can be read once this time has elapsed.

## Electrical data

|                                              |                                          |
|----------------------------------------------|------------------------------------------|
| <b>Connection type</b>                       | Cable, 22-wire, axial, 5 m               |
| <b>Supply voltage</b>                        | 10 ... 32 V DC                           |
| <b>Reverse polarity protection</b>           | ✓                                        |
| <b>Short-circuit protection</b>              | ✓                                        |
| <b>MTTFd: mean time to dangerous failure</b> | 300 years (EN ISO 13849-1) <sup>1)</sup> |

<sup>1)</sup> This product is a standard product and does not constitute a safety component as defined in the Machinery Directive. Calculation based on nominal load of components, average ambient temperature 40 °C, frequency of use 8760 h/a. All electronic failures are considered hazardous. For more information, see document no. 8015532.

## Mechanical data

|                          |                           |
|--------------------------|---------------------------|
| <b>Mechanical design</b> | Solid shaft, Servo flange |
| <b>Shaft diameter</b>    | 6 mm                      |
| <b>Wavelength</b>        | 10 mm                     |

|                                           |                                                                                            |
|-------------------------------------------|--------------------------------------------------------------------------------------------|
| <b>Housing material</b>                   | Aluminum die cast                                                                          |
| <b>Start up torque</b>                    | 0.25 Ncm                                                                                   |
| <b>Operating torque</b>                   | 0.2 Ncm                                                                                    |
| <b>Permissible Load capacity of shaft</b> | 20 N / radial<br>10 N / axial                                                              |
| <b>Moment of inertia of the rotor</b>     | 48 gcm <sup>2</sup>                                                                        |
| <b>Bearing lifetime</b>                   | 3.6 x 10 <sup>9</sup> revolutions                                                          |
| <b>Angular acceleration</b>               | ≤ 500,000 rad/s <sup>2</sup>                                                               |
| <b>Operating speed</b>                    | ≤ 6,000 min <sup>-1</sup> with shaft seal<br>≤ 10,000 min <sup>-1</sup> without shaft seal |

#### Ambient data

|                                      |                                                           |
|--------------------------------------|-----------------------------------------------------------|
| <b>EMC</b>                           | According to EN 61000-6-2 and EN 61000-6-3 <sup>1)</sup>  |
| <b>Enclosure rating</b>              | IP66 (according to IEC 60529)                             |
| <b>Permissible relative humidity</b> | 90 % (condensation of the optical scanning not permitted) |
| <b>Operating temperature range</b>   | -20 °C ... +85 °C                                         |
| <b>Storage temperature range</b>     | -40 °C ... +100 °C                                        |
| <b>Resistance to shocks</b>          | 50 g, 11 ms (according to EN 60068-2-27)                  |
| <b>Resistance to vibration</b>       | 20 g, 10 Hz ... 2,000 Hz (according to EN 60068-2-6)      |


<sup>1)</sup> EMC according to the standards quoted is achieved if shielded cables are used.

#### Classifications

|                       |          |
|-----------------------|----------|
| <b>ECI@ss 5.0</b>     | 27270502 |
| <b>ECI@ss 5.1.4</b>   | 27270502 |
| <b>ECI@ss 6.0</b>     | 27270590 |
| <b>ECI@ss 6.2</b>     | 27270590 |
| <b>ECI@ss 7.0</b>     | 27270502 |
| <b>ECI@ss 8.0</b>     | 27270502 |
| <b>ECI@ss 8.1</b>     | 27270502 |
| <b>ECI@ss 9.0</b>     | 27270502 |
| <b>ECI@ss 10.0</b>    | 27270502 |
| <b>ECI@ss 11.0</b>    | 27270502 |
| <b>ETIM 5.0</b>       | EC001486 |
| <b>ETIM 6.0</b>       | EC001486 |
| <b>ETIM 7.0</b>       | EC001486 |
| <b>UNSPSC 16.0901</b> | 41112113 |

### Dimensional drawing (Dimensions in mm (inch))

Servo flange, cable connection



General tolerances according to DIN ISO 2768-mk

① R = min. bending radius 40 mm

### Recommended accessories

Other models and accessories → [www.sick.com/ARS60\\_SSI\\_Parallel](http://www.sick.com/ARS60_SSI_Parallel)

|                            | Brief description                                                                                                                                                                                                                                                                                 | Type         | Part no. |
|----------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|----------|
| Other mounting accessories |                                                                                                                                                                                                                                                                                                   |              |          |
|                            | Mounting bell for encoder with servo flange, 50 mm spigot, mounting kit included                                                                                                                                                                                                                  | BEF-MG-50    | 5312987  |
|                            | Half-shell servo clamps (2 pcs.) for servo flanges with a 50 mm centering hub                                                                                                                                                                                                                     | BEF-WG-SF050 | 2029165  |
|                            | Servo clamps, large, for servo flanges (clamps, eccentric fastener), 3 pcs., without mounting material, without mounting hardware                                                                                                                                                                 | BEF-WK-SF    | 2029166  |
| Shaft adaptation           |                                                                                                                                                                                                                                                                                                   |              |          |
|                            | Bellows coupling, shaft diameter 6 mm / 6 mm, maximum shaft offset: radial ± 0.25 mm, axial ± 0.4 mm, angular +/- 4°; max. speed 10,000 rpm, -30 °C to +120 °C, max. torque 80 Ncm; material: stainless steel bellows, aluminum hub                                                               | KUP-0606-B   | 5312981  |
|                            | Bellows coupling, shaft diameter 6 mm / 10 mm, maximum shaft offset: radial ± 0.25 mm, axial ± 0.4 mm, angular +/- 4°; max. speed 10,000 rpm, -30 °C to +120 °C, max. torque 80 Ncm; material: stainless steel bellows, aluminum hub                                                              | KUP-0610-B   | 5312982  |
|                            | Spring washer coupling, shaft diameter 6 mm / 10 mm, Maximum shaft offset: radial +/- 0.3 mm, axial +/- 0.4 mm, angular +/- 2.5°; max. speed 12,000 rpm, -10° to +80 °C, max. torque 60 Ncm; material: aluminum flange, glass fiber-reinforced polyamide membrane and hardened steel coupling pin | KUP-0610-F   | 5312985  |

|                                                                                   | Brief description                                                                     | Type        | Part no. |
|-----------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|-------------|----------|
| Plug connectors and cables                                                        |                                                                                       |             |          |
|  | Head A: cable<br>Head B: Flying leads<br>Cable: parallel, PUR, halogen-free, shielded | LTG-2622-MW | 6027532  |

## SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

**For us, that is “Sensor Intelligence.”**

## WORLDWIDE PRESENCE:

Contacts and other locations –[www.sick.com](http://www.sick.com)