

LL3-TV0510000

LL3

FIBERS





Ordering information

Туре	Part no.
LL3-TV0510000	5337026

Other models and accessories → www.sick.com/LL3

Detailed technical data

Features

Device type	Fibers
Detection principle	Through-beam system (consisting of a sender and a receiver)
For fiber-optic sensor	GLL170(T), WLL180T
Fiber length	10,000 mm
Fiber material	Polymethylmethacrylat (PMMA)
Jacket material	Polyethylen (PE)
Fiber head material	PA
Outer diameter, fiber-optic cable connection	2.2 mm
Fiber-optic cable cuttable	✓ ¹)
Fiber-optic head design	Threaded sleeve, 90° deflection
Core structure	Ø 1 mm
Bend radius, fibre-optic cable	25 mm
Ambient operating temperature	-40 °C +70 °C
Minimal object diameter	0.4 mm ²⁾
Included with delivery	Mounting, 2 x M4 hexagon nut, FC fiber cutter (5304141)
Special features	90° deflection integrated, maximum sensing range
Core structure Bend radius, fibre-optic cable Ambient operating temperature Minimal object diameter Included with delivery	Ø 1 mm 25 mm -40 °C +70 °C 0.4 mm ²⁾ Mounting, 2 x M4 hexagon nut, FC fiber cutter (5304141)

 $^{^{1)}}$ FC fiber optic cable cutter included in delivery.

Mechanics/electronics

Bend radius, fibre-optic cable	25 mm
Ambient operating temperature	-40 °C +70 °C

Classifications

ECI@ss 5.0	27270905
ECI@ss 5.1.4	27270905
ECI@ss 6.0	27270905
ECI@ss 6.2	27270905
ECI@ss 7.0	27270905
ECI@ss 8.0	27270905
ECI@ss 8.1	27270905
ECI@ss 9.0	27270905

 $^{^{2)}}$ Minimum detectable object was determined at optimum measuring distance and optimum setting.

ECI@ss 10.0	27270905
ECI@ss 11.0	27270905
ETIM 5.0	EC002651
ETIM 6.0	EC002651
ETIM 7.0	EC002651
UNSPSC 16.0901	39121528

Sensing ranges with WLL180T

Operating mode 16 μs	228 mm
Operating mode 70 µs	489 mm
Operating mode 250 µs	1,174 mm
Operating mode 2 ms	2,900 mm
Operating mode 8 ms	3,400 mm


Sensing ranges with GLL170

Operating mode 250 µs	410 m
-----------------------	-------

Sensing ranges with GLL170T

Operating mode 50 µs	400 mm
Operating mode 250 µs	910 mm

Dimensional drawing (Dimensions in mm (inch))



SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is "Sensor Intelligence."

WORLDWIDE PRESENCE:

Contacts and other locations -www.sick.com

