





LL3-TW014000S05

LL3

FIBERS

SICK
Sensor Intelligence.



Ordering information

Type	Part no.
LL3-TW014000S05	5337906

Other models and accessories → www.sick.com/LL3

Detailed technical data

Features

Device type	Fibers
Detection principle	Through-beam system
For fiber-optic sensor	GLL170(T), WLL180T
Fiber length	4,000 mm
Fiber material	Glass
Jacket material	Stainless steel
Fiber head material	Stainless steel
Outer diameter, fiber-optic cable connection	2.2 mm
Thread diameter (housing)	M4
Fiber-optic head design	Threaded sleeve
Fiber arrangement	Multi-fiber – fiber bundle
Core structure	Ø 1.5 mm (multi-fiber) Multi-fiber – fiber bundle
Bend radius, fibre-optic cable	25 mm
Angle of dispersion < 60°	No
Compatibility with infrared light (1,450 nm)	Yes
Ambient operating temperature	–60 °C ... +210 °C
Application	Heat-resistant (≥100 °C)
Diameter/thread size from 2 mm taper	≥ 2.6 mm
Length of taper	≥ 3 mm
Highly flexible/elastic fibers (bend radius 1–4 mm)	No
Adapter end sleeves required	No
Angle of dispersion	60°
Integrated lens	No
Minimal object diameter	0.4 mm ¹⁾
Included with delivery	Mounting, 4 x M4 hexagon nut, 2 x washer
Compatibility tip adapters	Yes
Special features	Packaging unit: 1 arm

¹⁾ Minimum detectable object was determined at optimum measuring distance and optimum setting.

Mechanics/electronics

Bend radius, fibre-optic cable	25 mm
---------------------------------------	-------

Ambient operating temperature	-60 °C ... +210 °C
--------------------------------------	--------------------

Classifications

ECI@ss 5.0	27270905
ECI@ss 5.1.4	27270905
ECI@ss 6.0	27270905
ECI@ss 6.2	27270905
ECI@ss 7.0	27270905
ECI@ss 8.0	27270905
ECI@ss 8.1	27270905
ECI@ss 9.0	27270905
ECI@ss 10.0	27270905
ECI@ss 11.0	27270905
ETIM 5.0	EC002651
ETIM 6.0	EC002651
ETIM 7.0	EC002651
UNSPSC 16.0901	39121528

Sensing ranges with WLL180T

Operating mode 16 µs	80 mm
Operating mode 70 µs	230 mm
Operating mode 250 µs	350 mm
Operating mode 2 ms	560 mm
Operating mode 8 ms	980 mm


Sensing ranges with GLL170

Operating mode 250 µs	534 mm
------------------------------	--------

Sensing ranges with GLL170T

Operating mode 50 µs	821 mm
Operating mode 250 µs	1,393 mm

Dimensional drawing (Dimensions in mm (inch))



SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is “Sensor Intelligence.”

WORLDWIDE PRESENCE:

Contacts and other locations –www.sick.com