




LL3-DM04

LL3

FIBERS

SICK
Sensor Intelligence.



Ordering information

Type	Part no.
LL3-DM04	5337948

Other models and accessories → www.sick.com/LL3

Detailed technical data

Features

Device type	Fibers
Detection principle	Proximity system
For fiber-optic sensor	GLL170(T), WLL180T
Fiber length	2,000 mm
Fiber material	Polymethylmethacrylat (PMMA)
Jacket material	Polyethylen (PE)
Fiber head material	Stainless steel ¹⁾
Outer diameter, fiber-optic cable connection	1 mm
Fiber-optic cable cuttable	✓ ²⁾
Thread diameter (housing)	M3
Fiber-optic head design	Threaded sleeve, Long end sleeve, Bendable sleeve
Fiber arrangement	Monofiber
Core structure	2 x Ø 0,5 mm ³⁾ Monofiber
Bend radius, fibre-optic cable	15 mm
Angle of dispersion < 60°	No
Compatibility with infrared light (1,450 nm)	No
Ambient operating temperature	-55 °C ... +70 °C
Length of taper	≥ 90 mm
Diameter of taper	≥ 1.5 mm
Highly flexible/elastic fibers (bend radius 1–4 mm)	No
Adapter end sleeves required	Yes
Angle of dispersion	60°
Integrated lens	No
Minimal object diameter	0.015 mm ⁴⁾
Included with delivery	Mounting, 2 x M3 hexagon nut, 2 x washer, adapter sleeves, FC fiber cutter
Compatibility tip adapters	No

¹⁾ Stainless steel.

²⁾ FC fiber optic cable cutter included in delivery.

³⁾ C = Coaxial, S = Sender, E = Receiver.

⁴⁾ Minimum detectable object was determined at optimum measuring distance and optimum setting.

Special features	Ideal for small, insufficient objects. Compact head, bendable sleeve
-------------------------	--

- 1) Stainless steel.
2) FC fiber optic cable cutter included in delivery.
3) C = Coaxial, S = Sender, E = Receiver.
4) Minimum detectable object was determined at optimum measuring distance and optimum setting.

Mechanics/electronics

Bend radius, fibre-optic cable	15 mm
Ambient operating temperature	-55 °C ... +70 °C

Classifications

ECI@ss 5.0	27270905
ECI@ss 5.1.4	27270905
ECI@ss 6.0	27270905
ECI@ss 6.2	27270905
ECI@ss 7.0	27270905
ECI@ss 8.0	27270905
ECI@ss 8.1	27270905
ECI@ss 9.0	27270905
ECI@ss 10.0	27270905
ECI@ss 11.0	27270905
ETIM 5.0	EC002651
ETIM 6.0	EC002651
ETIM 7.0	EC002651
UNSPSC 16.0901	39121528

Sensing ranges with WLL180T

Operating mode 16 µs	30 mm
Operating mode 70 µs	90 mm
Operating mode 250 µs	125 mm
Operating mode 2 ms	300 mm
Operating mode 8 ms	380 mm


Sensing ranges with GLL170

Operating mode 250 µs	60 mm
------------------------------	-------

Sensing ranges with GLL170T

Operating mode 50 µs	35 mm
Operating mode 250 µs	70 mm

Dimensional drawing (Dimensions in mm (inch))



- ① Protective pipe
- ② Bendable area
- ③ Do not bend area, do not bend sleeve in this area

SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is “Sensor Intelligence.”

WORLDWIDE PRESENCE:

Contacts and other locations –www.sick.com