



# WL100-2P3429

## W100-2

MINIATURE PHOTOELECTRIC SENSORS

**SICK**  
Sensor Intelligence.



Illustration may differ



### Ordering information

| Type         | Part no. |
|--------------|----------|
| WL100-2P3429 | 6052385  |

**Included in delivery:** P250 (1), BEF-W100-A (1)

Other models and accessories → [www.sick.com/W100-2](http://www.sick.com/W100-2)

### Detailed technical data

#### Features

|                                        |                                                  |
|----------------------------------------|--------------------------------------------------|
| <b>Sensor/ detection principle</b>     | Photoelectric retro-reflective sensor, Dual lens |
| <b>Dimensions (W x H x D)</b>          | 11 mm x 31 mm x 20 mm                            |
| <b>Housing design (light emission)</b> | Rectangular                                      |
| <b>Sensing range max.</b>              | 0.01 m ... 3 m <sup>1)</sup>                     |
| <b>Sensing range</b>                   | 0.01 m ... 2.5 m <sup>1)</sup>                   |
| <b>Type of light</b>                   | Visible red light                                |
| <b>Light source</b>                    | LED <sup>2)</sup>                                |
| <b>Light spot size (distance)</b>      | Ø 140 mm (2 m)                                   |
| <b>Wave length</b>                     | 632 nm                                           |
| <b>Adjustment</b>                      | Potentiometer (Sensitivity)                      |
| <b>Special applications</b>            | Detecting transparent objects                    |
| <b>Special features</b>                | Detecting transparent objects                    |

<sup>1)</sup> Reflector PL80A.

<sup>2)</sup> Average service life: 100,000 h at T<sub>U</sub> = +25 °C.

#### Mechanics/electronics

|                       |                                   |
|-----------------------|-----------------------------------|
| <b>Supply voltage</b> | 10 V DC ... 30 V DC <sup>1)</sup> |
| <b>Ripple</b>         | ± 10 % <sup>2)</sup>              |

<sup>1)</sup> Limit values.

<sup>2)</sup> May not exceed or fall below U<sub>v</sub> tolerances.

<sup>3)</sup> Without load.

<sup>4)</sup> Signal transit time with resistive load.

<sup>5)</sup> With light/dark ratio 1:1.

<sup>6)</sup> A = V<sub>S</sub> connections reverse-polarity protected.

<sup>7)</sup> B = output reverse-polarity protected.

<sup>8)</sup> D = outputs overcurrent and short-circuit protected.

|                                       |                                                       |
|---------------------------------------|-------------------------------------------------------|
| <b>Current consumption</b>            | 30 mA <sup>3)</sup>                                   |
| <b>Switching output</b>               | PNP                                                   |
| <b>Switching mode</b>                 | Light/dark switching                                  |
| <b>Switching mode selector</b>        | Selectable via light/dark rotary switch               |
| <b>Signal voltage PNP HIGH/LOW</b>    | U <sub>V</sub> - 1,8 V / ca. 0 V                      |
| <b>Output current I<sub>max</sub></b> | 100 mA                                                |
| <b>Response time</b>                  | ≤ 0.5 ms <sup>4)</sup>                                |
| <b>Switching frequency</b>            | 1,000 Hz <sup>5)</sup>                                |
| <b>Attenuation along light beam</b>   | ≥ 20 %                                                |
| <b>Connection type</b>                | Connector M8, 3-pin                                   |
| <b>Circuit protection</b>             | A <sup>6)</sup><br>B <sup>7)</sup><br>D <sup>8)</sup> |
| <b>Protection class</b>               | III                                                   |
| <b>Housing material</b>               | Plastic, ABS/PC/POM                                   |
| <b>Optics material</b>                | Plastic, PMMA                                         |
| <b>Enclosure rating</b>               | IP67                                                  |
| <b>Items supplied</b>                 | Mounting bracket BEF-W100-A, Reflector P250           |
| <b>Special feature</b>                | Detecting transparent objects                         |
| <b>Ambient operating temperature</b>  | -25 °C ... +55 °C                                     |
| <b>Ambient storage temperature</b>    | -40 °C ... +70 °C                                     |

1) Limit values.

2) May not exceed or fall below U<sub>V</sub> tolerances.

3) Without load.

4) Signal transit time with resistive load.

5) With light/dark ratio 1:1.

6) A = V<sub>S</sub> connections reverse-polarity protected.

7) B = output reverse-polarity protected.

8) D = outputs overcurrent and short-circuit protected.

## Safety-related parameters

|                         |           |
|-------------------------|-----------|
| <b>MTTF<sub>D</sub></b> | 954 years |
| <b>DC<sub>avg</sub></b> | 0%        |


## Classifications

|                     |          |
|---------------------|----------|
| <b>ECI@ss 5.0</b>   | 27270902 |
| <b>ECI@ss 5.1.4</b> | 27270902 |
| <b>ECI@ss 6.0</b>   | 27270902 |
| <b>ECI@ss 6.2</b>   | 27270902 |
| <b>ECI@ss 7.0</b>   | 27270902 |
| <b>ECI@ss 8.0</b>   | 27270902 |
| <b>ECI@ss 8.1</b>   | 27270902 |
| <b>ECI@ss 9.0</b>   | 27270902 |
| <b>ECI@ss 10.0</b>  | 27270902 |

|                |          |
|----------------|----------|
| ECI@ss 11.0    | 27270902 |
| ETIM 5.0       | EC002717 |
| ETIM 6.0       | EC002717 |
| ETIM 7.0       | EC002717 |
| UNSPSC 16.0901 | 39121528 |

Connection diagram


Cd-045



Characteristic curve

WL100-2, clear material detection


Function reserve



- ① Reflector PL80A
- ② Reflector P250
- ③ Diamond Grade reflective tape, 100 mm x 100 mm


Light spot size

Light spot size



Sensing range diagram

WL100, 3 m




■ Sensing range ■ Sensing range max.

\*Close-up range at maximum sensitivity

- ① Reflector PL80A
- ② Reflector P250
- ③ Reflector PL50A, PL40A
- ④ Reflector PL30A, PL31A
- ⑤ Reflector PL20A
- ⑥ Reflective tape Diamond Grade
- ⑦ P45

## Adjustments

W100-2



- ① LED indicator orange: switching output active
- ② LED indicator green: power on
- ③ Sensing range adjustment: potentiometer
- ④ Light/ dark rotary switch: L = light switching, D = dark switching

## Recommended accessories

Other models and accessories → [www.sick.com/W100-2](http://www.sick.com/W100-2)

|                                                                                     | Brief description                                                                                                                    | Type               | Part no. |
|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------|--------------------|----------|
| Mounting brackets and plates                                                        |                                                                                                                                      |                    |          |
|  | Mounting bracket for wall mounting, stainless steel, mounting hardware included                                                      | BEF-W100-A         | 5311520  |
|  | Mounting bracket for floor mounting, steel, zinc coated, mounting hardware included                                                  | BEF-W100-B         | 5311521  |
|  | Universal mounting bracket for reflectors, steel, zinc coated                                                                        | BEF-WN-REFX        | 2064574  |
| Reflectors                                                                          |                                                                                                                                      |                    |          |
|  | Rectangular, screw connection, 51 mm x 61 mm, PMMA/ABS, Screw-on, 2 hole mounting                                                    | P250               | 5304812  |
| Plug connectors and cables                                                          |                                                                                                                                      |                    |          |
|  | Head A: female connector, M8, 3-pin, straight, A-coded<br>Head B: Flying leads<br>Cable: Sensor/actuator cable, PVC, unshielded, 5 m | YF8U13-050VA1XLEAX | 2095884  |
|  | Head A: male connector, M8, 3-pin, straight<br>Head B: -<br>Cable: unshielded                                                        | STE-0803-G         | 6037322  |

## SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

**For us, that is “Sensor Intelligence.”**

## WORLDWIDE PRESENCE:

Contacts and other locations –[www.sick.com](http://www.sick.com)