





## Absolute encoders ATM90 PROFIBUS

ATM90-PXG11X13



**Model Name** > ATM90-PXG11X13  
**Part No.** > 1032901



*Illustration may differ*

#### At a glance

- Extremely rugged, tried-and-tested absolute multiturn encoder with a resolution of up to 26 bits
- Mechanical interface: through hollow shaft with shallow installation depth
- Zero-set and preset functions via hardware or software
- No battery required
- Electrical interface: PROFIBUS DP as per IEC61158 / RS -485 , electrically isolated
- Electronically adjustable, configurable resolution
- Magnetic scanning

#### Your benefits

- Fewer variants are required since one freely programmable encoder offers all singleturn and multiturn resolutions
- Easy setup due to various electrical connection adapters (cable, M23)
- Application flexibility due to easily interchangeable collets for the blind hollow shaft
- Quick commissioning using the zero set/preset function either at the press of the button on the device or via software
- Increased productivity due to highly reliable shock and vibration resistance
- Worldwide availability and service ensure quick and reliable customer service



#### Performance

|                                      |                        |
|--------------------------------------|------------------------|
| Max. number of steps per revolution: | 2,048                  |
| Max. number of revolutions:          | 8,192                  |
| Resolution power:                    | 2,048 x 8,192          |
| Resolution:                          | 11 bit x 13 bit        |
| Error limits:                        | $\pm 0.25^\circ$       |
| Repeatability (Ta not constant):     | $0.1^\circ$            |
| Measuring step:                      | $0.043^\circ$          |
| Initialization time:                 | 1,250 ms <sup>1)</sup> |

<sup>1)</sup> Valid positional data can be read once this time has elapsed

#### Mechanical data

|                       |                      |
|-----------------------|----------------------|
| Mechanical interface: | Through hollow shaft |
| Shaft diameter:       | 16 mm                |
| Mass:                 | 0.8 kg               |

|                                 |                                   |
|---------------------------------|-----------------------------------|
| Start up torque:                | 0.5 Ncm                           |
| Operating torque:               | 0.4 Ncm                           |
| Moment of inertia of the rotor: | 153 gcm <sup>2</sup>              |
| Bearing lifetime:               | 3.6 x 10 <sup>9</sup> revolutions |
| Max. angular acceleration:      | 600,000 rad/s <sup>2</sup>        |
| Shaft material:                 | Stainless steel                   |
| Flange material:                | Aluminum                          |
| Housing material:               | Die-cast aluminum                 |

## Electrical data

---

|                                        |                                      |
|----------------------------------------|--------------------------------------|
| Operating voltage range:               | 10 V ... 32 V                        |
| Power consumption max.:                | 2 W                                  |
| MTTFd: mean time to dangerous failure: | 150 a (EN ISO 13849-1) <sup>1)</sup> |

<sup>1)</sup> This product is a standard product and does not constitute a safety component as defined in the Machinery Directive.

Calculation based on nominal load of components, average ambient

temperature 40°C, frequency of use 8760 h/a. All

electronic failures are considered hazardous. For more information, see document no. 8015532.

## Interfaces

---

|                                     |                                                  |
|-------------------------------------|--------------------------------------------------|
| Electrical interface:               | Bus adaptor with 3 cable screw fixings           |
| SET (electronic adjustment):        | Via PRESET push button or protocol               |
| Bus:                                | Profibus DP                                      |
| Bus interface:::                    | RS-485 <sup>1)</sup> <sup>2)</sup> <sup>3)</sup> |
| Data protocol:                      | Profile for encoders (07hex) - Class 2           |
| Address setting:                    | 0 ... 127, DIP-switches or protocol              |
| Data transmission rate (baud rate): | 9.6 kBaud / 12 MBaud / automatic detection       |
| Status information:                 | LED green (operation), LED red ( bus activity)   |
| Bus termination:                    | DIP switch                                       |

<sup>1)</sup> EN 50 170-2 <sup>2)</sup> DIN 19245 part 1-3 <sup>3)</sup> DC isolated via opto-couplers

## Ambient data

---

|                                |                                                 |
|--------------------------------|-------------------------------------------------|
| EMC:                           | (according to EN 61000-6-2 and EN 61000-6-3)    |
| Enclosure rating:              | IP 65 (according to IEC 60529), with shaft seal |
| Permissible relative humidity: | 98 %                                            |
| Working temperature range:     | -20 °C ... 80 °C                                |
| Storage temperature range:     | -40 °C ... 125 °C, without package              |
| Resistance to shocks:          | 6 g (according to EN 60068-2-27)                |
| Resistance to vibration:       | 20 g, 10 Hz ... 2,000 Hz                        |



#### **Australia**

Phone +61 3 9457 0600  
1800 334 802 – tollfree  
E-Mail sales@sick.com.au

#### **Belgium/Luxembourg**

Phone +32 (0)2 466 55 66  
E-Mail info@sick.be

#### **Brasil**

Phone +55 11 3215-4900  
E-Mail sac@sick.com.br

#### **Canada**

Phone +1 905 771 14 44  
E-Mail information@sick.com

#### **Ceská Republika**

Phone +420 2 57 91 18 50  
E-Mail sick@sick.cz

#### **China**

Phone +86 4000 121 000  
E-Mail info.china@sick.net.cn  
Phone +852-2153 6300  
E-Mail ghk@sick.com.hk

#### **Danmark**

Phone +45 45 82 64 00  
E-Mail sick@sick.dk

#### **Deutschland**

Phone +49 211 5301-301  
E-Mail kundenservice@sick.de

#### **España**

Phone +34 93 480 31 00  
E-Mail info@sick.es

#### **France**

Phone +33 1 64 62 35 00  
E-Mail info@sick.fr

#### **Great Britain**

Phone +44 (0)1727 831121  
E-Mail info@sick.co.uk

#### **India**

Phone +91-22-4033 8333  
E-Mail info@sick-india.com

#### **Israel**

Phone +972-4-6801000  
E-Mail info@sick-sensors.com

#### **Italia**

Phone +39 02 27 43 41  
E-Mail info@sick.it

#### **Japan**

Phone +81 (0)3 3358 1341  
E-Mail support@sick.jp

#### **Magyarország**

Phone +36 1 371 2680  
E-Mail office@sick.hu

#### **Nederlands**

Phone +31 (0)30 229 25 44  
E-Mail info@sick.nl

#### **Norge**

Phone +47 67 81 50 00  
E-Mail austefjord@sick.no

#### **Österreich**

Phone +43 (0)22 36 62 28 8-0  
E-Mail office@sick.at

#### **Polska**

Phone +48 22 837 40 50  
E-Mail info@sick.pl

#### **România**

Phone +40 356 171 120  
E-Mail office@sick.ro

#### **Russia**

Phone +7-495-775-05-30  
E-Mail info@sick.ru

#### **Schweiz**

Phone +41 41 619 29 39  
E-Mail contact@sick.ch

#### **Singapore**

Phone +65 6744 3732  
E-Mail admin@sicksgp.com.sg

#### **Slovenija**

Phone +386 (0)1-47 69 990  
E-Mail office@sick.si

#### **South Africa**

Phone +27 11 472 3733  
E-Mail info@sickautomation.co.za

#### **South Korea**

Phone +82 2 786 6321/4  
E-Mail info@sickkorea.net

#### **Suomi**

Phone +358-9-25 15 800  
E-Mail sick@sick.fi

#### **Sverige**

Phone +46 10 110 10 00  
E-Mail info@sick.se

#### **Taiwan**

Phone +886-2-2375-6288  
E-Mail sales@sick.com.tw

#### **Türkiye**

Phone +90 (216) 528 50 00  
E-Mail info@sick.com.tr

#### **United Arab Emirates**

Phone +971 (0) 4 8865 878  
E-Mail info@sick.ae

#### **USA/México**

Phone +1(952) 941-6780  
1 800-325-7425 – tollfree  
E-Mail info@sickusa.com

More representatives and agencies  
at [www.sick.com](http://www.sick.com)