



## Long range distance sensors DME4000, RS-422

DME4000-313



**Model Name** > [DME4000-313](#)  
**Part No.** > [1041952](#)




#### At a glance

- Multiple measurement and positioning options from 0.15 m to 220 m
- High-speed output rate
- Very high resolution, repeatability and accuracy
- Illuminated LC display with measured value output and setup diagnostic information
- Visible red light and bracket with springs for alignment
- Variety of interfaces: SSI, RS-422, PROFIBUS, HIPERFACE, CANopen, DeviceNet

#### Your benefits

- Fast measurement cycles offer optimized integration into control loops for increased productivity
- Red laser light as well as adjustable mounting brackets (optional accessory) enable fast and easy alignment, ensuring on-time and cost-effective installation
- Multi-point self checks provide maintenance and replacement warnings increasing overall machine availability
- A tough metal housing as well as heating and cooling accessories ensure reliability in rough ambient conditions
- User-friendly display with easy-to-use menu along with external PC/PLC programming offers fast and cost-efficient setup
- Multiple serial interfaces provide high-speed position output to the controller and high flexibility in application integration
- Integrated speed monitoring offers additional information for increased process reliability



CE **CDRH RS-422**

#### Performance

|                                               |                                                            |
|-----------------------------------------------|------------------------------------------------------------|
| Measuring range:                              | 0.15 m ... 220 m, on Diamond Grade                         |
| Resolution:                                   | 0.05 mm ... 5 mm                                           |
| Repeatability <sup>1)</sup> ; <sup>2)</sup> : | 3 mm                                                       |
| Accuracy:                                     | ± 6 mm                                                     |
| Light source <sup>3)</sup> :                  | Laser, red                                                 |
| Laser protection class:                       | 2 (EN 60825-1/CDRH)                                        |
| Typ. light spot size (distance):              | 130 mm (at 70 m)<br>270 mm (at 150 m)<br>360 mm (at 220 m) |
| Output rate:                                  | 2 ms                                                       |
| Max. movement speed:                          | 10 m/s                                                     |

1) On Diamond Grade 2) Statistical error 1  $\sigma$ , environmental conditions constant, min. warm-up time 10 min 3) Average service life of 50,000 h at  $T_A = +25^\circ\text{C}$

## Interfaces

Data interface: RS-422  
 Output type <sup>1)</sup>: Push-pull: PNP/NPN (100 mA)  
 Multifunctional input <sup>2)</sup>, <sup>3)</sup>: 1 x MF

<sup>1)</sup> HIGH =  $> V_S - 3\text{ V}$  / LOW =  $< 2\text{ V}$  <sup>2)</sup> HIGH =  $> 12\text{ V}$  / LOW =  $< 3\text{ V}$  <sup>3)</sup> Not reverse-polarity protected

## Mechanics/electronics

Supply voltage  $V_S$ : DC 18 V ... 30 V, limit values  
 Ripple <sup>1)</sup>:  $< 5\text{ Vpp}$   
 Initialization time <sup>2)</sup>: 1.5 s  
 Indication: Display  
 Weight: Ca. 1,650 g  
 Output current  $I_A$  <sup>3)</sup>:  $\leq 100\text{ mA}$   
 Power consumption: At 24 V DC  $< 250\text{ mA}$   
 Connection type: Connector M16, 8-pin


<sup>1)</sup> May not fall short of or exceed  $V_S$  tolerances <sup>2)</sup> After loss of reflector  $< 1\text{ s}$  at max. speed  $V_{\text{max}} < 1\text{ m/s}$  <sup>3)</sup> Short circuit/overload protected. Max. 100 nF/20 mH

## Ambient data

Enclosure rating: IP 65  
 Protection class <sup>1)</sup>: II  
 EMC: EN 61000-6-2, EN 55011: Class B  
 Effect of air pressure: 0.3 ppm/hPa  
 Effect of air temperature: 1 ppm/K  
 Temperature drift: Typ. 0.1 mm/K  
 Ambient temperature: Operation:  $-10 \dots 55^\circ\text{C}$   
 Operation with cooling case:  $-10 \dots 75^\circ\text{C}$   
 Storage:  $-25 \dots 75^\circ\text{C}$   
 Mechanical load: Noise: EN 600 68-2-64  
 Shock: EN 600 68-2-27/-2-29  
 Sine: EN 600 68-2-6


<sup>1)</sup> Reference voltage DC 32 V

Dimensional drawing



All dimensions in mm (inch)


Adjustments



Connection type



Connection diagram



[1] Connector M16, 8-pin

**Australia**

Phone +61 3 9457 0600  
1800 334 802 – tollfree  
E-Mail sales@sick.com.au

**Belgium/Luxembourg**

Phone +32 (0)2 466 55 66  
E-Mail info@sick.be

**Brasil**

Phone +55 11 3215-4900  
E-Mail sac@sick.com.br

**Canada**

Phone +1 905 771 14 44  
E-Mail information@sick.com

**Ceská Republika**

Phone +420 2 57 91 18 50  
E-Mail sick@sick.cz

**China**

Phone +86 4000 121 000  
E-Mail info.china@sick.net.cn  
Phone +852-2153 6300  
E-Mail ghk@sick.com.hk

**Danmark**

Phone +45 45 82 64 00  
E-Mail sick@sick.dk

**Deutschland**

Phone +49 211 5301-301  
E-Mail kundenservice@sick.de

**España**

Phone +34 93 480 31 00  
E-Mail info@sick.es

**France**

Phone +33 1 64 62 35 00  
E-Mail info@sick.fr

**Great Britain**

Phone +44 (0)1727 831121  
E-Mail info@sick.co.uk

**India**

Phone +91-22-4033 8333  
E-Mail info@sick-india.com

**Israel**

Phone +972-4-6801000  
E-Mail info@sick-sensors.com

**Italia**

Phone +39 02 27 43 41  
E-Mail info@sick.it

**Japan**

Phone +81 (0)3 3358 1341  
E-Mail support@sick.jp

**Magyarország**

Phone +36 1 371 2680  
E-Mail office@sick.hu

**Nederlands**

Phone +31 (0)30 229 25 44  
E-Mail info@sick.nl

**Norge**

Phone +47 67 81 50 00  
E-Mail austefjord@sick.no

**Österreich**

Phone +43 (0)22 36 62 28 8-0  
E-Mail office@sick.at

**Polska**

Phone +48 22 837 40 50  
E-Mail info@sick.pl

**România**

Phone +40 356 171 120  
E-Mail office@sick.ro

**Russia**

Phone +7-495-775-05-30  
E-Mail info@sick.ru

**Schweiz**

Phone +41 41 619 29 39  
E-Mail contact@sick.ch

**Singapore**

Phone +65 6744 3732  
E-Mail admin@sicksgp.com.sg

**Slovenija**

Phone +386 (0)1-47 69 990  
E-Mail office@sick.si

**South Africa**

Phone +27 11 472 3733  
E-Mail info@sickautomation.co.za

**South Korea**

Phone +82 2 786 6321/4  
E-Mail info@sickkorea.net

**Suomi**

Phone +358-9-25 15 800  
E-Mail sick@sick.fi

**Sverige**

Phone +46 10 110 10 00  
E-Mail info@sick.se

**Taiwan**

Phone +886-2-2375-6288  
E-Mail sales@sick.com.tw

**Türkiye**

Phone +90 (216) 528 50 00  
E-Mail info@sick.com.tr

**United Arab Emirates**

Phone +971 (0) 4 8865 878  
E-Mail info@sick.ae

**USA/México**

Phone +1(952) 941-6780  
1 800-325-7425 – tollfree  
E-Mail info@sickusa.com

More representatives and agencies  
at [www.sick.com](http://www.sick.com)