



Long range distance sensors DMT, DMT10-2, PROFIBUS DP

DMT10-2-2211



Model Name > [DMT10-2-2211](#)
Part No. > [1028541](#)



At a glance

- Measurement range from 0.5 m up to 155 m on natural targets
- Excellent accuracy thanks to time-of-flight measurement
- Easy alignment thanks to pilot laser
- Freely programmable parameters
- RS-422, RS-232, PROFIBUS, analog and two switching outputs
- Near field blanking parameter for operation through a protection window
- Models with filter for measurement of glowing, hot metal (up to 1,400 °C)

Your benefits

- Extremely wide measurement range of up to 155 m on natural targets offers high flexibility in applications where range is key
- Supplementary visible alignment laser allows fast and easy alignment - even over long distances, offering fast and cost-effective installation
- Tough metal housing design for trouble-free operation in the roughest environmental conditions
- Non-visible, Class 1 IR laser for safe measurement and detection
- User-friendly software with an easy-to-follow interface ensures fast and cost-optimized setup
- Serial and analog interfaces as well as two digital switching outputs allow flexible use for varied applications
- Integrated filter option allows for direct measurement of 1,400 °C glowing, hot targets



Performance

Measuring range:	0.5 m ... 155 m, 90 % remission 0.5 m ... 40 m, 6 % remission 0.5 m ... 65 m, 18 % remission
Resolution:	≤ 1 mm
Repeatability ¹⁾ , 2), 3), 4):	10 mm, 7 mm
Accuracy ⁵⁾ , 6):	± 10 mm
Light source:	Laser, infrared
Typ. light spot size (distance):	20 mm (+ 5 x distance in m)
Average depth:	1/16/64/256/1,024
Output rate ⁷⁾ :	1 ms ... 4,000 ms
Aperture delay time:	1 ms ⁸⁾
Note:	Electronic aperture

Response time ⁹⁾ :	1 ms ... 3,000 ms
Cycle time:	1,024 per sec.
Special characteristic:	Electronic aperture
Laser class:	1 (EN 60825-1:Nov.2001, IEC 60825-1:ÄM2:2001)

¹⁾ Dependant on distance and remission, 7 mm, at 6 % ... 90 % remission from 0.5 m ... 65 m, at 6 % ... 18 % remission from 0.5 m ... 40 m, at 6 % remission from 0.5 m ... 15 m ^{2) 4)} Environmental conditions constant, min. warm-up time 30 min, average depth 1,024, statistical error 1 σ ³⁾ Dependant on distance and remission, 10 mm, at 6 % ... 90 % remission from 60 m ... 155 m, at 6 % ... 18 % remission from 40 m ... 65 m, at 6 % remission from 15 m ... 40 m ⁵⁾ 23 °C air temperature, 977 hPa, min. warm-up time 30 min. ⁶⁾ When operating in ambient temperatures between +40 °C ... +55 °C the accuracy can decrease by factor 2.5 ^{7) 8)} Dependant on average setting, average depth, timeout, baud rate, data output and output format ⁹⁾ Dependant on average setting, average depth, timeout, baud rate, data output, output format and effective dead time of aperture

Interfaces

Data interface:	PROFIBUS DP
Output type ¹⁾ :	Q1, Q2
Interface for parametrization:	RS-232
Analog output:	4 mA ... 20 mA, scalable

¹⁾ Output Q short-circuit protected

Mechanics/electronics

Supply voltage Vs:	DC 18 V ... 30 V, limit values
Ripple ¹⁾ :	< 5 Vpp
Initialization time:	6 s
Weight:	Ca. 1,200 g
Output current IA:	100 mA
Power consumption ²⁾ :	≤ 6 W
Connection type:	1 x cable gland, 1 x Sub-D, 9-pin


¹⁾ May not fall short of or exceed V_S tolerances ²⁾ Without load

Ambient data


Enclosure rating:	IP 65
Protection class ¹⁾ :	III
Temperature drift ²⁾ , ³⁾ :	Typ. 0.3 mm/K Typ. 0.6 mm/K
Ambient temperature:	Operation: -10 ... 55 °C Operation with cooling case: -10 ... 75 °C Storage: -25 ... 70 °C
Mechanical load:	Shock: IEC 60068-2-27, -2-29 Sine: IEC 60068-2-6
Electromagnetic compatibility (EMC):	EN 55011:1998 Kl. B, Gr.1/EN 61000-6-2


¹⁾ Reference voltage DC 50 V PELV-voltage (EN 50178) ²⁾ -10° C ... 0° C, +40 °C ... +55 °C ³⁾ 0 °C ... +40 °C

Dimensional drawing





Adjustment possible






Connection type RS-232/PROFIBUS





- |1| NC = normally closed
- |5| M
- |6| L+
- |9| NC = normally closed



Australia

Phone +61 3 9457 0600
1800 334 802 – tollfree
E-Mail sales@sick.com.au

Belgium/Luxembourg

Phone +32 (0)2 466 55 66
E-Mail info@sick.be

Brasil

Phone +55 11 3215-4900
E-Mail sac@sick.com.br

Canada

Phone +1 905 771 14 44
E-Mail information@sick.com

Ceská Republika

Phone +420 2 57 91 18 50
E-Mail sick@sick.cz

China

Phone +86 4000 121 000
E-Mail info.china@sick.net.cn
Phone +852-2153 6300
E-Mail ghk@sick.com.hk

Danmark

Phone +45 45 82 64 00
E-Mail sick@sick.dk

Deutschland

Phone +49 211 5301-301
E-Mail kundenservice@sick.de

España

Phone +34 93 480 31 00
E-Mail info@sick.es

France

Phone +33 1 64 62 35 00
E-Mail info@sick.fr

Great Britain

Phone +44 (0)1727 831121
E-Mail info@sick.co.uk

India

Phone +91-22-4033 8333
E-Mail info@sick-india.com

Israel

Phone +972-4-6801000
E-Mail info@sick-sensors.com

Italia

Phone +39 02 27 43 41
E-Mail info@sick.it

Japan

Phone +81 (0)3 3358 1341
E-Mail support@sick.jp

Magyarország

Phone +36 1 371 2680
E-Mail office@sick.hu

Nederlands

Phone +31 (0)30 229 25 44
E-Mail info@sick.nl

Norge

Phone +47 67 81 50 00
E-Mail austefjord@sick.no

Österreich

Phone +43 (0)22 36 62 28 8-0
E-Mail office@sick.at

Polska

Phone +48 22 837 40 50
E-Mail info@sick.pl

România

Phone +40 356 171 120
E-Mail office@sick.ro

Russia

Phone +7-495-775-05-30
E-Mail info@sick.ru

Schweiz

Phone +41 41 619 29 39
E-Mail contact@sick.ch

Singapore

Phone +65 6744 3732
E-Mail admin@sicksgp.com.sg

Slovenija

Phone +386 (0)1-47 69 990
E-Mail office@sick.si

South Africa

Phone +27 11 472 3733
E-Mail info@sickautomation.co.za

South Korea

Phone +82 2 786 6321/4
E-Mail info@sickkorea.net

Suomi

Phone +358-9-25 15 800
E-Mail sick@sick.fi

Sverige

Phone +46 10 110 10 00
E-Mail info@sick.se

Taiwan

Phone +886-2-2375-6288
E-Mail sales@sick.com.tw

Türkiye

Phone +90 (216) 528 50 00
E-Mail info@sick.com.tr

United Arab Emirates

Phone +971 (0) 4 8865 878
E-Mail info@sick.ae

USA/México

Phone +1(952) 941-6780
1 800-325-7425 – tollfree
E-Mail info@sickusa.com

More representatives and agencies
at www.sick.com