



Standard automation light grids HLG

HLG2-050E811



Model Name > [HLG2-050E811](#)
Part No. > [1041849](#)



At a glance

- 2 mm resolution
- Response time 3 ms
- Detection height 50 mm
- Cable synchronization
- PNP or NPN with both Q and Qnot outputs (NO/NC)
- 1 x test, 1 x teach-in input
- Connector M12, 8-pin

Your benefits

- Reliable object detection throughout the entire working range ensures consistent and reliable operation
- High availability thanks to its ability to detect very flat objects
- The HLG's short response time allows the use of higher conveyor speeds directly leading to higher throughput
- Cable synchronization provides more reliable use and higher machine uptime
- Highest measurement resolution provides smallest minimum detectable object size, for exact counting and true leading edge detection of conveyed objects, for more machine control and increased throughput



Features

Technology:	Sender/receiver
Task:	Switching light grid
Minimum detectable object (MDO):	Parallel beam: ≥ 2 mm
Beam separation:	2 mm
Number of beams:	26
Detection height:	50 mm

Performance

Maximum range:	2 m
Minimum range:	≥ 0 mm
Working range:	1.5 m
Response time ¹⁾ :	Parallel beam: 3 ms

¹⁾ With resistive load

Interfaces

Output type: 2 x NPN (Q and /Q)
Connection type: Connector M12, 8-pin

Mechanics/electronics


Wave length:	950 nm
Supply voltage Vs ¹⁾ :	DC 15 V ... 30 V
Power consumption ²⁾ :	< 100 mA
Power consumption sender ³⁾ :	< 100 mA
Power consumption receiver ⁴⁾ :	> 100 mA
Ripple:	< 5 Vpp
Output current I _{max} :	100 mA
Output load capacitive:	100 nF
Output load inductive:	1 H
Initialization time:	0.8 s
Dimensions (W x H x D):	34 mm x 123 mm x 29 mm
Housing material:	Aluminum
Indication:	LED
Synchronization:	Cable
Enclosure rating:	IP 54
Circuit protection:	Output Q short-circuit protected Interference suppression VS connections reverse-polarity protected
Weight:	135 g
Front screen:	PMMA
Output mode ⁵⁾ :	Q dark switching
Teach input:	PNP

1) 2) 3) 4) Typical value ⁵⁾ Q = active in case one beam is interrupted, /Q = active in case all beam are free


Ambient data

Protection class:	III
EMC:	EN 60947-5-2
Ambient temperature:	Operation: -25 ... 55 °C Storage: -40 ... 70 °C
Ambient light safety ¹⁾ :	Indirect: ≤ 50,000 lx
Vibration resistance:	5 g, 10 Hz ... 55 Hz (IEC 68-2-6)
Shock load:	10 g/DIN EN 60068-2-29/16 ms

¹⁾ Sunlight




- |1| Detection height: 50 mm
- |2| Status indicator/power on
- |3| Connector M12, 8-pin




- 1| Supply voltage
- 2| No object in the light path
- 3| Light path interrupted
- 4| Synchronization error
- 5| Less received signal during teach-in
- 6| Device error
- 7| Activated teach-in procedure

Connection type and diagram



Characteristic curve: MDO



*) MDO: Minimum detectable object size measured in a direction parallel to the HLG

Australia

Phone +61 3 9457 0600
1800 334 802 – tollfree
E-Mail sales@sick.com.au

Belgium/Luxembourg

Phone +32 (0)2 466 55 66
E-Mail info@sick.be

Brasil

Phone +55 11 3215-4900
E-Mail sac@sick.com.br

Canada

Phone +1 905 771 14 44
E-Mail information@sick.com

Ceská Republika

Phone +420 2 57 91 18 50
E-Mail sick@sick.cz

China

Phone +86 4000 121 000
E-Mail info.china@sick.net.cn
Phone +852-2153 6300
E-Mail ghk@sick.com.hk

Danmark

Phone +45 45 82 64 00
E-Mail sick@sick.dk

Deutschland

Phone +49 211 5301-301
E-Mail kundenservice@sick.de

España

Phone +34 93 480 31 00
E-Mail info@sick.es

France

Phone +33 1 64 62 35 00
E-Mail info@sick.fr

Great Britain

Phone +44 (0)1727 831121
E-Mail info@sick.co.uk

India

Phone +91-22-4033 8333
E-Mail info@sick-india.com

Israel

Phone +972-4-6801000
E-Mail info@sick-sensors.com

Italia

Phone +39 02 27 43 41
E-Mail info@sick.it

Japan

Phone +81 (0)3 3358 1341
E-Mail support@sick.jp

Magyarország

Phone +36 1 371 2680
E-Mail office@sick.hu

Nederlands

Phone +31 (0)30 229 25 44
E-Mail info@sick.nl

Norge

Phone +47 67 81 50 00
E-Mail austefjord@sick.no

Österreich

Phone +43 (0)22 36 62 28 8-0
E-Mail office@sick.at

Polska

Phone +48 22 837 40 50
E-Mail info@sick.pl

România

Phone +40 356 171 120
E-Mail office@sick.ro

Russia

Phone +7-495-775-05-30
E-Mail info@sick.ru

Schweiz

Phone +41 41 619 29 39
E-Mail contact@sick.ch

Singapore

Phone +65 6744 3732
E-Mail admin@sicksgp.com.sg

Slovenija

Phone +386 (0)1-47 69 990
E-Mail office@sick.si

South Africa

Phone +27 11 472 3733
E-Mail info@sickautomation.co.za

South Korea

Phone +82 2 786 6321/4
E-Mail info@sickkorea.net

Suomi

Phone +358-9-25 15 800
E-Mail sick@sick.fi

Sverige

Phone +46 10 110 10 00
E-Mail info@sick.se

Taiwan

Phone +886-2-2375-6288
E-Mail sales@sick.com.tw

Türkiye

Phone +90 (216) 528 50 00
E-Mail info@sick.com.tr

United Arab Emirates

Phone +971 (0) 4 8865 878
E-Mail info@sick.ae

USA/México

Phone +1(952) 941-6780
1 800-325-7425 – tollfree
E-Mail info@sickusa.com

More representatives and agencies
at www.sick.com