



Hand-held scanners IDM160 / IDM160 Bluetooth / cordless / industrial / Long Range

IDM160-BT11E



Model Name > **IDM160-BT11E**
Part No. > **6045085**



At a glance

- Identification of all popular 1D codes, with PDF version also stacked codes
- Compact housing with up to IP 65 withstanding 50 drops from 2 m on concrete
- Good read feedback via LED, beeper and vibrator
- Supports all popular corded and cordless interfaces as well as industrial fieldbuses via SICK connectivity
- Tool-free exchange of cable and battery
- Corded and cordless versions available

Your benefits

- Increased productivity and throughput thanks to fast and reliable identification
- Reduced costs thanks to 2-in-1 scan engine: covering standard and high-density codes with a single device
- High reliability thanks to industrial grade and rugged housing
- Intuitive good read feedback for noisy industrial environment via vibration, beeper and LED
- Higher user comfort through ergonomic housing design, well balanced and light weight
- High flexibility and operator mobility with corded and cordless versions
- Quick integration in most corded and cordless PC or industrial networks



Features

Field of application:	Cordless, Industrial
Version:	Long Range
Scanner design:	1D code hand-held scanner
Light source:	Visible red light (630 nm)
Code resolution:	≥0.076 mm
Reading distance (at code resolution):	50 mm ... 800 mm (0.5 mm)
Reading field (at distance):	200 mm (200 mm)
Scanning frequency:	500 Hz

Performance

Supported code type:	1D
Bar code types:	Codabar, Code 11, Code 128, Code 32, Code 39, Code 93, German ITF Postal Code, Interleaved & Matrix 2 of 5, Limited/Expanded GS1 DataBar, Mainland China Postal Code, MSI/Plessey, Standard and Industrial 2 of 5, Telepen, UCC/EAN-128, UK/Plessey, UPC-A, UPC-E

Battery power:	Over 45,000 scans with full battery
Code buffer:	5000 Codes (EAN)

Interfaces

Serial:	✓
Function (Serial):	RS-232 TTL
Ethernet:	✓
Protocol (Ethernet):	PROFINET (optional via external connection module CDM)
Remark (Ethernet):	Optional via external connection module (CDM + CMF)
CAN bus:	✓
Remark (CAN bus):	Optional via external connection module (CAN232)
PROFIBUS DP:	✓
Remark (PROFIBUS DP):	Optional via external connection module (CDF)
DeviceNet:	✓
Remark (DeviceNet):	Optional via external connection module (CDM + CMF)
PS/2:	✓
Function (PS/2):	Keyboard wedge
USB:	✓
Function (USB):	Keyboard wedge, COM-Port emulation
Bluetooth:	✓
Function (Bluetooth):	Wireless operating range up to 30 m (free view), batch function for expansion of the wireless radius, up to seven scanners communicate with one base station
Optical indicators:	2 LEDs (good read, charge of battery , radio connection status)
Acoustic indicators:	Beeper, disengageable (good read)
Vibration:	Yes

Mechanics/electronics

Operating voltage:	5 V DC± 5 %
Power consumption:	Operation (vibration activated): 230 mA, Operation (vibration deactivated): 180 mA, Standby: Typ. 90 mA
Housing color:	Blue, gray
Enclosure rating:	IP 65
Weight:	266 g, incl. rechargeable battery
Dimensions:	104 mm x 76 mm x 185 mm


Ambient data

Shock resistance:	50 drops From 2 m height on concrete
Ambient operating temperature:	-20 °C ... 50 °C
Storage temperature:	-30 °C ... 70 °C
Permissible relative humidity:	± 95 %, non-condensing
Ambient light safety:	100,000 lx

General notes

Items supplied:	Cordless scanner and battery is included in delivery
-----------------	--

Code resolution in mm (mil)



Australia

Phone +61 3 9457 0600
1800 334 802 – tollfree
E-Mail sales@sick.com.au

Belgium/Luxembourg

Phone +32 (0)2 466 55 66
E-Mail info@sick.be

Brasil

Phone +55 11 3215-4900
E-Mail sac@sick.com.br

Canada

Phone +1 905 771 14 44
E-Mail information@sick.com

Ceská Republika

Phone +420 2 57 91 18 50
E-Mail sick@sick.cz

China

Phone +86 4000 121 000
E-Mail info.china@sick.net.cn
Phone +852-2153 6300
E-Mail ghk@sick.com.hk

Danmark

Phone +45 45 82 64 00
E-Mail sick@sick.dk

Deutschland

Phone +49 211 5301-301
E-Mail kundenservice@sick.de

España

Phone +34 93 480 31 00
E-Mail info@sick.es

France

Phone +33 1 64 62 35 00
E-Mail info@sick.fr

Great Britain

Phone +44 (0)1727 831121
E-Mail info@sick.co.uk

India

Phone +91-22-4033 8333
E-Mail info@sick-india.com

Israel

Phone +972-4-6801000
E-Mail info@sick-sensors.com

Italia

Phone +39 02 27 43 41
E-Mail info@sick.it

Japan

Phone +81 (0)3 3358 1341
E-Mail support@sick.jp

Magyarország

Phone +36 1 371 2680
E-Mail office@sick.hu

Nederlands

Phone +31 (0)30 229 25 44
E-Mail info@sick.nl

Norge

Phone +47 67 81 50 00
E-Mail austefjord@sick.no

Österreich

Phone +43 (0)22 36 62 28 8-0
E-Mail office@sick.at

Polska

Phone +48 22 837 40 50
E-Mail info@sick.pl

România

Phone +40 356 171 120
E-Mail office@sick.ro

Russia

Phone +7-495-775-05-30
E-Mail info@sick.ru

Schweiz

Phone +41 41 619 29 39
E-Mail contact@sick.ch

Singapore

Phone +65 6744 3732
E-Mail admin@sicksgp.com.sg

Slovenija

Phone +386 (0)1-47 69 990
E-Mail office@sick.si

South Africa

Phone +27 11 472 3733
E-Mail info@sickautomation.co.za

South Korea

Phone +82 2 786 6321/4
E-Mail info@sickkorea.net

Suomi

Phone +358-9-25 15 800
E-Mail sick@sick.fi

Sverige

Phone +46 10 110 10 00
E-Mail info@sick.se

Taiwan

Phone +886-2-2375-6288
E-Mail sales@sick.com.tw

Türkiye

Phone +90 (216) 528 50 00
E-Mail info@sick.com.tr

United Arab Emirates

Phone +971 (0) 4 8865 878
E-Mail info@sick.ae

USA/México

Phone +1(952) 941-6780
1 800-325-7425 – tollfree
E-Mail info@sickusa.com

More representatives and agencies
at www.sick.com