



## Inductive proximity sensors Cylindrical threaded housing, IM12

IM12-04BPO-ZCK



**Model Name** > [IM12-04BPO-ZCK](#)  
**Part No.** > [6025680](#)



#### At a glance

- Size M12
- IP 67 enclosure rating
- Operating temperature from -25° C to +75° C

#### Your benefits

- Reduced machine downtime
- Reduced mechanical damage
- Fewer maintenance costs due to longer service life
- High resistance to shock and vibrations



#### Features

|                      |                      |
|----------------------|----------------------|
| Housing:             | Cylindrical          |
| Thread size:         | M12 x 1              |
| Sensing range Sn:    | 4 mm                 |
| Installation type:   | Flush                |
| Switching frequency: | 2,000 Hz             |
| Output type:         | PNP                  |
| Output function:     | NC                   |
| Electrical wiring:   | DC 3-wire            |
| Enclosure rating:    | IP 67 <sup>1)</sup>  |
| Connection type:     | Connector M12, 4-pin |
| Housing:             | Short-body           |

<sup>1)</sup> According to EN 60529

#### Mechanics/electronics

|                                 |                                   |
|---------------------------------|-----------------------------------|
| Supply voltage:                 | 10 V DC ... 30 V DC               |
| Ripple:                         | ≤ 10 % <sup>1)</sup>              |
| Voltage drop:                   | ≤ 1.5 V <sup>2)</sup>             |
| Power consumption:              | ≤ 10 mA <sup>3)</sup>             |
| Time delay before availability: | ≤ 100 ms                          |
| Hysteresis:                     | 1 % ... 15 %                      |
| Repeatability:                  | ≤ 5 % <sup>4)</sup> <sup>5)</sup> |
| Temperature drift (% of Sr):    | ± 10 %                            |
| EMC:                            | According to EN 60947-5-2         |
| Output current Ia:              | ≤ 300 mA                          |


|                                |                                |
|--------------------------------|--------------------------------|
| Wire-break protection:         | 1                              |
| Short-circuit protection:      | ✓                              |
| Reverse polarity protection:   | ✓                              |
| Power-up pulse protection:     | ✓                              |
| Shock/vibration:               | 30 g, 11 ms/10 ... 55 Hz, 1 mm |
| Ambient operating temperature: | -25 °C ... 75 °C               |
| Housing material:              | Metal, Nickel-plated brass     |
| Housing cap material:          | Plastic                        |
| Housing length:                | 52.2 mm                        |
| Thread length:                 | 35 mm                          |
| Tightening torque, max.:       | 7 Nm                           |

1) Of  $V_S$  2) At  $I_a$  max 3) Without load 4)  $U_b$  and  $T_a$  constant 5) Of  $S_r$


#### Installation note

|         |                                       |
|---------|---------------------------------------|
| A:      | 6 mm                                  |
| B:      | 12 mm                                 |
| C:      | 12 mm                                 |
| D:      | 12 mm                                 |
| E:      | 2 mm                                  |
| F:      | 32 mm                                 |
| Remark: | Associated graphic see "Installation" |

#### Installation note




Dimensional drawing




All dimensions in mm (inch)

Connection diagram



## Connection type

---



**Australia**

Phone +61 3 9457 0600  
1800 334 802 – tollfree  
E-Mail sales@sick.com.au

**Belgium/Luxembourg**

Phone +32 (0)2 466 55 66  
E-Mail info@sick.be

**Brasil**

Phone +55 11 3215-4900  
E-Mail sac@sick.com.br

**Canada**

Phone +1 905 771 14 44  
E-Mail information@sick.com

**Ceská Republika**

Phone +420 2 57 91 18 50  
E-Mail sick@sick.cz

**China**

Phone +86 4000 121 000  
E-Mail info.china@sick.net.cn  
Phone +852-2153 6300  
E-Mail ghk@sick.com.hk

**Danmark**

Phone +45 45 82 64 00  
E-Mail sick@sick.dk

**Deutschland**

Phone +49 211 5301-301  
E-Mail kundenservice@sick.de

**España**

Phone +34 93 480 31 00  
E-Mail info@sick.es

**France**

Phone +33 1 64 62 35 00  
E-Mail info@sick.fr

**Great Britain**

Phone +44 (0)1727 831121  
E-Mail info@sick.co.uk

**India**

Phone +91-22-4033 8333  
E-Mail info@sick-india.com

**Israel**

Phone +972-4-6801000  
E-Mail info@sick-sensors.com

**Italia**

Phone +39 02 27 43 41  
E-Mail info@sick.it

**Japan**

Phone +81 (0)3 3358 1341  
E-Mail support@sick.jp

**Magyarország**

Phone +36 1 371 2680  
E-Mail office@sick.hu

**Nederlands**

Phone +31 (0)30 229 25 44  
E-Mail info@sick.nl

**Norge**

Phone +47 67 81 50 00  
E-Mail austefjord@sick.no

**Österreich**

Phone +43 (0)22 36 62 28 8-0  
E-Mail office@sick.at

**Polska**

Phone +48 22 837 40 50  
E-Mail info@sick.pl

**România**

Phone +40 356 171 120  
E-Mail office@sick.ro

**Russia**

Phone +7-495-775-05-30  
E-Mail info@sick.ru

**Schweiz**

Phone +41 41 619 29 39  
E-Mail contact@sick.ch

**Singapore**

Phone +65 6744 3732  
E-Mail admin@sicksgp.com.sg

**Slovenija**

Phone +386 (0)1-47 69 990  
E-Mail office@sick.si

**South Africa**

Phone +27 11 472 3733  
E-Mail info@sickautomation.co.za

**South Korea**

Phone +82 2 786 6321/4  
E-Mail info@sickkorea.net

**Suomi**

Phone +358-9-25 15 800  
E-Mail sick@sick.fi

**Sverige**

Phone +46 10 110 10 00  
E-Mail info@sick.se

**Taiwan**

Phone +886-2-2375-6288  
E-Mail sales@sick.com.tw

**Türkiye**

Phone +90 (216) 528 50 00  
E-Mail info@sick.com.tr

**United Arab Emirates**

Phone +971 (0) 4 8865 878  
E-Mail info@sick.ae

**USA/México**

Phone +1(952) 941-6780  
1 800-325-7425 – tollfree  
E-Mail info@sickusa.com

More representatives and agencies  
at [www.sick.com](http://www.sick.com)