



## Inductive proximity sensors Cylindrical threaded housing, IMF18

IMF18-08NPSVC05



**Model Name** > IMF18-08NPSVC0S  
**Part No.** > 6035472



#### At a glance

- Size M18
- Extremely watertight (IP 68/IP 69K)
- Extended temperature range (-40 to +80 °C). Tolerates short-term temperature increases up to 100 °C
- Stainless steel housing (316L/1.4404)
- Front cap made of PPS (FDA-certified material)
- Resistant to industrial cleaning agents, ECOLAB and JohnsonDiversey certified

#### Your benefits

- Reduced machine downtime
- Hygienic process due to FDA approved material and hygienic design
- Reduced maintenance costs due to sensor's resistance to aggressive cleaning cycles
- No restrictions on cleaning agents or processes, ensuring reliable operation



#### Features

|                           |                                    |
|---------------------------|------------------------------------|
| Housing:                  | Cylindrical                        |
| Thread size:              | M18 x 1                            |
| Sensing range Sn:         | 8 mm                               |
| Assured sensing range Sa: | 6.48 mm                            |
| Installation type:        | Non-flush                          |
| Switching frequency:      | 1,500 Hz                           |
| Output type:              | PNP                                |
| Output function:          | NO                                 |
| Electrical wiring:        | DC 3-wire                          |
| Enclosure rating::        | IP 68, IP 69K <sup>1) 2)</sup>     |
| Connection type:          | Connector M12, 4-pin <sup>3)</sup> |

<sup>1)</sup> According to EN 60529 <sup>2)</sup> According to EN40050 <sup>3)</sup> With gold plated contact pins

#### Mechanics/electronics

|                                 |                       |
|---------------------------------|-----------------------|
| Supply voltage:                 | 10 V ... 30 V         |
| Ripple:                         | ≤ 10 %                |
| Voltage drop:                   | ≤ 2 V                 |
| Power consumption:              | ≤ 15 mA <sup>1)</sup> |
| Time delay before availability: | Ca. 50 ms             |

|                                 |                                                     |
|---------------------------------|-----------------------------------------------------|
| Hysteresis:                     | 1 % ... 20 %                                        |
| Repeatability:                  | 5 % <sup>2)</sup> <sup>3)</sup>                     |
| Temperature drift (% of Sr):    | ± 10 %                                              |
| EMC:                            | According to EN 60947-5-2                           |
| Output current I <sub>a</sub> : | ≤ 200 mA                                            |
| Short-circuit protection:       | ✓                                                   |
| Reverse polarity protection:    | ✓                                                   |
| Power-up pulse protection:      | ✓                                                   |
| Shock/vibration:                | 30 g, 11 ms/10 Hz ... 55 Hz, 1 mm                   |
| Ambient operating temperature:  | -40 °C ... 80 °C <sup>4)</sup>                      |
| Housing material:               | Stainless steel, Stainless steel V4A (1.4404, 316L) |
| Housing cap material:           | PPS                                                 |
| Housing length:                 | 63 mm                                               |
| Thread length:                  | 27 mm                                               |
| Tightening torque, max.:        | 50 Nm                                               |

<sup>1)</sup> Without load <sup>2)</sup> U<sub>b</sub> and T<sub>a</sub> constant <sup>3)</sup> Of Sr <sup>4)</sup> +100 °C for 15 minutes

### Reduction factors

|                             |                                                |
|-----------------------------|------------------------------------------------|
| Note:                       | The values are reference values which may vary |
| Stainless steel (V2A, 304): | Ca. 0.7                                        |
| Copper (Cu):                | Ca. 0.27                                       |
| Aluminum (Al):              | Ca. 0.35                                       |
| Brass (Br):                 | Ca. 0.42                                       |


### Installation note

|         |                                       |
|---------|---------------------------------------|
| A:      | 18 mm                                 |
| B:      | 36 mm                                 |
| C:      | 18 mm                                 |
| D:      | 24 mm                                 |
| E:      | 12 mm                                 |
| F:      | 64 mm                                 |
| Remark: | Associated graphic see "Installation" |

Installation note



Dimensional drawing



All dimensions in mm (inch)


## Connection diagram

---



## Connection type

---



**Australia**

Phone +61 3 9457 0600  
1800 334 802 – tollfree  
E-Mail sales@sick.com.au

**Belgium/Luxembourg**

Phone +32 (0)2 466 55 66  
E-Mail info@sick.be

**Brasil**

Phone +55 11 3215-4900  
E-Mail sac@sick.com.br

**Canada**

Phone +1 905 771 14 44  
E-Mail information@sick.com

**Ceská Republika**

Phone +420 2 57 91 18 50  
E-Mail sick@sick.cz

**China**

Phone +86 4000 121 000  
E-Mail info.china@sick.net.cn  
Phone +852-2153 6300  
E-Mail ghk@sick.com.hk

**Danmark**

Phone +45 45 82 64 00  
E-Mail sick@sick.dk

**Deutschland**

Phone +49 211 5301-301  
E-Mail kundenservice@sick.de

**España**

Phone +34 93 480 31 00  
E-Mail info@sick.es

**France**

Phone +33 1 64 62 35 00  
E-Mail info@sick.fr

**Great Britain**

Phone +44 (0)1727 831121  
E-Mail info@sick.co.uk

**India**

Phone +91-22-4033 8333  
E-Mail info@sick-india.com

**Israel**

Phone +972-4-6801000  
E-Mail info@sick-sensors.com

**Italia**

Phone +39 02 27 43 41  
E-Mail info@sick.it

**Japan**

Phone +81 (0)3 3358 1341  
E-Mail support@sick.jp

**Magyarország**

Phone +36 1 371 2680  
E-Mail office@sick.hu

**Nederlands**

Phone +31 (0)30 229 25 44  
E-Mail info@sick.nl

**Norge**

Phone +47 67 81 50 00  
E-Mail austefjord@sick.no

**Österreich**

Phone +43 (0)22 36 62 28 8-0  
E-Mail office@sick.at

**Polska**

Phone +48 22 837 40 50  
E-Mail info@sick.pl

**România**

Phone +40 356 171 120  
E-Mail office@sick.ro

**Russia**

Phone +7-495-775-05-30  
E-Mail info@sick.ru

**Schweiz**

Phone +41 41 619 29 39  
E-Mail contact@sick.ch

**Singapore**

Phone +65 6744 3732  
E-Mail admin@sicksgp.com.sg

**Slovenija**

Phone +386 (0)1-47 69 990  
E-Mail office@sick.si

**South Africa**

Phone +27 11 472 3733  
E-Mail info@sickautomation.co.za

**South Korea**

Phone +82 2 786 6321/4  
E-Mail info@sickkorea.net

**Suomi**

Phone +358-9-25 15 800  
E-Mail sick@sick.fi

**Sverige**

Phone +46 10 110 10 00  
E-Mail info@sick.se

**Taiwan**

Phone +886-2-2375-6288  
E-Mail sales@sick.com.tw

**Türkiye**

Phone +90 (216) 528 50 00  
E-Mail info@sick.com.tr

**United Arab Emirates**

Phone +971 (0) 4 8865 878  
E-Mail info@sick.ae

**USA/México**

Phone +1(952) 941-6780  
1 800-325-7425 – tollfree  
E-Mail info@sickusa.com

More representatives and agencies  
at [www.sick.com](http://www.sick.com)