



Laser scanners JEF5xx / JEF500 / Indoor / Short Range

JEF500-00000



Model Name > JEF500-00000
Part No. > 1056365




At a glance

- 2D and 3D laser measurement sensor
- Multiple I/O and interfacing
- Large working range without any additional focal adjustments
- Output of reflectivity data

Your benefits

- Simple 3D measurement with one sensor
- Large area can be measured with one sensor
- No additional illumination needed



Features

Field of application:	Indoor
Version:	Short Range
Connection type:	Ethernet
Reading field:	Front
Light source:	Visible red light (650 nm)
MTBF:	40,000 h
Laser class:	2 (EN 60825-1 (A2:2001-03))
Field of view:	≤ 45 °
Scanning frequency:	600 Hz ... 800 Hz
Angular resolution:	1 °
Operating range:	0.4 m ... 2 m
Max. range with 10 % reflectivity:	1.2 m

Performance

Response time:	≥ 1.125 ms
Detectable object shape:	Almost any
Systematic error ¹⁾ :	± 25 mm
Statistical error ²⁾ :	± 25 mm

^{1) 2)} Typical value; actual value depends on environmental conditions.

Interfaces

Serial (RS-232, RS-422/485):	✓
------------------------------	---

Remark (Serial (RS-232, RS-422/485)):	AUX (only RS-232)
Function (Serial (RS-232, RS-422/485)):	Host, AUX
Data transmission rate (Serial (RS-232, RS-422/485)):	2,400 Baud ... 115 kBaud, AUX: 57.6 kBaud
Ethernet:	✓
Function (Ethernet):	Host, AUX
Data transmission rate (Ethernet):	10/100 Mbit
Protocol (Ethernet):	TCP/IP
CAN bus:	-
PROFIBUS DP:	-
PROFINET:	-
DeviceNet:	-
Switching inputs:	2
Switching outputs:	2
Optical indicators:	6 LEDs (Ready, laser, Data, CAN, LNK TX)
Memory card:	MicroSD memory card (flash card) 512 MB, optional

Mechanics/electronics

Electrical connection:	2 M12 cylindrical connectors (17-pin plug, 4-pin socket) on swivel connector
Operating voltage:	18 V DC ... 30 V DC
Power consumption:	8.5 W
Housing:	Die-cast aluminum
Housing color:	Light blue (RAL 5012)
Enclosure rating:	IP 65 (EN 60529)
Protection class:	III (EN 61140)
Weight:	250 g
Dimensions:	61 mm x 96 mm x 38 mm ¹⁾

¹⁾ Swivel connector is 15 mm longer

Ambient data

Electromagnetic compatibility (EMC):	(EN 61000-6-1 (2001-10)) (EN 61000-6-2:2005)
Vibration resistance:	(EN 60068-2-6 (1995))
Shock resistance:	(EN 60068-2-27 (1993))
Ambient operating temperature:	0 °C ... 40 °C
Storage temperature:	-20 °C ... 70 °C
Ambient light safety:	2,000 lx
Permissible relative humidity:	± 90 %, non-condensing

General notes

Note on use:	Not suitable for personnel protection
--------------	---------------------------------------

Technical drawing of the SICK IME 1200 sensor, showing three views: front, side, and top.

Front View:

- Field of view: 50°
- Overall width: 652
- Mounting flange width: 61
- Mounting flange thickness: 16
- Mounting flange hole diameter: 0.2
- Mounting flange hole spacing: 11
- Mounting flange hole diameter: 96
- Mounting flange hole spacing: 68
- Mounting flange hole diameter: 15
- Mounting flange hole spacing: 225
- Mounting flange hole diameter: 5.7
- Mounting flange hole spacing: 10

Side View:

- Overall height: 43.7
- Mounting flange height: 41.7
- Mounting flange thickness: 6.2
- Mounting flange hole diameter: 19.5
- Mounting flange hole spacing: 38

Top View:

- Overall width: 13.7
- Mounting flange width: 19.5
- Mounting flange thickness: 22.5
- Mounting flange hole diameter: 5.7
- Mounting flange hole spacing: 10

Labels:

- Blind hole tap M5, 5 deep
- SICK

Australia

Phone +61 3 9457 0600
1800 334 802 – tollfree
E-Mail sales@sick.com.au

Belgium/Luxembourg

Phone +32 (0)2 466 55 66
E-Mail info@sick.be

Brasil

Phone +55 11 3215-4900
E-Mail sac@sick.com.br

Canada

Phone +1 905 771 14 44
E-Mail information@sick.com

Ceská Republika

Phone +420 2 57 91 18 50
E-Mail sick@sick.cz

China

Phone +86 4000 121 000
E-Mail info.china@sick.net.cn
Phone +852-2153 6300
E-Mail ghk@sick.com.hk

Danmark

Phone +45 45 82 64 00
E-Mail sick@sick.dk

Deutschland

Phone +49 211 5301-301
E-Mail kundenservice@sick.de

España

Phone +34 93 480 31 00
E-Mail info@sick.es

France

Phone +33 1 64 62 35 00
E-Mail info@sick.fr

Great Britain

Phone +44 (0)1727 831121
E-Mail info@sick.co.uk

India

Phone +91-22-4033 8333
E-Mail info@sick-india.com

Israel

Phone +972-4-6801000
E-Mail info@sick-sensors.com

Italia

Phone +39 02 27 43 41
E-Mail info@sick.it

Japan

Phone +81 (0)3 3358 1341
E-Mail support@sick.jp

Magyarország

Phone +36 1 371 2680
E-Mail office@sick.hu

Nederlands

Phone +31 (0)30 229 25 44
E-Mail info@sick.nl

Norge

Phone +47 67 81 50 00
E-Mail austefjord@sick.no

Österreich

Phone +43 (0)22 36 62 28 8-0
E-Mail office@sick.at

Polska

Phone +48 22 837 40 50
E-Mail info@sick.pl

România

Phone +40 356 171 120
E-Mail office@sick.ro

Russia

Phone +7-495-775-05-30
E-Mail info@sick.ru

Schweiz

Phone +41 41 619 29 39
E-Mail contact@sick.ch

Singapore

Phone +65 6744 3732
E-Mail admin@sicksgp.com.sg

Slovenija

Phone +386 (0)1-47 69 990
E-Mail office@sick.si

South Africa

Phone +27 11 472 3733
E-Mail info@sickautomation.co.za

South Korea

Phone +82 2 786 6321/4
E-Mail info@sickkorea.net

Suomi

Phone +358-9-25 15 800
E-Mail sick@sick.fi

Sverige

Phone +46 10 110 10 00
E-Mail info@sick.se

Taiwan

Phone +886-2-2375-6288
E-Mail sales@sick.com.tw

Türkiye

Phone +90 (216) 528 50 00
E-Mail info@sick.com.tr

United Arab Emirates

Phone +971 (0) 4 8865 878
E-Mail info@sick.ae

USA/México

Phone +1(952) 941-6780
1 800-325-7425 – tollfree
E-Mail info@sickusa.com

More representatives and agencies
at www.sick.com