



Level sensors Vibrating level switch, LBV311

LBV311-XXAGCNKMX



Model Name > **LBV311-XXAGCNKMX**
Part No. > **6044866**



Illustration may differ

At a glance

- Compact, rugged device design
- Several housing materials and electrical outputs available
- Monoprobe design prevents bulk materials from sticking and jamming
- No sensor orientation requirements when mounted
- Commissioning without filling
- Process temperature up to 250 °C
- Polished versions for use in the food industry
- ATEX versions (1D/2D/1G/2G) available

Your benefits

- Easy installation, no orientation of the sensor required
- Easy operation and integration, saves time
- Monoprobe design for continual operation in challenging materials
- Simple, on-site sensor checking - no mounting required, which reduces installation time
- Flexible, rugged system suitable for several types of applications



Features

Medium:	Bulk solids
Measurement:	Switch
Probe length:	160 mm
Process pressure:	-1 bar ... 16 bar
Process temperature:	-50 °C ... 150 °C
ATEX certification:	-
Fill material density:	0.02 g/cm ³

Performance

Accuracy of sensor element:	± 10 mm
Repeatability:	≤ 5 mm
Response time:	500 ms when covered / 1000 ms when uncovered

Mechanical data

Housing material:	Plastic
Process connection:	G 1 A
Sensor material:	Stainless steel 316L, 318S


Electrical data

Enclosure rating:	IP 66/IP 67, IP 66/IP 68 (0.2 bar)
Power consumption:	1 mA/2,5 mA
VDE protection class 2:	✓
Initialization time:	< 2 s
Output signal:	NAMUR signal: 4.5 V DC ... 12 V DC
Hysteresis:	10 mm
Output current:	1 mA/2,5 mA
Connection type:	M20 x 1.5


Ambient data

Ambient operating temperature:	-40 °C ... 70 °C
Ambient storage temperature:	-40 °C ... 80 °C


Namur connection diagram



Horizontal mounting



Ambient temperature - process temperature



Australia

Phone +61 3 9457 0600
1800 334 802 – tollfree
E-Mail sales@sick.com.au

Belgium/Luxembourg

Phone +32 (0)2 466 55 66
E-Mail info@sick.be

Brasil

Phone +55 11 3215-4900
E-Mail sac@sick.com.br

Canada

Phone +1 905 771 14 44
E-Mail information@sick.com

Ceská Republika

Phone +420 2 57 91 18 50
E-Mail sick@sick.cz

China

Phone +86 4000 121 000
E-Mail info.china@sick.net.cn
Phone +852-2153 6300
E-Mail ghk@sick.com.hk

Danmark

Phone +45 45 82 64 00
E-Mail sick@sick.dk

Deutschland

Phone +49 211 5301-301
E-Mail kundenservice@sick.de

España

Phone +34 93 480 31 00
E-Mail info@sick.es

France

Phone +33 1 64 62 35 00
E-Mail info@sick.fr

Great Britain

Phone +44 (0)1727 831121
E-Mail info@sick.co.uk

India

Phone +91-22-4033 8333
E-Mail info@sick-india.com

Israel

Phone +972-4-6801000
E-Mail info@sick-sensors.com

Italia

Phone +39 02 27 43 41
E-Mail info@sick.it

Japan

Phone +81 (0)3 3358 1341
E-Mail support@sick.jp

Magyarország

Phone +36 1 371 2680
E-Mail office@sick.hu

Nederlands

Phone +31 (0)30 229 25 44
E-Mail info@sick.nl

Norge

Phone +47 67 81 50 00
E-Mail austefjord@sick.no

Österreich

Phone +43 (0)22 36 62 28 8-0
E-Mail office@sick.at

Polska

Phone +48 22 837 40 50
E-Mail info@sick.pl

România

Phone +40 356 171 120
E-Mail office@sick.ro

Russia

Phone +7-495-775-05-30
E-Mail info@sick.ru

Schweiz

Phone +41 41 619 29 39
E-Mail contact@sick.ch

Singapore

Phone +65 6744 3732
E-Mail admin@sicksgp.com.sg

Slovenija

Phone +386 (0)1-47 69 990
E-Mail office@sick.si

South Africa

Phone +27 11 472 3733
E-Mail info@sickautomation.co.za

South Korea

Phone +82 2 786 6321/4
E-Mail info@sickkorea.net

Suomi

Phone +358-9-25 15 800
E-Mail sick@sick.fi

Sverige

Phone +46 10 110 10 00
E-Mail info@sick.se

Taiwan

Phone +886-2-2375-6288
E-Mail sales@sick.com.tw

Türkiye

Phone +90 (216) 528 50 00
E-Mail info@sick.com.tr

United Arab Emirates

Phone +971 (0) 4 8865 878
E-Mail info@sick.ae

USA/México

Phone +1(952) 941-6780
1 800-325-7425 – tollfree
E-Mail info@sickusa.com

More representatives and agencies
at www.sick.com