



## Level sensors TDR level sensor

LFP0600-A5NMC



**Model Name** > LFP0600-A5NMC  
**Part No.** > 1062249



*Illustration may differ*

#### At a glance

- No mechanical moving parts
- Manually cuttable and exchangeable monoprobe with lengths from 200 mm up to 2,000 mm
- Immune to deposit formation
- Process temperature up to 100 °C; process pressure up to 10 bar
- Small inactive areas, ideal for small containers
- Accurate measurement, even when liquid type changes
- 3-in-1: combined display, analog output (acc. NAMUR NE 43) and binary output
- High enclosure rating of IP 67, rotatable housing

#### Your benefits

- Rugged design increases service life
- High flexibility due to cuttable and exchangeable monoprobe
- Cost savings due to multiple output signals: one system for both level detection and continuous level monitoring
- Time and cost savings due to low maintenance and quick commissioning
- No calibration or recalibration required for commissioning, thus saving time and costs
- Compact and rotatable housing ensures flexible installation
- No crosstalk when several sensors are mounted next to each other
- Advanced technology enables adjustment-free measurement of oil- and water-based liquids



#### Features

|                      |                    |
|----------------------|--------------------|
| Medium:              | Fluids             |
| Measurement:         | Switch, Continuous |
| Probe length:        | 600 mm             |
| Process pressure:    | -1 bar ... 10 bar  |
| Process temperature: | -20 °C ... 100 °C  |
| GOST approval:       | ✓                  |
| RoHS certificate:    | ✓                  |
| IO-Link:             | ✓                  |

#### Performance

|                             |                      |
|-----------------------------|----------------------|
| Maximum level change:       | 500 mm/s             |
| Resolution:                 | < 2 mm               |
| Accuracy of sensor element: | ± 5 mm <sup>1)</sup> |

|                                     |                                             |
|-------------------------------------|---------------------------------------------|
| Repeatability:                      | ≤ 2 mm                                      |
| Dielectricity constant:             | ≥ 1.8 with coaxial tube, ≥ 5 for mono probe |
| Inactive area at process connector: | 25 mm <sup>2)</sup>                         |
| Inactive area at probe end:         | 10 mm <sup>3)</sup>                         |
| Conductivity:                       | No limitation                               |
| Response time:                      | < 400 ms                                    |

1) 3) With water under reference conditions    2) With parameterized tank with water under reference conditions, otherwise 40 mm

### Mechanical data

|                     |              |
|---------------------|--------------|
| Housing material:   | Plastic PBT  |
| Max.probe load:     | 6 Nm         |
| Process connection: | G ¾ A        |
| Wetted parts:       | 1.4404, PTFE |

### Electrical data


|                      |                                                                                                                                                                                                         |
|----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Temperature drift:   | < 0.1 mm/K                                                                                                                                                                                              |
| Enclosure rating:    | IP 67: EN 60529                                                                                                                                                                                         |
| Supply voltage:      | 12 V DC ... 30 V DC <sup>1)</sup>                                                                                                                                                                       |
| Power consumption:   | ≤ 100 mA at 24 V DC without output load                                                                                                                                                                 |
| Protection class:    | III                                                                                                                                                                                                     |
| Initialization time: | ≤ 5 s                                                                                                                                                                                                   |
| Output signal:       | 1 PNP transistor output (Q1) und 3 PNP/NPN transistor output (Q2...Q4) switchable, Analog output 4 mA ... 20 mA, 0 V ... 10 V automatic switching to a current or voltage output depending on the load. |
| Output load:         | 0 V ... 10 V > 750 Ohm at Uv ≥ 14 V, 4 mA ... 20 mA < 350 Ohm at Uv > 12 V, 4 mA ... 20 mA < 500 Ohm at Uv > 15 V                                                                                       |
| Upper signal level:  | 20 mA ... 20.5 mA                                                                                                                                                                                       |
| Lower signal level:  | 3.8 mA ... 4 mA                                                                                                                                                                                         |
| Hysteresis:          | Min. 2 mm, free adjustable                                                                                                                                                                              |
| Output current:      | < 100 mA                                                                                                                                                                                                |
| Signal voltage HIGH: | Vs - 2 V                                                                                                                                                                                                |
| Signal voltage LOW:  | ≤ 2 V                                                                                                                                                                                                   |
| Capacitive load:     | 100 nF                                                                                                                                                                                                  |
| Inductive load:      | < 1 H                                                                                                                                                                                                   |
| Connection type:     | Round connector M12 x 1, 8-pin                                                                                                                                                                          |
| EMC:                 | EN 61326-1:2006, 2004/108/EG                                                                                                                                                                            |

1) All connections are polarity protected. All outputs are overload and short-circuit protected.



### Ambient data

|                                |                  |
|--------------------------------|------------------|
| Ambient operating temperature: | -20 °C ... 60 °C |
| Ambient storage temperature:   | -40 °C ... 80 °C |

## Dimensional drawing



## Connection type



- |1| L+: Supply voltage
- |2| Q2: Switching output 2, PNP/NPN
- |3| M: Ground, reference ground for current-/voltage output
- |4| C/Q1: Switching output 1, PNP/IO-Link-communication
- |5| Q3: Switching output 3, PNP/NPN
- |6| Q4: Switching output 4, PNP/NPN
- |7| QA: Analog current-/voltage output
- |8| No function

**Australia**

Phone +61 3 9457 0600  
1800 334 802 – tollfree  
E-Mail sales@sick.com.au

**Belgium/Luxembourg**

Phone +32 (0)2 466 55 66  
E-Mail info@sick.be

**Brasil**

Phone +55 11 3215-4900  
E-Mail sac@sick.com.br

**Canada**

Phone +1 905 771 14 44  
E-Mail information@sick.com

**Ceská Republika**

Phone +420 2 57 91 18 50  
E-Mail sick@sick.cz

**China**

Phone +86 4000 121 000  
E-Mail info.china@sick.net.cn  
Phone +852-2153 6300  
E-Mail ghk@sick.com.hk

**Danmark**

Phone +45 45 82 64 00  
E-Mail sick@sick.dk

**Deutschland**

Phone +49 211 5301-301  
E-Mail kundenservice@sick.de

**España**

Phone +34 93 480 31 00  
E-Mail info@sick.es

**France**

Phone +33 1 64 62 35 00  
E-Mail info@sick.fr

**Great Britain**

Phone +44 (0)1727 831121  
E-Mail info@sick.co.uk

**India**

Phone +91-22-4033 8333  
E-Mail info@sick-india.com

**Israel**

Phone +972-4-6801000  
E-Mail info@sick-sensors.com

**Italia**

Phone +39 02 27 43 41  
E-Mail info@sick.it

**Japan**

Phone +81 (0)3 3358 1341  
E-Mail support@sick.jp

**Magyarország**

Phone +36 1 371 2680  
E-Mail office@sick.hu

**Nederlands**

Phone +31 (0)30 229 25 44  
E-Mail info@sick.nl

**Norge**

Phone +47 67 81 50 00  
E-Mail austefjord@sick.no

**Österreich**

Phone +43 (0)22 36 62 28 8-0  
E-Mail office@sick.at

**Polska**

Phone +48 22 837 40 50  
E-Mail info@sick.pl

**România**

Phone +40 356 171 120  
E-Mail office@sick.ro

**Russia**

Phone +7-495-775-05-30  
E-Mail info@sick.ru

**Schweiz**

Phone +41 41 619 29 39  
E-Mail contact@sick.ch

**Singapore**

Phone +65 6744 3732  
E-Mail admin@sicksgp.com.sg

**Slovenija**

Phone +386 (0)1-47 69 990  
E-Mail office@sick.si

**South Africa**

Phone +27 11 472 3733  
E-Mail info@sickautomation.co.za

**South Korea**

Phone +82 2 786 6321/4  
E-Mail info@sickkorea.net

**Suomi**

Phone +358-9-25 15 800  
E-Mail sick@sick.fi

**Sverige**

Phone +46 10 110 10 00  
E-Mail info@sick.se

**Taiwan**

Phone +886-2-2375-6288  
E-Mail sales@sick.com.tw

**Türkiye**

Phone +90 (216) 528 50 00  
E-Mail info@sick.com.tr

**United Arab Emirates**

Phone +971 (0) 4 8865 878  
E-Mail info@sick.ae

**USA/México**

Phone +1(952) 941-6780  
1 800-325-7425 – tollfree  
E-Mail info@sickusa.com

More representatives and agencies  
at [www.sick.com](http://www.sick.com)