



## Level sensors TDR level sensor

LFP0900-G1NMB



**Model Name** > **LFP0900-G1NMB**  
**Part No.** > **1052074**



*Illustration may differ*

#### At a glance

- Level monitoring in hygienic applications
- Manually cutable monoprobe made from stainless steel 1.4404 up to 2,000 mm long with Ra 0.8 µm
- Process temperature up to 150 °C, process pressure up to 16 bar
- CIP/SIP resistant
- IP 67 and IP 69K enclosure rating
- Interchangeable hygienic process connections
- 3-in-1: combined display, analog output and binary output
- Analog output 4 mA ... 20 mA / 0 V ... 10 V, switchable, plus two binary outputs

#### Your benefits

- Robust design increases service life
- High flexibility due to cutable probe and interchangeable connection concept
- Cost savings due to multiple output signals: one system for both level detection and continuous level monitoring
- Time and cost savings due to low maintenance and quick commissioning
- No calibration or recalibration required for commissioning, thus saving time and costs



#### Features

|                      |                    |
|----------------------|--------------------|
| Medium:              | Fluids             |
| Measurement:         | Switch, Continuous |
| Probe length:        | 900 mm             |
| Process pressure:    | -1 bar ... 16 bar  |
| Process temperature: | -20 °C ... 150 °C  |
| EHEDG approval:      | ✓                  |
| GOST approval:       | ✓                  |
| RoHS certificate:    | ✓                  |
| IO-Link:             | ✓                  |
| 3-A:                 | 0                  |

#### Performance

|                                     |                     |
|-------------------------------------|---------------------|
| Resolution:                         | < 2 mm              |
| Accuracy of sensor element:         | ± 5 mm              |
| Repeatability:                      | ≤ 2 mm              |
| Dielectricity constant:             | ≥ 5                 |
| Inactive area at process connector: | 25 mm <sup>1)</sup> |

|                             |                     |
|-----------------------------|---------------------|
| Inactive area at probe end: | 10 mm <sup>2)</sup> |
| Conductivity:               | No limitation       |
| Response time:              | < 400 ms            |

<sup>1)</sup> With parameterized tank with water under reference conditions, otherwise 40 mm <sup>2)</sup> With water under reference conditions

#### Mechanical data

---

|                     |                          |
|---------------------|--------------------------|
| Housing material:   | 303                      |
| Max.probe load:     | 6 Nm                     |
| Process connection: | G ¾ A                    |
| Wetted parts:       | 316L (Ra ≤ 0,8 µm), PEEK |
| Housing design:     | With PMMA viewing window |

#### Electrical data

---

|                               |                                                                                                                     |
|-------------------------------|---------------------------------------------------------------------------------------------------------------------|
| Temperature drift:            | < 0.1 mm/K                                                                                                          |
| Enclosure rating:             | IP 67: EN 60529, IP 69K: EN 40050                                                                                   |
| Supply voltage:               | 12 V DC ... 30 V DC <sup>1)</sup>                                                                                   |
| Power consumption:            | ≤ 75 mA at 24 V DC without output load                                                                              |
| Protection class:             | III                                                                                                                 |
| Initialization time:          | ≤ 2 s                                                                                                               |
| Output load:                  | 0 V ... 10 V > 750 Ohm at Uv ≥ 14 V, 4 mA ... 20 mA < 400 Ohm at Uv > 12 V, 4 mA ... 20 mA < 500 Ohm at Uv > 13,5 V |
| Upper signal level:           | 20 mA ... 20.5 mA                                                                                                   |
| Lower signal level:           | 3.8 mA ... 4 mA                                                                                                     |
| Hysteresis:                   | Min. 2 mm, free adjustable                                                                                          |
| Output current:               | < 100 mA                                                                                                            |
| Signal voltage HIGH:          | Vs - 2 V                                                                                                            |
| Signal voltage LOW:           | ≤ 2 V                                                                                                               |
| Capacitive load:              | 100 nF                                                                                                              |
| Inductive load:               | < 1 H                                                                                                               |
| Connection type:              | Round connector M12 x 1, 5-pin                                                                                      |
| EMC:                          | EN 61326-1:2006, 2004/108/EG                                                                                        |
| Interference resistance:      | EN 61000-6-2:2005                                                                                                   |
| Interference emission:        | EN 61000-6-4:2007                                                                                                   |
| Single- and continuous shock: | EN 60068-2-27                                                                                                       |


<sup>1)</sup> All connections are polarity protected. All outputs are overload and short-circuit protected.

#### Ambient data



---

|                                |                  |
|--------------------------------|------------------|
| Ambient operating temperature: | -20 °C ... 60 °C |
| Ambient storage temperature:   | -40 °C ... 80 °C |

## Dimensional drawing



## Connection type



- |1| L+: Supply voltage, brown
- |2| QA: Analog current-/voltage output, white
- |3| M: Ground, reference ground  
for current-/voltage output, blue
- |4| C/Q1: Switching output 1,  
PNP/IO-Link-communication, black
- |5| Q2: Switching output 2, PNP/NPN, grey

#### **Australia**

Phone +61 3 9457 0600  
1800 334 802 – tollfree  
E-Mail sales@sick.com.au

#### **Belgium/Luxembourg**

Phone +32 (0)2 466 55 66  
E-Mail info@sick.be

#### **Brasil**

Phone +55 11 3215-4900  
E-Mail sac@sick.com.br

#### **Canada**

Phone +1 905 771 14 44  
E-Mail information@sick.com

#### **Ceská Republika**

Phone +420 2 57 91 18 50  
E-Mail sick@sick.cz

#### **China**

Phone +86 4000 121 000  
E-Mail info.china@sick.net.cn  
Phone +852-2153 6300  
E-Mail ghk@sick.com.hk

#### **Danmark**

Phone +45 45 82 64 00  
E-Mail sick@sick.dk

#### **Deutschland**

Phone +49 211 5301-301  
E-Mail kundenservice@sick.de

#### **España**

Phone +34 93 480 31 00  
E-Mail info@sick.es

#### **France**

Phone +33 1 64 62 35 00  
E-Mail info@sick.fr

#### **Great Britain**

Phone +44 (0)1727 831121  
E-Mail info@sick.co.uk

#### **India**

Phone +91-22-4033 8333  
E-Mail info@sick-india.com

#### **Israel**

Phone +972-4-6801000  
E-Mail info@sick-sensors.com

#### **Italia**

Phone +39 02 27 43 41  
E-Mail info@sick.it

#### **Japan**

Phone +81 (0)3 3358 1341  
E-Mail support@sick.jp

#### **Magyarország**

Phone +36 1 371 2680  
E-Mail office@sick.hu

#### **Nederlands**

Phone +31 (0)30 229 25 44  
E-Mail info@sick.nl

#### **Norge**

Phone +47 67 81 50 00  
E-Mail austefjord@sick.no

#### **Österreich**

Phone +43 (0)22 36 62 28 8-0  
E-Mail office@sick.at

#### **Polska**

Phone +48 22 837 40 50  
E-Mail info@sick.pl

#### **România**

Phone +40 356 171 120  
E-Mail office@sick.ro

#### **Russia**

Phone +7-495-775-05-30  
E-Mail info@sick.ru

#### **Schweiz**

Phone +41 41 619 29 39  
E-Mail contact@sick.ch

#### **Singapore**

Phone +65 6744 3732  
E-Mail admin@sicksgp.com.sg

#### **Slovenija**

Phone +386 (0)1-47 69 990  
E-Mail office@sick.si

#### **South Africa**

Phone +27 11 472 3733  
E-Mail info@sickautomation.co.za

#### **South Korea**

Phone +82 2 786 6321/4  
E-Mail info@sickkorea.net

#### **Suomi**

Phone +358-9-25 15 800  
E-Mail sick@sick.fi

#### **Sverige**

Phone +46 10 110 10 00  
E-Mail info@sick.se

#### **Taiwan**

Phone +886-2-2375-6288  
E-Mail sales@sick.com.tw

#### **Türkiye**

Phone +90 (216) 528 50 00  
E-Mail info@sick.com.tr

#### **United Arab Emirates**

Phone +971 (0) 4 8865 878  
E-Mail info@sick.ae

#### **USA/México**

Phone +1(952) 941-6780  
1 800-325-7425 – tollfree  
E-Mail info@sickusa.com

More representatives and agencies  
at [www.sick.com](http://www.sick.com)