



## Laser scanners LMS1xx / LMS13x / Security / Semi-Outdoor / Short Range

LMS132-10100 Security



**Model Name** > [LMS132-10100 Security](#)

**Part No.** > [1051402](#)



#### At a glance

- Economical measurement sensor
- Real-time output of measurement data via Ethernet interface
- Field evaluation using intelligent algorithms and programmable applications
- Number of switching outputs can be expanded via external CAN modules
- Parameter setting interface is accessible from the front while the device is mounted
- Rugged housing

#### Your benefits

- Lightweight housing makes it easy to mount
- No wiring between sender and receiver
- Advanced filtering technology rigorously reduces false trips caused by outdoor environmental factors like fog, rain and snow
- Optional external CAN I/O module increases number of switching outputs for greater application flexibility
- Fast, easy commissioning due to SOPAS software



#### Features

|                                    |                          |
|------------------------------------|--------------------------|
| Field of application:              | Security, Semi-Outdoor   |
| Version:                           | Short Range              |
| Light source:                      | Infrared (905 nm)        |
| Laser class:                       | 1 (IEC 60825-1 (2007-3)) |
| Field of view:                     | 270 °                    |
| Scanning frequency:                | 25 Hz / 50 Hz            |
| Angular resolution:                | 0.25 °<br>0.5 °          |
| Heating:                           | Yes                      |
| Operating range:                   | 0.5 m ... 20 m           |
| Max. range with 10 % reflectivity: | 18 m                     |
| Amount of evaluated echoes:        | 2                        |
| Fog correction:                    | Yes                      |

#### Performance

|                                  |            |
|----------------------------------|------------|
| Response time:                   | ≥ 20 ms    |
| Detectable object shape:         | Almost any |
| Systematic error <sup>1)</sup> : | ± 30 mm    |

|                                   |                  |
|-----------------------------------|------------------|
| Statistical error <sup>2)</sup> : | ± 12 mm          |
| Integrated application:           | Field evaluation |
| Number of field sets:             | 10 fields        |
| Simultaneous processing cases:    | 10               |

1) 2)  
Typical value; actual value depends on environmental conditions.

## Interfaces

|                                           |                                                                                                      |
|-------------------------------------------|------------------------------------------------------------------------------------------------------|
| Serial (RS-232):                          | ✓                                                                                                    |
| Function (Serial (RS-232)):               | Host, AUX                                                                                            |
| Data transmission rate (Serial (RS-232)): | 9.6 kBaud ... 115.2 kBaud                                                                            |
| Ethernet:                                 | ✓                                                                                                    |
| Function (Ethernet):                      | Host                                                                                                 |
| Data transmission rate (Ethernet):        | 10/100 Mbit                                                                                          |
| Protocol (Ethernet):                      | TCP/IP, OPC                                                                                          |
| CAN bus:                                  | ✓                                                                                                    |
| Function (CAN bus):                       | Outputs extension                                                                                    |
| PROFIBUS DP:                              | -                                                                                                    |
| PROFINET:                                 | -                                                                                                    |
| DeviceNet:                                | -                                                                                                    |
| Switching inputs:                         | 4 (2 x IN, 2 x increment (1-phase))                                                                  |
| Switching outputs:                        | 3 (2 relay, 1 digital)                                                                               |
| Optical indicators:                       | 1 7-segment display (plus 5 LEDs showing device status, contamination warning and initial condition) |

## Mechanics/electronics

|                        |                                   |
|------------------------|-----------------------------------|
| Electrical connection: | 1 M12 circular plug-in connector  |
| Operating voltage:     | 9 V DC ... 30 V DC                |
| Power consumption:     | 60 W                              |
| Housing color:         | Black (RAL 9005)                  |
| Enclosure rating:      | IP 67 (EN 60529, Section 14.2.5)  |
| Protection class:      | III (EN 50178 (1997;10))          |
| Weight:                | 1.1 kg, without connecting cables |
| Dimensions:            | 105 mm x 102 mm x 162 mm          |


## Ambient data

|                                      |                                              |
|--------------------------------------|----------------------------------------------|
| Object remission:                    | 2 % ... > 1,000 % (reflectors)               |
| Electromagnetic compatibility (EMC): | (EN 61000-6-2:2005) (EN 61000-6-4 (2007-01)) |
| Vibration resistance:                | (EN 60068-2-6 (1995-04))                     |
| Shock resistance:                    | (EN 60068-2-27 (1993-03))                    |
| Ambient operating temperature:       | -30 °C ... 50 °C                             |
| Storage temperature:                 | -30 °C ... 70 °C                             |
| Ambient light safety:                | 40,000 lx                                    |

## General notes

|              |                                       |
|--------------|---------------------------------------|
| Note on use: | Not suitable for personnel protection |
|--------------|---------------------------------------|

Operating range diagram



**Australia**

Phone +61 3 9457 0600  
1800 334 802 – tollfree  
E-Mail sales@sick.com.au

**Belgium/Luxembourg**

Phone +32 (0)2 466 55 66  
E-Mail info@sick.be

**Brasil**

Phone +55 11 3215-4900  
E-Mail sac@sick.com.br

**Canada**

Phone +1 905 771 14 44  
E-Mail information@sick.com

**Ceská Republika**

Phone +420 2 57 91 18 50  
E-Mail sick@sick.cz

**China**

Phone +86 4000 121 000  
E-Mail info.china@sick.net.cn  
Phone +852-2153 6300  
E-Mail ghk@sick.com.hk

**Danmark**

Phone +45 45 82 64 00  
E-Mail sick@sick.dk

**Deutschland**

Phone +49 211 5301-301  
E-Mail kundenservice@sick.de

**España**

Phone +34 93 480 31 00  
E-Mail info@sick.es

**France**

Phone +33 1 64 62 35 00  
E-Mail info@sick.fr

**Great Britain**

Phone +44 (0)1727 831121  
E-Mail info@sick.co.uk

**India**

Phone +91-22-4033 8333  
E-Mail info@sick-india.com

**Israel**

Phone +972-4-6801000  
E-Mail info@sick-sensors.com

**Italia**

Phone +39 02 27 43 41  
E-Mail info@sick.it

**Japan**

Phone +81 (0)3 3358 1341  
E-Mail support@sick.jp

**Magyarország**

Phone +36 1 371 2680  
E-Mail office@sick.hu

**Nederlands**

Phone +31 (0)30 229 25 44  
E-Mail info@sick.nl

**Norge**

Phone +47 67 81 50 00  
E-Mail austefjord@sick.no

**Österreich**

Phone +43 (0)22 36 62 28 8-0  
E-Mail office@sick.at

**Polska**

Phone +48 22 837 40 50  
E-Mail info@sick.pl

**România**

Phone +40 356 171 120  
E-Mail office@sick.ro

**Russia**

Phone +7-495-775-05-30  
E-Mail info@sick.ru

**Schweiz**

Phone +41 41 619 29 39  
E-Mail contact@sick.ch

**Singapore**

Phone +65 6744 3732  
E-Mail admin@sicksgp.com.sg

**Slovenija**

Phone +386 (0)1-47 69 990  
E-Mail office@sick.si

**South Africa**

Phone +27 11 472 3733  
E-Mail info@sickautomation.co.za

**South Korea**

Phone +82 2 786 6321/4  
E-Mail info@sickkorea.net

**Suomi**

Phone +358-9-25 15 800  
E-Mail sick@sick.fi

**Sverige**

Phone +46 10 110 10 00  
E-Mail info@sick.se

**Taiwan**

Phone +886-2-2375-6288  
E-Mail sales@sick.com.tw

**Türkiye**

Phone +90 (216) 528 50 00  
E-Mail info@sick.com.tr

**United Arab Emirates**

Phone +971 (0) 4 8865 878  
E-Mail info@sick.ae

**USA/México**

Phone +1(952) 941-6780  
1 800-325-7425 – tollfree  
E-Mail info@sickusa.com

More representatives and agencies  
at [www.sick.com](http://www.sick.com)