



## Level sensors Optical level switch, MHF15

MHF15-21NG1PSM



**Model Name** > [MHF15-21NG1PSM](#)  
**Part No.** > [1052237](#)



#### At a glance

- Robust level monitoring in liquid without additional requirements
- Small, compact design; no medium calibration required
- Process temperature up to 55 °C, process pressure up to 16 bar
- IP 67 and IP 69K enclosure rating
- Process connection G ½
- Highly medium resistant due to stainless steel housing 1.4404, polysulfone apex
- Output available as PNP or NPN transistor
- FDA-compliant, UL

#### Your benefits

- Small, compact sensor ideal for difficult installation conditions with limited space
- Quick commissioning without medium calibration saves time and money
- No moving mechanical parts reduce maintenance and eliminate the need to recalibrate -- even after long periods of use.



#### Features

|                      |                     |
|----------------------|---------------------|
| Medium:              | Fluids              |
| Measurement:         | Switch              |
| Light source:        | LED                 |
| Type of light:       | Red light           |
| Wave length:         | 650 nm              |
| Process pressure:    | -0.5 bar ... 16 bar |
| Process temperature: | -25 °C ... 55 °C    |
| UL approval:         | ✓                   |

#### Performance

|                |      |
|----------------|------|
| Response time: | 2 ms |
|----------------|------|

#### Mechanical data

|                     |                                       |
|---------------------|---------------------------------------|
| Housing material:   | Stainless steel 1.4404                |
| Process connection: | G 1/2                                 |
| Wetted parts:       | Stainless steel 316L, polysulfon, NBR |

#### Electrical data

|                   |                                   |
|-------------------|-----------------------------------|
| Enclosure rating: | IP 67: EN 60529, IP 69K: EN 40050 |
| Supply voltage:   | 10 V DC ... 30 V DC <sup>1)</sup> |

|                      |                                                  |
|----------------------|--------------------------------------------------|
| Ripple:              | $\leq 5 \text{ Vpp}$ <sup>2)</sup>               |
| Power consumption:   | $\leq 30 \text{ mA}$ at 24 V without output load |
| Protection class:    | III                                              |
| Output signal:       | 1x PNP <sup>3)</sup>                             |
| Switching mode:      | Normally closed                                  |
| Output current:      | $\leq 100 \text{ mA}$ <sup>4)</sup>              |
| Signal voltage HIGH: | $V_s - 2.9 \text{ V}$                            |
| Signal voltage LOW:  | Approx. 0 V                                      |
| Switching frequency: | 250 Hz <sup>5)</sup>                             |
| Connection type:     | M12x1, 4-pin                                     |


1)  $V_S$  connections reverse-polarity protected 2) May not exceed or fall short of  $V_S$  tolerances 3) 4) Output overcurrent and short-circuit protected 5) With light/dark ratio

1:1

## Ambient data


|                                |                  |
|--------------------------------|------------------|
| Ambient operating temperature: | -25 °C ... 55 °C |
| Ambient storage temperature:   | -25 °C ... 70 °C |

## Dimensional drawing




Dimensions in mm (inch)

Connection type



Connection diagram



**Australia**

Phone +61 3 9457 0600  
1800 334 802 – tollfree  
E-Mail sales@sick.com.au

**Belgium/Luxembourg**

Phone +32 (0)2 466 55 66  
E-Mail info@sick.be

**Brasil**

Phone +55 11 3215-4900  
E-Mail sac@sick.com.br

**Canada**

Phone +1 905 771 14 44  
E-Mail information@sick.com

**Ceská Republika**

Phone +420 2 57 91 18 50  
E-Mail sick@sick.cz

**China**

Phone +86 4000 121 000  
E-Mail info.china@sick.net.cn  
Phone +852-2153 6300  
E-Mail ghk@sick.com.hk

**Danmark**

Phone +45 45 82 64 00  
E-Mail sick@sick.dk

**Deutschland**

Phone +49 211 5301-301  
E-Mail kundenservice@sick.de

**España**

Phone +34 93 480 31 00  
E-Mail info@sick.es

**France**

Phone +33 1 64 62 35 00  
E-Mail info@sick.fr

**Great Britain**

Phone +44 (0)1727 831121  
E-Mail info@sick.co.uk

**India**

Phone +91-22-4033 8333  
E-Mail info@sick-india.com

**Israel**

Phone +972-4-6801000  
E-Mail info@sick-sensors.com

**Italia**

Phone +39 02 27 43 41  
E-Mail info@sick.it

**Japan**

Phone +81 (0)3 3358 1341  
E-Mail support@sick.jp

**Magyarország**

Phone +36 1 371 2680  
E-Mail office@sick.hu

**Nederlands**

Phone +31 (0)30 229 25 44  
E-Mail info@sick.nl

**Norge**

Phone +47 67 81 50 00  
E-Mail austefjord@sick.no

**Österreich**

Phone +43 (0)22 36 62 28 8-0  
E-Mail office@sick.at

**Polska**

Phone +48 22 837 40 50  
E-Mail info@sick.pl

**România**

Phone +40 356 171 120  
E-Mail office@sick.ro

**Russia**

Phone +7-495-775-05-30  
E-Mail info@sick.ru

**Schweiz**

Phone +41 41 619 29 39  
E-Mail contact@sick.ch

**Singapore**

Phone +65 6744 3732  
E-Mail admin@sicksgp.com.sg

**Slovenija**

Phone +386 (0)1-47 69 990  
E-Mail office@sick.si

**South Africa**

Phone +27 11 472 3733  
E-Mail info@sickautomation.co.za

**South Korea**

Phone +82 2 786 6321/4  
E-Mail info@sickkorea.net

**Suomi**

Phone +358-9-25 15 800  
E-Mail sick@sick.fi

**Sverige**

Phone +46 10 110 10 00  
E-Mail info@sick.se

**Taiwan**

Phone +886-2-2375-6288  
E-Mail sales@sick.com.tw

**Türkiye**

Phone +90 (216) 528 50 00  
E-Mail info@sick.com.tr

**United Arab Emirates**

Phone +971 (0) 4 8865 878  
E-Mail info@sick.ae

**USA/México**

Phone +1(952) 941-6780  
1 800-325-7425 – tollfree  
E-Mail info@sickusa.com

More representatives and agencies  
at [www.sick.com](http://www.sick.com)