





## Advanced automation light grids MLG, MLG Standard

MLG3-3120F511



**Model Name** > [MLG3-3120F511](#)  
**Part No.** > [1060133](#)



#### At a glance

- Up to 3 x PNP or NPN switching outputs
- Resolutions of 10 / 20 / 30 / 50 mm and customer-specific resolutions
- Working range up to 8.5 m
- Detection heights of over 3 m and up to 240 beams possible
- Short response time
- Automatic teach during power on

#### Your benefits

- Easy-to-see status information helps avoid interrupting operation, saves costs
- Different beam separation options, detection heights and output configurations ensure a reliable solution
- Integrated interfaces reduce cabling time and costs
- A fully modular system guarantees the optimal solution for the customer



#### Features

|                                  |                             |
|----------------------------------|-----------------------------|
| Technology:                      | Sender/receiver             |
| Task:                            | Measurement light grid      |
| Minimum detectable object (MDO): | Parallel beam: $\geq 35$ mm |
| Beam separation:                 | 30 mm                       |
| Number of beams:                 | 105                         |
| Detection height:                | 3,120 mm                    |
| Configuration:                   | Standard (switching)        |

#### Performance

|                               |                                |
|-------------------------------|--------------------------------|
| Maximum range <sup>1)</sup> : | 7 m                            |
| Minimum range:                | Parallel beam: $\geq 0$ mm     |
| Response time <sup>2)</sup> : | Parallel beam: $\geq 16.75$ ms |
| Working range:                | 5 m                            |

<sup>1)</sup> No reserve for environmental issue and deterioration of the diode    <sup>2)</sup> With resistive load

#### Interfaces

|                  |                      |
|------------------|----------------------|
| Output type:     | 1 x PNP              |
| Connection type: | Connector M12, 5-pin |
| IO-Link:         | 0                    |

## Mechanics/electronics

---

|                                            |                                                                                                       |
|--------------------------------------------|-------------------------------------------------------------------------------------------------------|
| Wave length:                               | IR 880 nm                                                                                             |
| Supply voltage Vs:                         | DC 18 V ... 30 V                                                                                      |
| Power consumption sender <sup>1)</sup> :   | 350 mA                                                                                                |
| Power consumption receiver <sup>2)</sup> : | 415 mA                                                                                                |
| Ripple:                                    | < 5 Vpp                                                                                               |
| Output current I <sub>max</sub> :          | 100 mA                                                                                                |
| Output load capacitive:                    | 100 nF                                                                                                |
| Output load inductive:                     | 1 H                                                                                                   |
| Initialization time:                       | 1 s                                                                                                   |
| Dimensions (W x H x D):                    | 34 mm x 3,214 mm x 29 mm                                                                              |
| Housing material:                          | Aluminum                                                                                              |
| Indication:                                | 7-segment display, LED                                                                                |
| Synchronization:                           | Cable                                                                                                 |
| Enclosure rating:                          | IP 65                                                                                                 |
| Circuit protection:                        | Output Q short-circuit protected, Interference suppression, VS connections reverse-polarity protected |
| Weight:                                    | 7.676 kg                                                                                              |
| Power consumption:                         | 350 mA <sup>3)</sup>                                                                                  |
| Front screen:                              | PMMA                                                                                                  |

1) 2) 3) Without load with 24 V


## Ambient data

---

|                                      |                                                  |
|--------------------------------------|--------------------------------------------------|
| Protection class:                    | III                                              |
| EMC:                                 | EN 60947-5-2                                     |
| Ambient temperature:                 | Operation: -25 ... 55 °C, Storage: -40 ... 70 °C |
| Ambient light safety <sup>1)</sup> : | Direct: ≥12,500 lx, Indirect: ≥50,000 lx         |
| Vibration resistance:                | 5 g, 10 Hz ... 55 Hz (IEC 68-2-6)                |
| Shock load:                          | 10 g/IEC 68-2-29/16 ms                           |

1) Sunlight

## Dimensional drawing



| A                               |                                                   |
|---------------------------------|---------------------------------------------------|
| Distance: MLG edge - first beam |                                                   |
| Beam separation 10 mm           | 49 (1.93)                                         |
| Beam separation 20 mm           | 49 (1.93) <sup>1)</sup> / 59 (2.32) <sup>2)</sup> |
| Beam separation 30 mm           | 69 (2.72)                                         |
| Beam separation 50 mm           | 89 (3.50)                                         |

<sup>1)</sup> With even number of beams.  
<sup>2)</sup> With odd number of beams.

- |1| Detection height (see optical performance)
- |2| Beam separation (10, 20, 30, 50 mm)
- |3| Status indicator: LEDs green, yellow, red
- |4| Indicator panel, 7-segment display
- |5| Connector M12, 5-pin

## Adjustments receiver



- |1| Supply voltage
- |2| Device error
- |3| No object in the light path
- |4| Pollution indication
- |5| Blocked Beams Hold (BBH)
- |6| Activated teach-in procedure
- |7| ParamMode is active
- |8| standby
- |9| Error: E1 = sync. error; E2 = less receiver signal; E9 = defect



**Australia**

Phone +61 3 9457 0600  
1800 334 802 – tollfree  
E-Mail sales@sick.com.au

**Belgium/Luxembourg**

Phone +32 (0)2 466 55 66  
E-Mail info@sick.be

**Brasil**

Phone +55 11 3215-4900  
E-Mail sac@sick.com.br

**Canada**

Phone +1 905 771 14 44  
E-Mail information@sick.com

**Ceská Republika**

Phone +420 2 57 91 18 50  
E-Mail sick@sick.cz

**China**

Phone +86 4000 121 000  
E-Mail info.china@sick.net.cn  
Phone +852-2153 6300  
E-Mail ghk@sick.com.hk

**Danmark**

Phone +45 45 82 64 00  
E-Mail sick@sick.dk

**Deutschland**

Phone +49 211 5301-301  
E-Mail kundenservice@sick.de

**España**

Phone +34 93 480 31 00  
E-Mail info@sick.es

**France**

Phone +33 1 64 62 35 00  
E-Mail info@sick.fr

**Great Britain**

Phone +44 (0)1727 831121  
E-Mail info@sick.co.uk

**India**

Phone +91-22-4033 8333  
E-Mail info@sick-india.com

**Israel**

Phone +972-4-6801000  
E-Mail info@sick-sensors.com

**Italia**

Phone +39 02 27 43 41  
E-Mail info@sick.it

**Japan**

Phone +81 (0)3 3358 1341  
E-Mail support@sick.jp

**Magyarország**

Phone +36 1 371 2680  
E-Mail office@sick.hu

**Nederlands**

Phone +31 (0)30 229 25 44  
E-Mail info@sick.nl

**Norge**

Phone +47 67 81 50 00  
E-Mail austefjord@sick.no

**Österreich**

Phone +43 (0)22 36 62 28 8-0  
E-Mail office@sick.at

**Polska**

Phone +48 22 837 40 50  
E-Mail info@sick.pl

**România**

Phone +40 356 171 120  
E-Mail office@sick.ro

**Russia**

Phone +7-495-775-05-30  
E-Mail info@sick.ru

**Schweiz**

Phone +41 41 619 29 39  
E-Mail contact@sick.ch

**Singapore**

Phone +65 6744 3732  
E-Mail admin@sicksgp.com.sg

**Slovenija**

Phone +386 (0)1-47 69 990  
E-Mail office@sick.si

**South Africa**

Phone +27 11 472 3733  
E-Mail info@sickautomation.co.za

**South Korea**

Phone +82 2 786 6321/4  
E-Mail info@sickkorea.net

**Suomi**

Phone +358-9-25 15 800  
E-Mail sick@sick.fi

**Sverige**

Phone +46 10 110 10 00  
E-Mail info@sick.se

**Taiwan**

Phone +886-2-2375-6288  
E-Mail sales@sick.com.tw

**Türkiye**

Phone +90 (216) 528 50 00  
E-Mail info@sick.com.tr

**United Arab Emirates**

Phone +971 (0) 4 8865 878  
E-Mail info@sick.ae

**USA/México**

Phone +1(952) 941-6780  
1 800-325-7425 – tollfree  
E-Mail info@sickusa.com

More representatives and agencies  
at [www.sick.com](http://www.sick.com)