



## Pressure sensors Pressure transmitter

PBT-RM016SG1SSFALA0V



**Model Name** > [PBT-RM016SG1SSFALA0V](#)  
**Part No.** > [6040934](#)



#### At a glance

- Gauge pressure measurement ranges from 0 ... 0.1 MPa up to 0 ... 60 MPa
- A large variety of available process connections
- No moving parts: No mechanical wear, fatigue-proof, maintenance-free
- Circularly welded, hermetically sealed stainless steel membrane
- Output signal 4 ... 20 mA, 0 ... 5 V or 0 ... 10 V
- Electrical connection M12x1, L-connector acc. to DIN 175301-803 A or flying leads

#### Your benefits

- Compact size takes up less space
- Simple and cost-saving installation
- Available in a wide selection of configurations, enabling a perfect match to individual customer requirements
- Robust design enables higher reliability
- Excellent price-performance ratio



#### Features

|                      |                  |
|----------------------|------------------|
| Pressure type:       | Gauge pressure   |
| Measuring range:     | 0 MPa ... 16 MPa |
| Process temperature: | 0 °C ... 80 °C   |
| Rated temperature:   | 0 °C ... 80 °C   |
| CE-conformity:       | ✓                |
| Output signal:       | 4...20 mA        |

#### Performance

|                |                                       |
|----------------|---------------------------------------|
| Accuracy:      | ≤ +/- 1 % (of span)                   |
| Non-linearity: | 0.5 % (Best Fit Straight Line (BFSL)) |

#### Mechanics/electronics

|                     |                                                                                                            |
|---------------------|------------------------------------------------------------------------------------------------------------|
| Process connection: | G 1/4 A (DIN 3852-E)                                                                                       |
| Wetted parts:       | Pressure Connection: 316 L, Pressure sensor: 316 L (for measurement ranges from 0 ... 10 bar rel: 13-8 PH) |
| Seal:               | FPM/FKM                                                                                                    |
| Pressure port:      | Standard                                                                                                   |
| Housing material:   | 316 L                                                                                                      |
| Enclosure rating:   | IP 65                                                                                                      |
| Connection type:    | L-connector DIN EN 175301-803 A, IP 65                                                                     |

|                       |                                                                                                                                                                                           |
|-----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Supply voltage:       | 8 V DC ... 30 V DC                                                                                                                                                                        |
| Electrical safety:    | Short-circuit protection: QA towards M, Reference conditions: According to IEC 61298-1, Overvoltage protection 32 VDC, 36 VDC with 4 ... 20 mA, Reverse polarity protection: L+ towards M |
| Protection class III: | ✓                                                                                                                                                                                         |

#### Ambient data

---

|                      |                                                             |
|----------------------|-------------------------------------------------------------|
| Ambient temperature: | 0 °C ... 80 °C                                              |
| Shock load:          | 500 g according to IEC 60068-2-27 (mechanical shock)        |
| Vibration load:      | 10 g according to IEC 60068-2-6 (vibration under resonance) |

#### **Australia**

Phone +61 3 9457 0600  
1800 334 802 – tollfree  
E-Mail sales@sick.com.au

#### **Belgium/Luxembourg**

Phone +32 (0)2 466 55 66  
E-Mail info@sick.be

#### **Brasil**

Phone +55 11 3215-4900  
E-Mail sac@sick.com.br

#### **Canada**

Phone +1 905 771 14 44  
E-Mail information@sick.com

#### **Ceská Republika**

Phone +420 2 57 91 18 50  
E-Mail sick@sick.cz

#### **China**

Phone +86 4000 121 000  
E-Mail info.china@sick.net.cn  
Phone +852-2153 6300  
E-Mail ghk@sick.com.hk

#### **Danmark**

Phone +45 45 82 64 00  
E-Mail sick@sick.dk

#### **Deutschland**

Phone +49 211 5301-301  
E-Mail kundenservice@sick.de

#### **España**

Phone +34 93 480 31 00  
E-Mail info@sick.es

#### **France**

Phone +33 1 64 62 35 00  
E-Mail info@sick.fr

#### **Great Britain**

Phone +44 (0)1727 831121  
E-Mail info@sick.co.uk

#### **India**

Phone +91-22-4033 8333  
E-Mail info@sick-india.com

#### **Israel**

Phone +972-4-6801000  
E-Mail info@sick-sensors.com

#### **Italia**

Phone +39 02 27 43 41  
E-Mail info@sick.it

#### **Japan**

Phone +81 (0)3 3358 1341  
E-Mail support@sick.jp

#### **Magyarország**

Phone +36 1 371 2680  
E-Mail office@sick.hu

#### **Nederlands**

Phone +31 (0)30 229 25 44  
E-Mail info@sick.nl

#### **Norge**

Phone +47 67 81 50 00  
E-Mail austefjord@sick.no

#### **Österreich**

Phone +43 (0)22 36 62 28 8-0  
E-Mail office@sick.at

#### **Polska**

Phone +48 22 837 40 50  
E-Mail info@sick.pl

#### **România**

Phone +40 356 171 120  
E-Mail office@sick.ro

#### **Russia**

Phone +7-495-775-05-30  
E-Mail info@sick.ru

#### **Schweiz**

Phone +41 41 619 29 39  
E-Mail contact@sick.ch

#### **Singapore**

Phone +65 6744 3732  
E-Mail admin@sicksgp.com.sg

#### **Slovenija**

Phone +386 (0)1-47 69 990  
E-Mail office@sick.si

#### **South Africa**

Phone +27 11 472 3733  
E-Mail info@sickautomation.co.za

#### **South Korea**

Phone +82 2 786 6321/4  
E-Mail info@sickkorea.net

#### **Suomi**

Phone +358-9-25 15 800  
E-Mail sick@sick.fi

#### **Sverige**

Phone +46 10 110 10 00  
E-Mail info@sick.se

#### **Taiwan**

Phone +886-2-2375-6288  
E-Mail sales@sick.com.tw

#### **Türkiye**

Phone +90 (216) 528 50 00  
E-Mail info@sick.com.tr

#### **United Arab Emirates**

Phone +971 (0) 4 8865 878  
E-Mail info@sick.ae

#### **USA/México**

Phone +1(952) 941-6780  
1 800-325-7425 – tollfree  
E-Mail info@sickusa.com

More representatives and agencies  
at [www.sick.com](http://www.sick.com)