



Pressure sensors  
Pressure transmitter

PFT-SAB1X6AGDSSAAMSSZ



**Model Name** > **PFT-SAB1X6AGDSSAAMSSZ**  
**Part No.** > **6043446**



*Product may differ  
from illustration*

#### At a glance

- Absolute pressure measurement ranges from 0 ... 0.25 bar up to 0 ... 25 bar
- Process temperature up to 125 °C (optional)
- High shock and vibration resistance
- Accuracy 0.5% or 0.25%
- Output signal 4 ... 20 mA, 0 ... 5 V, or 0 ... 10 V
- Zero and span adjustable
- Electrical connection M12x1, L-connector according to DIN 175301-803 A or flying leads

#### Your benefits

- Reliable and highly accurate measurement technology
- Wide application range
- No mechanical wear, fatigue-proof, maintenance-free as no moving parts
- Simple and cost-saving installation
- Optimal solution for individual requirements due to very versatile configurability
- Maximum installation flexibility due to availability of a large range of customary thread types



#### Features

|                      |                   |
|----------------------|-------------------|
| Pressure type:       | Absolute Pressure |
| Measuring range:     | 0 bar ... 1.6 bar |
| Process temperature: | -30 °C ... 100 °C |
| CE-conformity:       | ✓                 |
| Output signal:       | 4...20 mA         |

#### Performance

|                                                     |                                                                                                                       |
|-----------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------|
| Accuracy:                                           | ≤ +/- 0.25 % (of span)                                                                                                |
| Non-linearity:                                      | ≤ +/- 0.2 % (of span (Best Fit Straight Line, BFSL) according to IEC 61298-2)                                         |
| Long-term drift/one-year stability:                 | ≤ +/- 0.2 % of span (at reference conditions)                                                                         |
| Temperature coefficient in rated temperature range: | Mean TC of span ≤ 0.2 % of span/10 K, Mean TC of zero: ≤ 0.2 % of span/10 K (< 0.4 % for pressure ranges ≤ 0.25 bar)  |
| Rated temperature range:                            | 0 °C ... 80 °C                                                                                                        |
| Non-repeatability:                                  | ≤ +/- 0.1 % of span                                                                                                   |
| Response time (10 % ... 90 %):                      | ≤ 1 ms (≤ 10 ms at medium temperatures below < -30°C for pressure ranges up to 25 bar or with flush-mounted membrane) |


## Mechanics/electronics

|                       |                                                                                                                                           |
|-----------------------|-------------------------------------------------------------------------------------------------------------------------------------------|
| Process connection:   | G 1/2 B according to EN 837                                                                                                               |
| Wetted parts:         | Standard: Stainless steel                                                                                                                 |
| Seal:                 | Without seal                                                                                                                              |
| Pressure port:        | Standard                                                                                                                                  |
| Housing material:     | Stainless steel                                                                                                                           |
| Enclosure rating:     | IP 67                                                                                                                                     |
| Connection type:      | M12 x 1, 4-pin, IP 67                                                                                                                     |
| Supply voltage:       | 10 V DC ... 30 V DC                                                                                                                       |
| Electrical safety:    | Short-circuit protection: QA towards M, Protection class: III, Overvoltage protection: 36 V DC, Reverse polarity protection: L+ towards M |
| Dielectric strength:  | 500 V DC, NEC Class 02 power supply (low voltage and low current max. 100 VA even under fault conditions)                                 |
| Protection class III: | ✓                                                                                                                                         |
| Weight sensor:        | 200 g                                                                                                                                     |
| CE-conformity:        | Pressure equipment directive: 97/23/EC, EMC directive: 2004/108/EEC, EN 61326-2-3                                                         |


## Ambient data

|                      |                                                             |
|----------------------|-------------------------------------------------------------|
| Storage temperature: | -40 °C ... 100 °C                                           |
| Ambient temperature: | -20 °C ... 80 °C                                            |
| Shock load:          | 1000 g according to IEC 60068-2-27 (mechanical shock)       |
| Vibration load:      | 20 g according to IEC 60068-2-6 (vibration under resonance) |

## Dimensional drawing process connection



Connection type



#### **Australia**

Phone +61 3 9457 0600  
1800 334 802 – tollfree  
E-Mail sales@sick.com.au

#### **Belgium/Luxembourg**

Phone +32 (0)2 466 55 66  
E-Mail info@sick.be

#### **Brasil**

Phone +55 11 3215-4900  
E-Mail sac@sick.com.br

#### **Canada**

Phone +1 905 771 14 44  
E-Mail information@sick.com

#### **Ceská Republika**

Phone +420 2 57 91 18 50  
E-Mail sick@sick.cz

#### **China**

Phone +86 4000 121 000  
E-Mail info.china@sick.net.cn  
Phone +852-2153 6300  
E-Mail ghk@sick.com.hk

#### **Danmark**

Phone +45 45 82 64 00  
E-Mail sick@sick.dk

#### **Deutschland**

Phone +49 211 5301-301  
E-Mail kundenservice@sick.de

#### **España**

Phone +34 93 480 31 00  
E-Mail info@sick.es

#### **France**

Phone +33 1 64 62 35 00  
E-Mail info@sick.fr

#### **Great Britain**

Phone +44 (0)1727 831121  
E-Mail info@sick.co.uk

#### **India**

Phone +91-22-4033 8333  
E-Mail info@sick-india.com

#### **Israel**

Phone +972-4-6801000  
E-Mail info@sick-sensors.com

#### **Italia**

Phone +39 02 27 43 41  
E-Mail info@sick.it

#### **Japan**

Phone +81 (0)3 3358 1341  
E-Mail support@sick.jp

#### **Magyarország**

Phone +36 1 371 2680  
E-Mail office@sick.hu

#### **Nederlands**

Phone +31 (0)30 229 25 44  
E-Mail info@sick.nl

#### **Norge**

Phone +47 67 81 50 00  
E-Mail austefjord@sick.no

#### **Österreich**

Phone +43 (0)22 36 62 28 8-0  
E-Mail office@sick.at

#### **Polska**

Phone +48 22 837 40 50  
E-Mail info@sick.pl

#### **România**

Phone +40 356 171 120  
E-Mail office@sick.ro

#### **Russia**

Phone +7-495-775-05-30  
E-Mail info@sick.ru

#### **Schweiz**

Phone +41 41 619 29 39  
E-Mail contact@sick.ch

#### **Singapore**

Phone +65 6744 3732  
E-Mail admin@sicksgp.com.sg

#### **Slovenija**

Phone +386 (0)1-47 69 990  
E-Mail office@sick.si

#### **South Africa**

Phone +27 11 472 3733  
E-Mail info@sickautomation.co.za

#### **South Korea**

Phone +82 2 786 6321/4  
E-Mail info@sickkorea.net

#### **Suomi**

Phone +358-9-25 15 800  
E-Mail sick@sick.fi

#### **Sverige**

Phone +46 10 110 10 00  
E-Mail info@sick.se

#### **Taiwan**

Phone +886-2-2375-6288  
E-Mail sales@sick.com.tw

#### **Türkiye**

Phone +90 (216) 528 50 00  
E-Mail info@sick.com.tr

#### **United Arab Emirates**

Phone +971 (0) 4 8865 878  
E-Mail info@sick.ae

#### **USA/México**

Phone +1(952) 941-6780  
1 800-325-7425 – tollfree  
E-Mail info@sickusa.com

More representatives and agencies  
at [www.sick.com](http://www.sick.com)