



## Motor feedback systems rotary HIPERFACE® SRS/SRM50

SRM50-HEV0-K21



**Model Name** > SRM50-HEV0-K21  
**Part No.** > 1037089



*Illustration may differ*

#### At a glance

- Motor feedback systems for the top performance range
- 1,024 sine/ cosine periods per revolution
- Absolute position with a resolution of 32,768 increments per revolution and 4,096 revolutions with the multiturn system
- HIPERFACE® interface: Programming of the position value and electronic type label
- Insert shaft or tapered shaft with various torque supports
- Integrated version, mounted version or stand-alone design
- Certified according to SIL2/PL d (only valid for SRS50S/SRM50S...)
- Conforms to RoHs

#### Your benefits

- Motor feedback system with HIPERFACE® interface
- High shock/vibration resistance thanks to built-in metal code disk
- Consistent motor design due to identical size of single and multiturn design
- Compliance with the new machine directive thanks to use of a motor feedback system certified according to SIL2/PL d
- Very smooth running thanks to maximum ball bearing distance



#### Performance

|                                                   |                                                                                                                         |
|---------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------|
| Number of sine/cosine periods per revolution:     | 1,024                                                                                                                   |
| Number of the absolute ascertainable revolutions: | 4,096 (Multiturn)                                                                                                       |
| Total number of steps:                            | 134,217,728                                                                                                             |
| Measuring step:                                   | 0.3 angular seconds at interpolation of the sine/cosine signals with e.g. 12 Bit                                        |
| Integral non-linearity typ.:                      | ± 45 angular seconds (Error limits for evaluating sine/cosine period) without mechanical tension of the stator coupling |
| Differential non-linearity:                       | ± 7 angular seconds (Non-linearity within a sine/cosine period)                                                         |
| Operating speed:                                  | 6,000 /min, up to which the absolute position can be reliably produced                                                  |
| Available memory area:                            | 128 Byte (EEPROM 512)                                                                                                   |

#### Mechanical data

|                                 |                            |
|---------------------------------|----------------------------|
| Flange type/stator coupling:    | Rubber support             |
| Dimensions:                     | See dimensional drawing    |
| Moment of inertia of the rotor: | 10 gcm <sup>2</sup>        |
| Maximum operating speed:        | 12,000 /min                |
| Maximum angular acceleration:   | 200,000 rad/s <sup>2</sup> |

|                                                               |                                       |
|---------------------------------------------------------------|---------------------------------------|
| Operating torque:                                             | 0.2 Ncm                               |
| Start up torque:                                              | 0.4 Ncm                               |
| Permissible shaft movement, radial, static:                   | ± 0.5 mm                              |
| Permissible shaft movement, radial, dynamic:                  | ± 0.1 mm                              |
| Permissible shaft movement, axial, static:                    | ± 0.75 mm                             |
| Permissible shaft movement, axial, dynamic:                   | ± 0.2 mm                              |
| Life of ball bearings:                                        | 3.6 x 10 <sup>9</sup> revolutions     |
| Connection type:                                              | Stranded cable, 8-pin, radial, 200 mm |
| Shaft version:                                                | Tapered shaft                         |
| Angular motion perpendicular to the rotational axis, static:  | ± 0.005 mm/mm                         |
| Angular motion perpendicular to the rotational axis, dynamic: | ± 0.002 mm/mm                         |

#### Electrical data

|                                           |                     |
|-------------------------------------------|---------------------|
| Electrical interface:                     | HIPERFACE           |
| Operating voltage range/supply Voltage:   | 7 V DC ... 12 V DC  |
| Recommended supply voltage:               | 8 V DC              |
| Output frequency for sine/cosine signals: | 0 kHz ... 200 kHz   |
| Operating power consumption (no load):    | 80 mA <sup>1)</sup> |

<sup>1)</sup> Without load

#### Interfaces

|                                      |                                                                                                        |
|--------------------------------------|--------------------------------------------------------------------------------------------------------|
| Type of code for the absolute value: | Binary                                                                                                 |
| Code sequence:                       | Increasing, for clockwise shaft rotation, looking in direction "A" (see dimensional drawing)           |
| Interface signals:                   | Parameter channel RS 485: digital, Process data channel SIN, REFSIN, COS, REFCOS: analog, differential |

#### Ambient data

|                                 |                                                               |
|---------------------------------|---------------------------------------------------------------|
| Working temperature range:      | -30 °C ... 115 °C                                             |
| Storage temperature range:      | -40 °C ... 125 °C, without package                            |
| Relative humidity/Condensation: | 90 %, Condensation not permitted                              |
| Resistance to shocks:           | 100 g, 6 ms (according to EN 60068-2-27)                      |
| Resistance to vibration:        | 20 g, 10 Hz ... 2,000 Hz (according to EN 60068-2-6)          |
| EMC:                            | According to EN 61000-6-2 and EN 61000-6-3 <sup>1)</sup>      |
| Enclosure rating:               | IP 40, according to IEC 60529, with mating connector inserted |

<sup>1)</sup> The EMC according to the standards quoted is achieved when the motor feedback system is mounted in an electrically conductive housing, which is connected to the central earthing point of the motor controller via a cable screen. This is also where the GND (0 V) connection of the power supply voltage is linked to earth. Users must perform their own tests when other screen designs are used.

Technical drawing of the 1000W motor assembly, showing dimensions in mm (inch) in parentheses. The drawing includes a front view, a side view, and a top view.

**Front View Dimensions:**

- Total length:  $46.1 \pm 0.5$  (1.81)
- Distance from front face to start of mounting flange:  $23 \pm 0.3$  (0.91)
- Distance from front face to center of mounting flange:  $13.8$  (0.54)
- Distance from front face to center of motor shaft:  $10$  (0.39)
- Distance from front face to center of mounting flange:  $9$  (0.35)
- Motor shaft diameter:  $\varnothing 8 f7$  (0.31)
- Motor shaft length:  $\varnothing 5.5 h7$  (0.22)
- Motor shaft thread:  $M4$
- Motor shaft angle:  $9.5^\circ \pm 3'$
- Motor shaft diameter:  $\varnothing 47$  (1.85)

**Side View Dimensions:**

- Mounting flange diameter:  $\varnothing 53 \pm 0.2$  (2.09)
- Mounting flange thickness:  $1$  (0.04)

**Top View Dimensions:**

- Mounting flange diameter:  $\varnothing 53 \pm 0.2$  (2.09)

**Other Features:**

- Mounting flange: Cylindrical screw Torx15 head
- Motor shaft: Torx15 head

All dimensions in mm (inch)

**Australia**

Phone +61 3 9457 0600  
1800 334 802 – tollfree  
E-Mail sales@sick.com.au

**Belgium/Luxembourg**

Phone +32 (0)2 466 55 66  
E-Mail info@sick.be

**Brasil**

Phone +55 11 3215-4900  
E-Mail sac@sick.com.br

**Canada**

Phone +1 905 771 14 44  
E-Mail information@sick.com

**Ceská Republika**

Phone +420 2 57 91 18 50  
E-Mail sick@sick.cz

**China**

Phone +86 4000 121 000  
E-Mail info.china@sick.net.cn  
Phone +852-2153 6300  
E-Mail ghk@sick.com.hk

**Danmark**

Phone +45 45 82 64 00  
E-Mail sick@sick.dk

**Deutschland**

Phone +49 211 5301-301  
E-Mail kundenservice@sick.de

**España**

Phone +34 93 480 31 00  
E-Mail info@sick.es

**France**

Phone +33 1 64 62 35 00  
E-Mail info@sick.fr

**Great Britain**

Phone +44 (0)1727 831121  
E-Mail info@sick.co.uk

**India**

Phone +91-22-4033 8333  
E-Mail info@sick-india.com

**Israel**

Phone +972-4-6801000  
E-Mail info@sick-sensors.com

**Italia**

Phone +39 02 27 43 41  
E-Mail info@sick.it

**Japan**

Phone +81 (0)3 3358 1341  
E-Mail support@sick.jp

**Magyarország**

Phone +36 1 371 2680  
E-Mail office@sick.hu

**Nederlands**

Phone +31 (0)30 229 25 44  
E-Mail info@sick.nl

**Norge**

Phone +47 67 81 50 00  
E-Mail austefjord@sick.no

**Österreich**

Phone +43 (0)22 36 62 28 8-0  
E-Mail office@sick.at

**Polska**

Phone +48 22 837 40 50  
E-Mail info@sick.pl

**România**

Phone +40 356 171 120  
E-Mail office@sick.ro

**Russia**

Phone +7-495-775-05-30  
E-Mail info@sick.ru

**Schweiz**

Phone +41 41 619 29 39  
E-Mail contact@sick.ch

**Singapore**

Phone +65 6744 3732  
E-Mail admin@sicksgp.com.sg

**Slovenija**

Phone +386 (0)1-47 69 990  
E-Mail office@sick.si

**South Africa**

Phone +27 11 472 3733  
E-Mail info@sickautomation.co.za

**South Korea**

Phone +82 2 786 6321/4  
E-Mail info@sickkorea.net

**Suomi**

Phone +358-9-25 15 800  
E-Mail sick@sick.fi

**Sverige**

Phone +46 10 110 10 00  
E-Mail info@sick.se

**Taiwan**

Phone +886-2-2375-6288  
E-Mail sales@sick.com.tw

**Türkiye**

Phone +90 (216) 528 50 00  
E-Mail info@sick.com.tr

**United Arab Emirates**

Phone +971 (0) 4 8865 878  
E-Mail info@sick.ae

**USA/México**

Phone +1(952) 941-6780  
1 800-325-7425 – tollfree  
E-Mail info@sickusa.com

More representatives and agencies  
at [www.sick.com](http://www.sick.com)