



Photoelectric sensors W12G, Photoelectric retro-reflective sensor

WL12G-3P2582S04



Model Name > [WL12G-3P2582S04](#)
Part No. > [1059644](#)



At a glance

- Reliable detection of transparent objects
- IR sender, wave length 850 nm
- Reliable detection of clear materials, e.g. glass ,PET-Bottles
- Static threshold
- Tree threshold operation levels (Mode 1= 40% + Mode 2 =18% +Mode 3 = 10 %), selectable by teach-in via button or external teach-in (ET)

Your benefits

- Reliable detection of transparent objects, including PET bottles and transparent film
- Precise switching characteristics and high-performance object detection provides increased productivity
- Rugged metal housing (optional Teflon® coating available) requires less maintenance due to its resistance to high-pressure cleaning environments
- Highly visible status LEDs simplify commissioning, reduce installation time and provide quick diagnostics information



Features

Sensor/detection principle:	Photoelectric retro-reflective sensor
Dimensions (W x H x D):	15.5 mm x 48.5 mm x 42 mm
Housing design (light emission):	Rectangular
Sensing range max.:	0 m ... 4 m ¹⁾
Type of light:	Infrared light
Light source:	LED ²⁾
Wave length:	850 nm
Light spot diameter (distance):	Ø 25 mm (1.5 m)
Sensitivity adjustment:::	Cable, Teach-in button ^{3) 4) 5)}

¹⁾ PL80A ²⁾ Average service life 100,000 h at Ta = +25 °C ³⁾ Mode I, 40 % attenuation ⁴⁾ Mode II, 18 % attenuation ⁵⁾ Mode I, 10 % attenuation


Mechanics/electronics

Supply voltage:	10 V DC ... 30 V DC ¹⁾
Ripple:	≤ 5 Vpp ²⁾
Power consumption:	≤ 40 mA ³⁾
Output type:	PNP
Switching mode:	Light switching ⁴⁾
Signal voltage PNP HIGH/LOW:	Approx. VS - 2.5 V / 0 V

Output current I _{max} ::	100 mA
Response time:	≤ 333 μs ⁵⁾
Switching frequency:	1,500 Hz ⁶⁾
Connection type:	Connector M12, 5-pin
Circuit protection:::	A, B, C, D ⁷⁾ 8) 9)
Protection class:	II ¹⁰⁾
Weight:	120 g
Polarisation filter:	✓
Special device:	-
Housing material:	Zinc diecast
Optics material:	PMMA
Enclosure rating:	IP 66 IP 67
Special feature:	For transparent objects
Ambient operating temperature:	≤ 60 °C
Ambient storage temperature:	-40 °C ... 75 °C
UL File-No.:	UL No. NRKH.E181493 & cUL No. NRKH7.E181493


¹⁾ Limit values, operation in short-circuit protected network max. 8 A ²⁾ May not exceed or fall short of V_S ³⁾ Without load ⁴⁾ PNP toff 50 ms ⁵⁾ Signal transit time with resistive load
⁶⁾ With light/dark ratio 1:1 ⁷⁾ A = V_S connections reverse-polarity protected ⁸⁾ C = interference suppression ⁹⁾ D = outputs overcurrent and short-circuit protected
¹⁰⁾ Reference voltage 50 V DC

Dimensional drawing




- [1] Optical axis
- [2] LED indicator yellow: Light received
- [3] Green LED indicator: supply voltage active
- [4] M4 threaded mounting hole, 4 mm deep
- [5] Mounting hole, Ø 4.2 mm
- [6] Sensitivity adjustment: poti
- [7] Connection

Adjustments possible




- |2| LED indicator yellow: Light received
- |3| LED indicator, green: power on, teach-in mode I, LED indicator, blue: teach-in mode II
- |6| Single-teach-in button, function
1: teach-in sensitivity on reflector
, function 2: change operation/teach-in mode

Connection diagram




Sensing range diagram



■ Sensing range max.

Connection type



Australia

Phone +61 3 9457 0600
1800 334 802 – tollfree
E-Mail sales@sick.com.au

Belgium/Luxembourg

Phone +32 (0)2 466 55 66
E-Mail info@sick.be

Brasil

Phone +55 11 3215-4900
E-Mail sac@sick.com.br

Canada

Phone +1 905 771 14 44
E-Mail information@sick.com

Ceská Republika

Phone +420 2 57 91 18 50
E-Mail sick@sick.cz

China

Phone +86 4000 121 000
E-Mail info.china@sick.net.cn
Phone +852-2153 6300
E-Mail ghk@sick.com.hk

Danmark

Phone +45 45 82 64 00
E-Mail sick@sick.dk

Deutschland

Phone +49 211 5301-301
E-Mail kundenservice@sick.de

España

Phone +34 93 480 31 00
E-Mail info@sick.es

France

Phone +33 1 64 62 35 00
E-Mail info@sick.fr

Great Britain

Phone +44 (0)1727 831121
E-Mail info@sick.co.uk

India

Phone +91-22-4033 8333
E-Mail info@sick-india.com

Israel

Phone +972-4-6801000
E-Mail info@sick-sensors.com

Italia

Phone +39 02 27 43 41
E-Mail info@sick.it

Japan

Phone +81 (0)3 3358 1341
E-Mail support@sick.jp

Magyarország

Phone +36 1 371 2680
E-Mail office@sick.hu

Nederlands

Phone +31 (0)30 229 25 44
E-Mail info@sick.nl

Norge

Phone +47 67 81 50 00
E-Mail austefjord@sick.no

Österreich

Phone +43 (0)22 36 62 28 8-0
E-Mail office@sick.at

Polska

Phone +48 22 837 40 50
E-Mail info@sick.pl

România

Phone +40 356 171 120
E-Mail office@sick.ro

Russia

Phone +7-495-775-05-30
E-Mail info@sick.ru

Schweiz

Phone +41 41 619 29 39
E-Mail contact@sick.ch

Singapore

Phone +65 6744 3732
E-Mail admin@sicksgp.com.sg

Slovenija

Phone +386 (0)1-47 69 990
E-Mail office@sick.si

South Africa

Phone +27 11 472 3733
E-Mail info@sickautomation.co.za

South Korea

Phone +82 2 786 6321/4
E-Mail info@sickkorea.net

Suomi

Phone +358-9-25 15 800
E-Mail sick@sick.fi

Sverige

Phone +46 10 110 10 00
E-Mail info@sick.se

Taiwan

Phone +886-2-2375-6288
E-Mail sales@sick.com.tw

Türkiye

Phone +90 (216) 528 50 00
E-Mail info@sick.com.tr

United Arab Emirates

Phone +971 (0) 4 8865 878
E-Mail info@sick.ae

USA/México

Phone +1(952) 941-6780
1 800-325-7425 – tollfree
E-Mail info@sickusa.com

More representatives and agencies
at www.sick.com