ONLINE DATA SHEET
www.mysick.com

Photoelectric sensors
W12-2 Laser, Photoelectric retro-reflective sensor, autocollimation

WL12L-2P130

SICK
Sensor Intelligence.

Photoelectric sensors
W12-2 Laser, Photoelectric retro-reflective sensor, autocollimation

Model Name > WL12L-2P130
Part No. > 1022041

Illustration may differ

At a glance

- Laser protection class 1 or 2
- Autocollimation optics
- Rugged sensors for industrial use
- Highly visible laser light spot for versatile detection of objects
- Rugged die-cast zinc housing with optional Teflon® coating
- Versatile mounting options due to dovetail mounting - mounting holes and oblong holes
- Highly visible status LEDs
- Adjustable sensing range and focus

Your benefits

Reliable detection of all types of objects

High immunity to optical interference ensures fewer false readings and less downtime

Highly visible laser light spot provides quick and easy setup

Highly visible status LEDs simplify commissioning and reduce installation time

Rugged metal housing (optional Teflon® coating available) requires less maintenance due to its resistance to high-pressure cleaning environments

Laser protection class 1 or 2 for eye safety

Rotatable connectors simplify installation

Features

Sensor/detection principle:	Photoelectric retro-reflective sensor, autocollimation
Dimensions (W x H x D):	15 mm x 49 mm x 41.5 mm
Housing design (light emission):	Rectangular
Sensing range max.:	0 m ... 18 m [1)]
Type of light:	Visible red light
Light source:	Laser [2)]
Light spot (distance):	0.8 mm (300 mm)
Wave length:	650 nm
Sensitivity adjustment:	Potentiometer

© SICK AG. Subject to change without notice.

[1] PL80A [2] Average service life 50,000 h at Ta = +25 °C

Mechanics/electronics

Supply voltage:	10 V DC ... 30 V DC [1]
Ripple:	≤ 5 Vpp [2]
Power consumption:	≤ 55 mA [3]
Output type:	NPN, Dark-switching, 0 V or not connected, light-switching, PNP, Light-switching, Selectable via L/D control wire, Uv, dark-switching
Signal voltage PNP HIGH/LOW:	Uv - < 2.9 V, Uv V/0 V ≤ 1.5 V
Signal voltage NPN HIGH/LOW:	Uv - < 2.9 V, Uv V/0 V ≤ 1.5 V
Output current Imax.:	100 mA
Response time:	≤ 200 µs [4]
Switching frequency:	2,500 Hz [5]
Connection type:	Cable, 4-wire, 2 m
Circuit protection:::	A, C, D [6] [7] [8]
Protection class:	II
Polarisation filter:	✓
Enclosure rating:	IP 67 IP 69K
Ambient operating temperature:	-10 °C ... 50 °C
Ambient storage temperature:	-25 °C ... 75 °C
UL File-No.:	UL No. NRKH.E181493, CDRH-Konform (0312012-00)

[1] Limit values [2] May not exceed or fall short of V_S [3] Without load [4] Signal transit time with resistive load [5] With light/dark ratio 1:1 [6] A = V_S connections reverse-polarity protected [7] C = interference suppression [8] D = outputs overcurrent and short-circuit protected

© SICK AG. Subject to change without notice.

Dimensional drawing



|1| Operating indicator, green
|2| LED reception indicator, yellow
|3| Center of optical axis

|5| Mounting hole, Ø 4.2 mm
|6| Focal adjustment
|7| Sensitivity adjustment

Adjustments possible



|1| Operating indicator, green
|2| LED reception indicator, yellow
|6| Focal adjustment
|7| Sensitivity adjustment

© SICK AG. Subject to change without notice.

Characteristic curve



Sensing range diagram



Reflector type

① PL80A
② PL50A
③ PL40A
④ P250
⑤ PL30A
⑥ PL20A
⑦ Reflective tape Diamond Grade

© SICK AG. Subject to change without notice.

Connection type



© SICK AG. Subject to change without notice.

· USmod 4c int40

Australia
Phone +61 3 9457 0600
1800 334 802 – tollfree
E-Mail sales@sick.com.au

Belgium/Luxembourg
Phone +32 (0)2 466 55 66
E-Mail info@sick.be

Brasil
Phone +55 11 3215-4900
E-Mail sac@sick.com.br

Canada
Phone +1 905 771 14 44
E-Mail information@sick.com

Ceská Republika
Phone +420 2 57 91 18 50
E-Mail sick@sick.cz

China
Phone +86 4000 121 000
E-Mail info.china@sick.net.cn
Phone +852-2153 6300
E-Mail ghk@sick.com.hk

Danmark
Phone +45 45 82 64 00
E-Mail sick@sick.dk

Deutschland
Phone +49 211 5301-301
E-Mail kundenservice@sick.de

España
Phone +34 93 480 31 00
E-Mail info@sick.es

France
Phone +33 1 64 62 35 00
E-Mail info@sick.fr

Great Britain
Phone +44 (0)1727 831121
E-Mail info@sick.co.uk

India
Phone +91–22–4033 8333
E-Mail info@sick-india.com

Israel
Phone +972-4-6801000
E-Mail info@sick-sensors.com

Italia
Phone +39 02 27 43 41
E-Mail info@sick.it

Japan
Phone +81 (0)3 3358 1341
E-Mail support@sick.jp

Magyarország
Phone +36 1 371 2680
E-Mail office@sick.hu

Nederlands
Phone +31 (0)30 229 25 44
E-Mail info@sick.nl

Norge
Phone +47 67 81 50 00
E-Mail austefjord@sick.no

Österreich
Phone +43 (0)22 36 62 28 8-0
E-Mail office@sick.at

Polska
Phone +48 22 837 40 50
E-Mail info@sick.pl

România
Phone +40 356 171 120
E-Mail office@sick.ro

Russia
Phone +7-495-775-05-30
E-Mail info@sick.ru

Schweiz
Phone +41 41 619 29 39
E-Mail contact@sick.ch

Singapore
Phone +65 6744 3732
E-Mail admin@sicksgp.com.sg

Slovenija
Phone +386 (0)1-47 69 990
E-Mail office@sick.si

South Africa
Phone +27 11 472 3733
E-Mail info@sickautomation.co.za

South Korea
Phone +82 2 786 6321/4
E-Mail info@sickkorea.net

Suomi
Phone +358-9-25 15 800
E-Mail sick@sick.fi

Sverige
Phone +46 10 110 10 00
E-Mail info@sick.se

Taiwan
Phone +886-2-2375-6288
E-Mail sales@sick.com.tw

Türkiye
Phone +90 (216) 528 50 00
E-Mail info@sick.com.tr

United Arab Emirates
Phone +971 (0) 4 8865 878
E-Mail info@sick.ae

USA/México
Phone +1(952) 941-6780
1 800-325-7425 – tollfree
E-Mail info@sickusa.com

More representatives and agencies
at **www.sick.com**

SICK
Sensor Intelligence.