



Photoelectric sensors W260, Photoelectric retro-reflective sensor

WL260-S270



Model Name > [WL260-S270](#)
Part No. > [6020767](#)



Illustration may differ

At a glance

- Long sensing ranges
- Mounting bracket and reflector included with delivery
- Selectable operation mode (light/dark)
- Optional time stages
- M12 connector or terminal chamber
- Versions for 10 - 30 V DC or 12 - 240 V DC/ 24 – 240 V AC voltage supply

Your benefits

- High operating reserve provides increased reliability
- Configuration controls are protected by a cover, ensuring less damage and a longer service life
- Easily accessible terminal chamber for electrical connections simplifies installation
- Simplified integration due to mounting compatibility since variants for DC or DC/AC voltage supply are available in the same design
- Polarizing filter ensures reliable detection, even with shiny targets



Features

Sensor/detection principle:	Photoelectric retro-reflective sensor
Dimensions (W x H x D):	25 mm x 78 mm x 63 mm
Housing design (light emission):	Rectangular
Sensing range max.:	0.01 m ... 15 m ¹⁾
Sensing range::	0.01 m ... 10 m, 0.01 m ... 13 m ^{2) 3)}
Type of light:	Visible red light
Light source:	LED ⁴⁾
Light spot (distance):	300 mm (10 m)
Sensitivity adjustment:	Potentiometer, 270°
Angle of dispersion:	1.7 °

^{1) 3)} PL80A ²⁾ P250 ⁴⁾ Average service life 100,000 h at Ta = +25 °C


Mechanics/electronics

Supply voltage::	12 V DC ... 240 V DC, 24 V AC ... 240 V AC ^{1) 2)}
Power consumption:	≤ 5 VA
Output type:	Relay, Light-switching, change-over contacts, electrically isolated ³⁾
Switching current (switching voltage):	3 A (240 V AC), 3 A (30 V DC)


Response time:	≤ 20 ms
Switching frequency:	25 Hz ⁴⁾
Connection type:	Cable gland
Circuit protection:	A, C ^{5) 6)}
Protection class:	II ⁷⁾
Weight:	120 g
Polarisation filter:	✓
Interference emission:	Level EN 61000-6-3 Residential and commercial areas
Housing material:	ABS
Optics material:	PMMA
Enclosure rating:	IP 67
Items supplied:	Mounting bracket BEF-W260, Reflector P250
Usage category:	AC-15, DC-13, According to EN 60947-1
Ambient operating temperature:	-25 °C ... 55 °C
Ambient storage temperature:	-40 °C ... 70 °C
UL File-No.:	EN50081-1, 242356

1) 2) ±10 % ³⁾ Provide suitable spark suppression for inductive or capacitive loads ⁴⁾ With light/dark ratio 1:1 ⁵⁾ A = V_S connections reverse-polarity protected ⁶⁾ C = interference suppression ⁷⁾ Rated voltage 250 V AC/DC

Dimensional drawing




Adjustments possible




- |3| LED indicator orange: WE 260:
switching output activeWS 260: sender active
- |5| Sensitivity adjustment
- |8| Terminals


Connection diagram



Characteristic curve




Sensing range diagram



Reflector type		Operating range
1	PL 80 A	0.01 ... 13.0 m
2	P 250	0.01 ... 10.0 m
3	PL 50 A or PL 40 A	0.01 ... 11.5 m
4	PL 30 A or PL 31 A	0.01 ... 8.5 m
5	PL 20 A	0.01 ... 6.5 m
6	Reflective tape Diamond Grade	0.02 ... 5.3 m

Connection type



Australia

Phone +61 3 9457 0600
1800 334 802 – tollfree
E-Mail sales@sick.com.au

Belgium/Luxembourg

Phone +32 (0)2 466 55 66
E-Mail info@sick.be

Brasil

Phone +55 11 3215-4900
E-Mail sac@sick.com.br

Canada

Phone +1 905 771 14 44
E-Mail information@sick.com

Ceská Republika

Phone +420 2 57 91 18 50
E-Mail sick@sick.cz

China

Phone +86 4000 121 000
E-Mail info.china@sick.net.cn
Phone +852-2153 6300
E-Mail ghk@sick.com.hk

Danmark

Phone +45 45 82 64 00
E-Mail sick@sick.dk

Deutschland

Phone +49 211 5301-301
E-Mail kundenservice@sick.de

España

Phone +34 93 480 31 00
E-Mail info@sick.es

France

Phone +33 1 64 62 35 00
E-Mail info@sick.fr

Great Britain

Phone +44 (0)1727 831121
E-Mail info@sick.co.uk

India

Phone +91-22-4033 8333
E-Mail info@sick-india.com

Israel

Phone +972-4-6801000
E-Mail info@sick-sensors.com

Italia

Phone +39 02 27 43 41
E-Mail info@sick.it

Japan

Phone +81 (0)3 3358 1341
E-Mail support@sick.jp

Magyarország

Phone +36 1 371 2680
E-Mail office@sick.hu

Nederlands

Phone +31 (0)30 229 25 44
E-Mail info@sick.nl

Norge

Phone +47 67 81 50 00
E-Mail austefjord@sick.no

Österreich

Phone +43 (0)22 36 62 28 8-0
E-Mail office@sick.at

Polska

Phone +48 22 837 40 50
E-Mail info@sick.pl

România

Phone +40 356 171 120
E-Mail office@sick.ro

Russia

Phone +7-495-775-05-30
E-Mail info@sick.ru

Schweiz

Phone +41 41 619 29 39
E-Mail contact@sick.ch

Singapore

Phone +65 6744 3732
E-Mail admin@sicksgp.com.sg

Slovenija

Phone +386 (0)1-47 69 990
E-Mail office@sick.si

South Africa

Phone +27 11 472 3733
E-Mail info@sickautomation.co.za

South Korea

Phone +82 2 786 6321/4
E-Mail info@sickkorea.net

Suomi

Phone +358-9-25 15 800
E-Mail sick@sick.fi

Sverige

Phone +46 10 110 10 00
E-Mail info@sick.se

Taiwan

Phone +886-2-2375-6288
E-Mail sales@sick.com.tw

Türkiye

Phone +90 (216) 528 50 00
E-Mail info@sick.com.tr

United Arab Emirates

Phone +971 (0) 4 8865 878
E-Mail info@sick.ae

USA/México

Phone +1(952) 941-6780
1 800-325-7425 – tollfree
E-Mail info@sickusa.com

More representatives and agencies
at www.sick.com