



Photoelectric sensors  
W2 Slim, Photoelectric retro-reflective sensor,  
Standard optics

WL2S-F011S03



**Model Name** > [WL2S-F011S03](#)  
**Part No.** > [1056350](#)



*Illustration may differ*

#### At a glance

- Small, sharply defined light spot of Ø 10 mm at 100 mm distance
- Maximum sensing range of 800 mm on the small PL20A reflector
- Fast response time of 0.6 ms

#### Your benefits

- PinPoint LED provides a sharply defined, highly visible light spot for quick and easy alignment
- Compact design saves space while providing long sensing ranges
- High immunity to crosstalk with another device enables the installation of several sensors in a single area
- Ball-and-socket bracket for quick and easy alignment



#### Features

|                                  |                                                        |
|----------------------------------|--------------------------------------------------------|
| Sensor/detection principle:      | Photoelectric retro-reflective sensor, Standard optics |
| Dimensions (W x H x D):          | 7.6 mm x 25.1 mm x 12.5 mm                             |
| Housing design (light emission): | Rectangular                                            |
| Sensing range max.:              | 0.04 m ... 0.8 m <sup>1)</sup>                         |
| Sensing range:                   | 0.04 m ... 0.8 m <sup>2)</sup>                         |
| Type of light:                   | Visible red light                                      |
| Light source:                    | PinPoint LED <sup>3)</sup>                             |
| Wave length:                     | 660 nm                                                 |
| Focus adjustable:                | ✓                                                      |
| Light spot size (distance):      | Ø 10 mm (100 mm)                                       |

<sup>1) 2)</sup> PL20A <sup>3)</sup> Average service life 75,000 h at T<sub>A</sub> = +25 °C


#### Mechanics/electronics

|                                   |                                                      |
|-----------------------------------|------------------------------------------------------|
| Supply voltage:                   | 10 V DC ... 30 V DC <sup>1)</sup>                    |
| Ripple:                           | ≤ 5 Vpp <sup>2)</sup>                                |
| Output type:                      | PNP                                                  |
| Switching mode:                   | Dark-switching                                       |
| Output current I <sub>max</sub> : | ≤ 50 mA                                              |
| Response time:                    | < 0.6 ms <sup>3)</sup>                               |
| Switching frequency:              | 800 Hz <sup>4)</sup>                                 |
| Connection type:                  | Cable with connector M8, 3-pin, 300 mm <sup>5)</sup> |

|                                |                             |
|--------------------------------|-----------------------------|
| Cable material:                | PVC                         |
| Cable diameter:                | Ø 2.4 mm                    |
| Circuit protection:::          | A, C, D <sup>6) 7) 8)</sup> |
| Weight:                        | 20 g                        |
| Polarisation filter:           | ✓                           |
| Reverse polarity protection:   | ✓                           |
| Short-circuit protection:      | ✓                           |
| Housing material:              | ABS, Plastic                |
| Optics material:               | PMMA                        |
| Enclosure rating:              | IP 67<br>IP 69K             |
| Ambient operating temperature: | -20 °C ... 50 °C            |
| Ambient storage temperature:   | -40 °C ... 75 °C            |


<sup>1)</sup> Limit values   <sup>2)</sup> May not exceed or fall short of  $V_S$  tolerances   <sup>3)</sup> Signal transit time with resistive load   <sup>4)</sup> With light/dark ratio 1:1   <sup>5)</sup> Do not bend below 0 °C   <sup>6)</sup> A = V  
<sup>7)</sup> C = interference suppression   <sup>8)</sup> D = outputs overcurrent and short-circuit protected

## Dimensional drawing




- |1| Mounting hole, Ø approx. 3.1 mm
- |2| LED signal strength indicator
- |3| Optical axis, receiver
- |4| Optical axis, sender


Connection diagram



Characteristic curve



Sensing range diagram




- |1| PL40A
- |2| PL30A
- |3| PL20F
- |4| PL22
- |5| PL10F

Reflector type

- ① PL40A
- ② PL30A
- ③ PL20F
- ④ PL22
- ⑤ PL10F <sup>1)</sup>

<sup>1)</sup> With reflector arrangement along the sensor axis.

Connection type



#### **Australia**

Phone +61 3 9457 0600  
1800 334 802 – tollfree  
E-Mail sales@sick.com.au

#### **Belgium/Luxembourg**

Phone +32 (0)2 466 55 66  
E-Mail info@sick.be

#### **Brasil**

Phone +55 11 3215-4900  
E-Mail sac@sick.com.br

#### **Canada**

Phone +1 905 771 14 44  
E-Mail information@sick.com

#### **Ceská Republika**

Phone +420 2 57 91 18 50  
E-Mail sick@sick.cz

#### **China**

Phone +86 4000 121 000  
E-Mail info.china@sick.net.cn  
Phone +852-2153 6300  
E-Mail ghk@sick.com.hk

#### **Danmark**

Phone +45 45 82 64 00  
E-Mail sick@sick.dk

#### **Deutschland**

Phone +49 211 5301-301  
E-Mail kundenservice@sick.de

#### **España**

Phone +34 93 480 31 00  
E-Mail info@sick.es

#### **France**

Phone +33 1 64 62 35 00  
E-Mail info@sick.fr

#### **Great Britain**

Phone +44 (0)1727 831121  
E-Mail info@sick.co.uk

#### **India**

Phone +91-22-4033 8333  
E-Mail info@sick-india.com

#### **Israel**

Phone +972-4-6801000  
E-Mail info@sick-sensors.com

#### **Italia**

Phone +39 02 27 43 41  
E-Mail info@sick.it

#### **Japan**

Phone +81 (0)3 3358 1341  
E-Mail support@sick.jp

#### **Magyarország**

Phone +36 1 371 2680  
E-Mail office@sick.hu

#### **Nederlands**

Phone +31 (0)30 229 25 44  
E-Mail info@sick.nl

#### **Norge**

Phone +47 67 81 50 00  
E-Mail austefjord@sick.no

#### **Österreich**

Phone +43 (0)22 36 62 28 8-0  
E-Mail office@sick.at

#### **Polska**

Phone +48 22 837 40 50  
E-Mail info@sick.pl

#### **România**

Phone +40 356 171 120  
E-Mail office@sick.ro

#### **Russia**

Phone +7-495-775-05-30  
E-Mail info@sick.ru

#### **Schweiz**

Phone +41 41 619 29 39  
E-Mail contact@sick.ch

#### **Singapore**

Phone +65 6744 3732  
E-Mail admin@sicksgp.com.sg

#### **Slovenija**

Phone +386 (0)1-47 69 990  
E-Mail office@sick.si

#### **South Africa**

Phone +27 11 472 3733  
E-Mail info@sickautomation.co.za

#### **South Korea**

Phone +82 2 786 6321/4  
E-Mail info@sickkorea.net

#### **Suomi**

Phone +358-9-25 15 800  
E-Mail sick@sick.fi

#### **Sverige**

Phone +46 10 110 10 00  
E-Mail info@sick.se

#### **Taiwan**

Phone +886-2-2375-6288  
E-Mail sales@sick.com.tw

#### **Türkiye**

Phone +90 (216) 528 50 00  
E-Mail info@sick.com.tr

#### **United Arab Emirates**

Phone +971 (0) 4 8865 878  
E-Mail info@sick.ae

#### **USA/México**

Phone +1(952) 941-6780  
1 800-325-7425 – tollfree  
E-Mail info@sickusa.com

More representatives and agencies  
at [www.sick.com](http://www.sick.com)