



## Photoelectric sensors W4-3 Glass, Photoelectric retro-reflective sensor

WLG4-3F3234S05



**Model Name** > [WLG4-3F3234S05](#)  
**Part No.** > [1043538](#)



*Illustration may differ*

#### At a glance

- Fast and reliable setup via teach-in pushbutton
- Continuous threshold adjustment technology to detect objects in changing conditions such as temperature, contamination and reflector wear
- Versions without polarizing filters to better detect depolarizing objects such as PET bottles, CD sleeves and shrink-wrapped, glossy objects

#### Your benefits

- Reliable and quick setting via the push of a button
- Flat housing design eliminates alignment or mounting brackets, which saves time and money
- Low-cost machine integration due to small dimensions that enable mounting in areas with space restrictions
- Quick and easy setup due to highly visible intensive light spot
- The PinPoint LED's well-defined, intense light spot simplifies alignment
- Nearly all transparent objects can be reliably detected



#### Features

|                                  |                                       |
|----------------------------------|---------------------------------------|
| Sensor/detection principle:      | Photoelectric retro-reflective sensor |
| Dimensions (W x H x D):          | 16 mm x 39.5 mm x 12 mm               |
| Housing design (light emission): | Rectangular, Flat                     |
| Sensing range max.:              | 0.01 m ... 4 m <sup>1)</sup>          |
| Sensing range:                   | 0.02 m ... 3.5 m <sup>2)</sup>        |
| Type of light:                   | Visible red light                     |
| Light source:                    | PinPoint LED <sup>3)</sup>            |
| Wave length:                     | 650 nm                                |
| Teach-in:                        | Single teach-in button                |
| Adjustment:                      | Cable, Teach-in                       |

<sup>1) 2)</sup> PL80A <sup>3)</sup> Average service life of 100,000 h at T<sub>A</sub> = +25 °C


#### Mechanics/electronics

|                                     |                                   |
|-------------------------------------|-----------------------------------|
| Supply voltage:                     | 10 V DC ... 30 V DC <sup>1)</sup> |
| Ripple:                             | < 5 Vpp <sup>2)</sup>             |
| Power consumption:                  | ≤ 20 mA <sup>3)</sup>             |
| Output type:                        | PNP                               |
| Switching mode:                     | Dark-switching                    |
| Output current I <sub>max</sub> ..: | ≤ 100 mA                          |

|                                |                                                      |
|--------------------------------|------------------------------------------------------|
| Response time:                 | < 0.5 ms <sup>4)</sup>                               |
| Switching frequency:           | 1,000 Hz <sup>5)</sup>                               |
| Angle of reception:            | 30 °                                                 |
| Attenuation along light beam:  | > 8 %                                                |
| Connection type:               | Cable with connector M8, 4-pin, 100 mm <sup>6)</sup> |
| Cable material:                | PVC                                                  |
| Conductor cross-section:       | 0.14 mm <sup>2</sup>                                 |
| Cable diameter:                | 3.4 mm                                               |
| Circuit protection:::          | A, C, D <sup>7)</sup> <sup>8)</sup> <sup>9)</sup>    |
| Protection class:              | III                                                  |
| Weight:                        | 30 g                                                 |
| Polarisation filter:           | ✓                                                    |
| Special device:                | -                                                    |
| Housing material:              | ABS, Plastic                                         |
| Optics material:               | PMMA                                                 |
| Enclosure rating:              | IP 67<br>IP 66                                       |
| Special feature:               | For transparent objects                              |
| Special features:              | Without polarisation filter                          |
| Ambient operating temperature: | -40 °C ... 60 °C                                     |
| Ambient storage temperature:   | -40 °C ... 75 °C                                     |


<sup>1)</sup> Limit values   <sup>2)</sup> May not exceed or fall short of  $V_S$  tolerances   <sup>3)</sup> Without load   <sup>4)</sup> Signal transit time with resistive load   <sup>5)</sup> With light/dark ratio 1:1   <sup>6)</sup> Do not bend below 0 °C   <sup>7)</sup> A =  $V_S$  connections reverse-polarity protected   <sup>8)</sup> C = interference suppression   <sup>9)</sup> D = outputs overcurrent and short-circuit protected

## Dimensional drawing




- [1] Center of optical axis, sender
- [2] Center of optical axis, receiver
- [3] LED indicator orange: status of received light beam
- [4] Status indicator LED green: power on
- [5] Threaded mounting hole M3
- [6] Connection
- [7] Teach-in button

## Connection diagram



## Connection type



#### **Australia**

Phone +61 3 9457 0600  
1800 334 802 – tollfree  
E-Mail sales@sick.com.au

#### **Belgium/Luxembourg**

Phone +32 (0)2 466 55 66  
E-Mail info@sick.be

#### **Brasil**

Phone +55 11 3215-4900  
E-Mail sac@sick.com.br

#### **Canada**

Phone +1 905 771 14 44  
E-Mail information@sick.com

#### **Ceská Republika**

Phone +420 2 57 91 18 50  
E-Mail sick@sick.cz

#### **China**

Phone +86 4000 121 000  
E-Mail info.china@sick.net.cn  
Phone +852-2153 6300  
E-Mail ghk@sick.com.hk

#### **Danmark**

Phone +45 45 82 64 00  
E-Mail sick@sick.dk

#### **Deutschland**

Phone +49 211 5301-301  
E-Mail kundenservice@sick.de

#### **España**

Phone +34 93 480 31 00  
E-Mail info@sick.es

#### **France**

Phone +33 1 64 62 35 00  
E-Mail info@sick.fr

#### **Great Britain**

Phone +44 (0)1727 831121  
E-Mail info@sick.co.uk

#### **India**

Phone +91-22-4033 8333  
E-Mail info@sick-india.com

#### **Israel**

Phone +972-4-6801000  
E-Mail info@sick-sensors.com

#### **Italia**

Phone +39 02 27 43 41  
E-Mail info@sick.it

#### **Japan**

Phone +81 (0)3 3358 1341  
E-Mail support@sick.jp

#### **Magyarország**

Phone +36 1 371 2680  
E-Mail office@sick.hu

#### **Nederlands**

Phone +31 (0)30 229 25 44  
E-Mail info@sick.nl

#### **Norge**

Phone +47 67 81 50 00  
E-Mail austefjord@sick.no

#### **Österreich**

Phone +43 (0)22 36 62 28 8-0  
E-Mail office@sick.at

#### **Polska**

Phone +48 22 837 40 50  
E-Mail info@sick.pl

#### **România**

Phone +40 356 171 120  
E-Mail office@sick.ro

#### **Russia**

Phone +7-495-775-05-30  
E-Mail info@sick.ru

#### **Schweiz**

Phone +41 41 619 29 39  
E-Mail contact@sick.ch

#### **Singapore**

Phone +65 6744 3732  
E-Mail admin@sicksgp.com.sg

#### **Slovenija**

Phone +386 (0)1-47 69 990  
E-Mail office@sick.si

#### **South Africa**

Phone +27 11 472 3733  
E-Mail info@sickautomation.co.za

#### **South Korea**

Phone +82 2 786 6321/4  
E-Mail info@sickkorea.net

#### **Suomi**

Phone +358-9-25 15 800  
E-Mail sick@sick.fi

#### **Sverige**

Phone +46 10 110 10 00  
E-Mail info@sick.se

#### **Taiwan**

Phone +886-2-2375-6288  
E-Mail sales@sick.com.tw

#### **Türkiye**

Phone +90 (216) 528 50 00  
E-Mail info@sick.com.tr

#### **United Arab Emirates**

Phone +971 (0) 4 8865 878  
E-Mail info@sick.ae

#### **USA/México**

Phone +1(952) 941-6780  
1 800-325-7425 – tollfree  
E-Mail info@sickusa.com

More representatives and agencies  
at [www.sick.com](http://www.sick.com)