



fiber-optic sensors  
WLL180T, Fiber-optic photoelectric sensor

WLL180T-F434S05



Model Name > **WLL180T-F434S05**  
Part No. > **6045340**



*Illustration may differ*

#### At a glance

- Selectable response time up to 16  $\mu$ s
- Sensing range up to 20 m, sensing distance up to 1400 mm
- Bus-compatible with anti-interference
- 2 x 4-digit display
- Adjustable hysteresis
- Rotatable display screen
- High-resolution signal processing
- Programmable time delays

#### Your benefits

- Reliable, rapid process detection, even under the most difficult ambient conditions, such as dust, spray or mist
- Easy commissioning and product changeover due to external teach-in
- Cross-talk is eliminated when utilizing bus configuration option
- Quick, easy setup and adjustment due to an intuitive operating menu
- Flexible parameter adjustment due to high-resolution signal processing. Hysteresis and time delays can be adapted to suit the application, e.g., when detecting tiny or transparent objects
- Easy-to-read display, even under difficult installation conditions



#### Features

|                         |                                                                                                             |
|-------------------------|-------------------------------------------------------------------------------------------------------------|
| Device type:            | Expansion unit                                                                                              |
| Dimensions (W x H x D): | 10.5 mm x 34.6 mm x 71.9 mm                                                                                 |
| Sensing range max.::    | 0 m ... 20 m, through-beam system <sup>1) 2)</sup>                                                          |
| Sensing range::         | 0 mm ... 1,400 mm, proximity system <sup>3) 4)</sup>                                                        |
| Light source:           | LED <sup>5)</sup>                                                                                           |
| Type of light:          | Visible red light                                                                                           |
| Wave length:            | 650 nm                                                                                                      |
| Adjustment:             | Cable, +/- increment button, manual, Teach-in button, Teach-in button cable<br>+/- increment button, manual |
| Teach-in:               | Menu-controlled                                                                                             |
| Time type:              | Without time delay<br>time delay off<br>switch on delay<br>ON and OFF delay<br>one shot                     |
| Delay time:             | Programmable: 0 ... 9,999 ms                                                                                |

|                                  |                                                                                                                                                                             |
|----------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Indication:                      | Display                                                                                                                                                                     |
| Sensor/detection principle:      | Fiber-optic photoelectric sensor                                                                                                                                            |
| Angle of dispersion:             | Ca. 65 °                                                                                                                                                                    |
| Housing design (light emission): | Rectangular                                                                                                                                                                 |
| Display:                         | LED status display / 2x 4-character digital dual displays, Set value (green indicator) and actual value (red indicator) are displayed simultaneously, display of parameters |

<sup>1)</sup> Sensing range with 8 ms response time. Reduction with shorter response time (see tables LL3/WLL180T) <sup>2)</sup> LL3-TX01 <sup>3)</sup> Objects to be sensed with 90% reflectivity (based on DIN 5033 white standard). Sensing range with 8 ms response time. Reduction with shorter response time (see tables LL3/WLL180T) <sup>4)</sup> LL3-DK06 <sup>5)</sup>

Average service life of 100,000 h at T<sub>A</sub> = +25 °C


## Mechanics/electronics

|                                   |                                                                     |
|-----------------------------------|---------------------------------------------------------------------|
| Enclosure rating:                 | IP 50 <sup>1)</sup>                                                 |
| Supply voltage:                   | 12 V DC ... 24 V DC <sup>2)</sup>                                   |
| Ripple:                           | ≤ 10 % <sup>3)</sup>                                                |
| Power consumption:                | ≤ 50 mA <sup>4)</sup>                                               |
| Output type:                      | PNP                                                                 |
| Output current I <sub>max</sub> : | ≤ 100 mA                                                            |
| Response time:                    | ≤ 2 ms<br>≤ 8 ms<br>≤ 16 µs<br>≤ 70 µs <sup>5)</sup><br>≤ 250 µs    |
| Switching frequency:              | ± 31.2 kHz<br>± 7.1 kHz<br>± 2 kHz<br>± 250 Hz<br>± 62.5 Hz         |
| Connection type:                  | Cable with connector M8, 4-pin, 0.2 m <sup>6)</sup>                 |
| Protection class:                 | III                                                                 |
| Circuit protection:::             | A, B, C, D <sup>7)</sup> <sup>8)</sup> <sup>9)</sup> <sup>10)</sup> |
| Special device:                   | 1                                                                   |
| Housing material:                 | ABS/PC, Plastic                                                     |
| Ambient operating temperature:    | -25 °C ... 55 °C <sup>11)</sup>                                     |
| Ambient storage temperature:      | -25 °C ... 70 °C                                                    |
| Switching mode:                   | Light/dark-switching                                                |
| Output characteristic:            | Open collector                                                      |
| Switching mode selector:          | Manually selectable                                                 |


See LL3 fiber-optic data;

<sup>1)</sup> With correctly attached fibre-optic cable LL3 and closed protection hood <sup>2)</sup> +- 10% <sup>3)</sup> May not exceed or fall short of V<sub>S</sub> tolerances <sup>4)</sup> Without load <sup>5)</sup> Selectable <sup>6)</sup>  
Do not bend below 0 °C <sup>7)</sup> A = V<sub>S</sub> connections reverse-polarity protected <sup>8)</sup> B = inputs and output reverse-polarity protected <sup>9)</sup> C = interference suppression <sup>10)</sup> D =  
outputs overcurrent and short-circuit protected <sup>11)</sup> Operating temperature fluctuates according to number of devices connected: 4-8 devices: -25 °C ... +50 °C (output  
current 50 mA)/9-16 devices: -25 °C ... +45 °C (output current 20 mA)

## Dimensional drawing



## Adjustments possible



**Australia**

Phone +61 3 9457 0600  
1800 334 802 – tollfree  
E-Mail sales@sick.com.au

**Belgium/Luxembourg**

Phone +32 (0)2 466 55 66  
E-Mail info@sick.be

**Brasil**

Phone +55 11 3215-4900  
E-Mail sac@sick.com.br

**Canada**

Phone +1 905 771 14 44  
E-Mail information@sick.com

**Ceská Republika**

Phone +420 2 57 91 18 50  
E-Mail sick@sick.cz

**China**

Phone +86 4000 121 000  
E-Mail info.china@sick.net.cn  
Phone +852-2153 6300  
E-Mail ghk@sick.com.hk

**Danmark**

Phone +45 45 82 64 00  
E-Mail sick@sick.dk

**Deutschland**

Phone +49 211 5301-301  
E-Mail kundenservice@sick.de

**España**

Phone +34 93 480 31 00  
E-Mail info@sick.es

**France**

Phone +33 1 64 62 35 00  
E-Mail info@sick.fr

**Great Britain**

Phone +44 (0)1727 831121  
E-Mail info@sick.co.uk

**India**

Phone +91-22-4033 8333  
E-Mail info@sick-india.com

**Israel**

Phone +972-4-6801000  
E-Mail info@sick-sensors.com

**Italia**

Phone +39 02 27 43 41  
E-Mail info@sick.it

**Japan**

Phone +81 (0)3 3358 1341  
E-Mail support@sick.jp

**Magyarország**

Phone +36 1 371 2680  
E-Mail office@sick.hu

**Nederlands**

Phone +31 (0)30 229 25 44  
E-Mail info@sick.nl

**Norge**

Phone +47 67 81 50 00  
E-Mail austefjord@sick.no

**Österreich**

Phone +43 (0)22 36 62 28 8-0  
E-Mail office@sick.at

**Polska**

Phone +48 22 837 40 50  
E-Mail info@sick.pl

**România**

Phone +40 356 171 120  
E-Mail office@sick.ro

**Russia**

Phone +7-495-775-05-30  
E-Mail info@sick.ru

**Schweiz**

Phone +41 41 619 29 39  
E-Mail contact@sick.ch

**Singapore**

Phone +65 6744 3732  
E-Mail admin@sicksgp.com.sg

**Slovenija**

Phone +386 (0)1-47 69 990  
E-Mail office@sick.si

**South Africa**

Phone +27 11 472 3733  
E-Mail info@sickautomation.co.za

**South Korea**

Phone +82 2 786 6321/4  
E-Mail info@sickkorea.net

**Suomi**

Phone +358-9-25 15 800  
E-Mail sick@sick.fi

**Sverige**

Phone +46 10 110 10 00  
E-Mail info@sick.se

**Taiwan**

Phone +886-2-2375-6288  
E-Mail sales@sick.com.tw

**Türkiye**

Phone +90 (216) 528 50 00  
E-Mail info@sick.com.tr

**United Arab Emirates**

Phone +971 (0) 4 8865 878  
E-Mail info@sick.ae

**USA/México**

Phone +1(952) 941-6780  
1 800-325-7425 – tollfree  
E-Mail info@sickusa.com

More representatives and agencies  
at [www.sick.com](http://www.sick.com)