



Photoelectric sensors  
W27-3, Photoelectric proximity sensor,  
Background suppression

WTB27-3P2411P02



**Model Name** > **WTB27-3P2411P02**  
**Part No.** > **1029225**



*Illustration may differ*

#### At a glance

- Precise background suppression with no scanning distance drift
- PinPoint technology: intense red LED with consistent light spot
- Resistant to ambient light, optical reflections, and crosstalk from other photoelectric devices
- Sensing range adjustment with potentiometer or teach-in
- Operating temperature: -40 °C to +60 °C
- Flexible sensing ranges and hysteresis settings
- Key lock function, remote teach, quality monitoring
- Diagnostics messages (contamination and short-circuit)

#### Your benefits

- PinPoint technology can replace laser photoelectric proximity sensors in some applications. No laser safety regulations and a longer operating life due to PinPoint technology
- Less downtime due to ASIC (application-specific integrated circuit) chip technology by SICK
- Resistant to ambient light, optical reflections, and immune to crosstalk from other photoelectric devices, reducing false detection
- Durable housing with reinforced mounting holes withstands harsh conditions
- Reliable operation in harsh environments with temperatures as low as -40 °C
- Quick and easy format adjustment
- Easy monitoring of sensor status
- Key lock function and parameter download prevent incorrect settings
- Simple sensor cloning



#### Features

|                                  |                                                        |
|----------------------------------|--------------------------------------------------------|
| Sensor/detection principle:      | Photoelectric proximity sensor, Background suppression |
| Dimensions (W x H x D):          | 24.6 mm x 80.6 mm x 54 mm                              |
| Housing design (light emission): | Rectangular                                            |
| Sensing range max.:              | 30 mm ... 1,600 mm <sup>1)</sup>                       |
| Sensing range:                   | 100 mm ... 1,600 mm                                    |
| Type of light:                   | Infrared light                                         |
| Light source:                    | LED <sup>2)</sup>                                      |
| Wave length:                     | 880 nm                                                 |
| Adjustment:                      | Potentiometer                                          |
| Light spot size (distance):      | Ø 25 mm (800 mm)                                       |


1) Object with 90 % reflectance (referred to standard white DIN 5033) 2) Average service life of 100,000 h at  $T_A = +25\text{ °C}$

## Mechanics/electronics


|                                   |                                                                 |
|-----------------------------------|-----------------------------------------------------------------|
| Supply voltage:                   | 10 V DC ... 30 V DC <sup>1)</sup>                               |
| Power consumption:                | $\leq 40\text{ mA}$ <sup>2)</sup>                               |
| Output type:                      | PNP                                                             |
| Output function:                  | Complementary                                                   |
| Switching mode:                   | Light/dark-switching                                            |
| Signal voltage PNP HIGH/LOW:      | Approx. $V_S - 2.5\text{ V} / 0\text{ V}$                       |
| Output current $I_{\text{max}}$ : | $\leq 100\text{ mA}$                                            |
| Response time:                    | $\leq 1.5\text{ ms}$ <sup>3)</sup>                              |
| Switching frequency:              | 350 Hz <sup>4)</sup>                                            |
| Connection type:                  | Connector M12, 4-pin                                            |
| Circuit protection:::             | A, B, C <sup>5)</sup> <sup>6)</sup> <sup>7)</sup>               |
| Protection class:                 | II <sup>8)</sup>                                                |
| Weight:                           | 100 g                                                           |
| Front screen heating:             | -                                                               |
| IO-Link:                          | -                                                               |
| Special device:                   | ✓                                                               |
| Housing material:                 | ABS, Plastic                                                    |
| Optics material:                  | PMMA                                                            |
| Enclosure rating:                 | IP 69K                                                          |
| Special features:                 | WTB27-3P2411, 1025994, pre-assembled on the bracket BEF-KHS-A01 |
| Ambient operating temperature:    | $-40\text{ °C} \dots 60\text{ °C}$                              |
| Ambient storage temperature:      | $-40\text{ °C} \dots 75\text{ °C}$                              |
| UL File No.:                      | NRKH.E181493 & NRKH7.E181493                                    |

1) Limit values, operation in short-circuit protected network max. 8 A 2) Without load 3) Signal transit time with resistive load 4) With light/dark ratio 1:1 5)  $A = V_S$   
 connections reverse-polarity protected 6) B = inputs and output reverse-polarity protected 7) C = interference suppression 8) Reference voltage 50 V DC

Dimensional drawing




Adjustments possible



## Connection diagram




## Characteristic curve




- |1| Sensing range on black, 6 % remission
- |2| Sensing range on grey, 18 % remission
- |3| Sensing range on white, 90 % remission

Connection type



Sensing range diagram



- Sensing range
- ① Sensing range on black, 6 % remission
  - ② Sensing range on gray, 18 % remission
  - ③ Sensing range on white, 90 % remission

#### **Australia**

Phone +61 3 9457 0600  
1800 334 802 – tollfree  
E-Mail sales@sick.com.au

#### **Belgium/Luxembourg**

Phone +32 (0)2 466 55 66  
E-Mail info@sick.be

#### **Brasil**

Phone +55 11 3215-4900  
E-Mail sac@sick.com.br

#### **Canada**

Phone +1 905 771 14 44  
E-Mail information@sick.com

#### **Ceská Republika**

Phone +420 2 57 91 18 50  
E-Mail sick@sick.cz

#### **China**

Phone +86 4000 121 000  
E-Mail info.china@sick.net.cn  
Phone +852-2153 6300  
E-Mail ghk@sick.com.hk

#### **Danmark**

Phone +45 45 82 64 00  
E-Mail sick@sick.dk

#### **Deutschland**

Phone +49 211 5301-301  
E-Mail kundenservice@sick.de

#### **España**

Phone +34 93 480 31 00  
E-Mail info@sick.es

#### **France**

Phone +33 1 64 62 35 00  
E-Mail info@sick.fr

#### **Great Britain**

Phone +44 (0)1727 831121  
E-Mail info@sick.co.uk

#### **India**

Phone +91-22-4033 8333  
E-Mail info@sick-india.com

#### **Israel**

Phone +972-4-6801000  
E-Mail info@sick-sensors.com

#### **Italia**

Phone +39 02 27 43 41  
E-Mail info@sick.it

#### **Japan**

Phone +81 (0)3 3358 1341  
E-Mail support@sick.jp

#### **Magyarország**

Phone +36 1 371 2680  
E-Mail office@sick.hu

#### **Nederlands**

Phone +31 (0)30 229 25 44  
E-Mail info@sick.nl

#### **Norge**

Phone +47 67 81 50 00  
E-Mail austefjord@sick.no

#### **Österreich**

Phone +43 (0)22 36 62 28 8-0  
E-Mail office@sick.at

#### **Polska**

Phone +48 22 837 40 50  
E-Mail info@sick.pl

#### **România**

Phone +40 356 171 120  
E-Mail office@sick.ro

#### **Russia**

Phone +7-495-775-05-30  
E-Mail info@sick.ru

#### **Schweiz**

Phone +41 41 619 29 39  
E-Mail contact@sick.ch

#### **Singapore**

Phone +65 6744 3732  
E-Mail admin@sicksgp.com.sg

#### **Slovenija**

Phone +386 (0)1-47 69 990  
E-Mail office@sick.si

#### **South Africa**

Phone +27 11 472 3733  
E-Mail info@sickautomation.co.za

#### **South Korea**

Phone +82 2 786 6321/4  
E-Mail info@sickkorea.net

#### **Suomi**

Phone +358-9-25 15 800  
E-Mail sick@sick.fi

#### **Sverige**

Phone +46 10 110 10 00  
E-Mail info@sick.se

#### **Taiwan**

Phone +886-2-2375-6288  
E-Mail sales@sick.com.tw

#### **Türkiye**

Phone +90 (216) 528 50 00  
E-Mail info@sick.com.tr

#### **United Arab Emirates**

Phone +971 (0) 4 8865 878  
E-Mail info@sick.ae

#### **USA/México**

Phone +1(952) 941-6780  
1 800-325-7425 – tollfree  
E-Mail info@sickusa.com

More representatives and agencies  
at [www.sick.com](http://www.sick.com)