

SSRPCDS125A3

solid state relay - panel mounting - input 3-32 V DC, output 48-660 V AC, 125A



Main

Range of product	Zelio Relay
Product or component type	Solid state relay
Device short name	SSR
Network number of phases	1 phase
Mounting support	Panel
[In] rated current	125 A
Output voltage	48...660 V AC
Control circuit voltage	4...32 V DC

Complementary

Contacts type and composition	1 NO
Tightening torque	<= 1.1 N.m for input <= 2.2 N.m for output
Local signalling	LED green for input status
Switching voltage	4 V DC turn-on 1 V DC turn-off
Input current limits	10 mA
Solid state output type	Zero voltage switching SCR output
Load current	0.25...125 A
Output sustained overvoltage	1200 V
Surge current	1750 A for 16.6 ms
Voltage drop	1.7 V on-state
Thermal resistance	0.22 °C/W
Maximum I ² t for fusing	12700 A ² .s for 8.3 ms
Leakage current	<= 1 mA off-state
DV/Dt	500 V/μs off-state at maximum voltage
Response time	0.5 cycle turn-on 0.5 cycle turn-off

Environment


Standards	UL E258297 CSA LR 40487 IEC 60950-1 IEC 62314
Marking	CE
IP degree of protection	IP20
Ambient air temperature for operation	-40...80 °C
Ambient air temperature for storage	-40...125 °C

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 0940 - Schneider Electric declaration of conformity

Dimensions


Panel Mounting



(1) $\varnothing 4.9 \pm 0.25 \text{ mm} / \varnothing 0.16 \pm 0.0098 \text{ in.}$ hole

Thermal Derating Curves

125 A Relays



- A: Power dissipation
B: Load current (Arms)
C: Max. ambient temperature (°C)
D: Base plate temperature (°C)

Note : These are typical curves, actual durability depends on load, environment, duty cycle, etc.