


SU8200

Ultrasonic flow meter

SUR11HGBFPKG/W/US-100-IPF



installation length with pipe adapter E40152 / E40155: 205 mm
installation length with pipe adapter E40153 / E40156: 215 mm



Application

Application	for industrial applications
Installation	connection to pipe by means of an adapter
Media	water; glycol solutions; coolants; oil
Medien	low-viscosity oils with viscosity: 7...40 mm ² /s (40 °C) high-viscosity oils with viscosity: 30...68 mm ² /s (40 °C)
Medium temperature [°C]	-10...80
Pressure rating [bar]	16

Electrical data

Operating voltage [V]	19...30 DC; (according to EN 50178 SELV/PELV)
Current consumption [mA]	100
Min. insulation resistance [MΩ]	100; (500 V DC)
Protection class	III
Reverse polarity protection	yes
Power-on delay time [s]	10



Ultrasonic flow meter

SUR11HGBFPKG/W/US-100-IPF

Outputs		
Total number of outputs	2	
Output signal	switching signal	
Electrical design	PNP	
Number of digital outputs	2	
Output function	normally open / normally closed; (parameterisable)	
Max. voltage drop switching output DC [V]	2	
Permanent current rating of switching output DC [mA]	250; (per output)	
Short-circuit protection	yes	
Type of short-circuit protection	pulsed	
Overload protection	yes	
Measuring/setting range		
Measuring range	0...26.42 gpm	0...100 l/min
Display range	0...31.7 gpm	0...120 l/min
Resolution	0.02 gpm	0.1 l/min
Set point SP	0.06...26.42 gpm	0.2...100 l/min
Reset point rP	0...26.38 gpm	0...99.8 l/min
Max. flow rate [l/min]	110	
Max. flow rate [m³/h]	6.6	
In steps of	0.02 gpm	0.1 l/min
Temperature monitoring		
Measuring range [°C]	-10...80	
Resolution [°C]	0.2	
Set point SP [°C]	-9.8...80	
Reset point rP [°C]	-10...79.8	
In steps of [°C]	0.2	
Accuracy / deviations		
Flow monitoring		
Accuracy (in the measuring range)	< ± (3 % MW + 0,2 % MEW) / < ± (5 % MW + 0,5 % MEW); (water; glycol: 35%; oil: viscosity 68 mm²/s at 40 °C)	
Repeatability	0,2 l/min (0,05 gpm)	
Temperature monitoring		
Accuracy [K]	0,2	
Response times		
Flow monitoring		
Response time [s]	0.25; (dAP = 0)	
Delay time programmable dS, dr [s]	0...50	
Damping for the switching output dAP [s]	0...1	
Temperature monitoring		
Dynamic response T05 / T09 [s]	T09 = 70 (Q > 5 l/min); (water)	



Ultrasonic flow meter

SUR11HGBFPKG/W/US-100-IPF

Software / programming		
Parameter setting options	Flow monitoring; Temperature monitoring	
Operating conditions		
Ambient temperature	[°C]	-10...60
Storage temperature	[°C]	-25...80
Protection	IP 67	
Tests / approvals		
EMC	EN 61000-4-2 ESD	4 kV CD / 8 kV AD
	EN 61000-4-3 HF radiated	10 V/m
	EN 61000-4-4 Burst	2 kV
	EN 61000-4-5 Surge	0,5 kV
	EN 61000-4-6 HF conducted	10 V
Shock resistance	DIN IEC 68-2-27	20 g (11 ms)
Vibration resistance	DIN IEC 68-2-6	5 g (10...2000 Hz)
MTTF	[years]	246
Pressure Equipment Directive	Sound Engineering Practice; can be used for group 2 fluids; group 1 fluids on request	
Mechanical data		
Weight	[g]	1695.4
Materials	housing: AlMgSi0,5 anodised; Sealing: FKM; connector housing: brass Optalloy-plated; PA 6.6; cover film: PA	
Materials (wetted parts)	stainless steel (1.4404 / 316L); FKM; PES; Centellen 200	
Process connection	threaded connection G 1 flat seal	
Displays / operating elements		
Display	Display unit	4 x LED, green (l/min, m³/h, gal/min, gal/h)
	Display unit	2 x LED, yellow (°C / °F)
	switching status	2 x LED, yellow
	measured values	alphanumeric display, 4-digit
	programming	alphanumeric display, 4-digit
Display unit	l/min; m³/h; gpm; gph; °C; °F	
Accessories		
Accessories (supplied)	sealings: 2, Centellen	
Accessories (optional)	adapter for pipe: 1 x R1/2, stainless steel, E40179	
	adapter for pipe: 1 x R3/4, stainless steel, E40180	
	adapter for pipe: 1 x 1/2 NPT, stainless steel, E40192	
	adapter for pipe: 1 x 3/4 NPT, stainless steel, E40193	
	adapter for pipe: 1 x R1/2, brass, E40152	
	adapter for pipe: 1 x R3/4, brass, E40153	
	adapter for pipe: 1 x 1/2 NPT, brass, E40155	
	adapter for pipe: 1 x 3/4 NPT, brass, E40156	
Remarks		
Remarks	MW = measured value	
	MEW = Final value of the measuring range	
	sealing: only with supplied Centellen seals	
Pack quantity	1 pcs.	
Electrical connection		
Connector: 1 x M12; Moulded body: brass, Optalloy-plated; Contacts: gold-plated		


SU8200

Ultrasonic flow meter

SUR11HGBFPKG/W/US-100-IPF




Connection



Diagrams and graphs

Pressure loss



dP Pressure loss

Q volumetric flow quantity