



PRODUCT-DETAILS

# TBM0750

## MEDIUM WALL 3:1 ADH.LINED



---

### General Information

Extended Product Type	TBM0750
Product ID	7TCA017410R0007
EAN	5414363109419
Catalog Description	MEDIUM WALL 3:1 ADH.LINED
Long Description	Heat Shrink Tubing, Rated for 600 Volts, 90 Degree C, Continuous Use, RoHS Compliance, 19.1mm Expanded, 5 Per Bag, Black, Medium Wall, Adhesive Liner

---

### Ordering

E-Number (Finland)	5240646
EAN	5414363109419

---

### Dimensions

Product Net Weight	.13 lb 58.957 g
--------------------	--------------------

---

### Container Information

Package Level 1 Units	5 piece
Package Level 2 Units	35 piece
Package Level 2 Width	6.7 in 170 mm

Package Level 2 Height	6.7 in 170 mm
Package Level 2 Depth / Length	51.2 in 1300 mm

### Additional Information

Brand / Label	Shrink-Kon
Color	Black
Flammability Hazard Rating	Flame Retardant
Number of Batteries	0
Process Temperature Rating	-67 to +230 °F -55 to +110 °C
Product Name	PLASTIC CONDUIT
Product Type	Heat Shrinkable Tubing
Shrink Ratio	3:1
Shrink Temperature	248 °F 120 °C
UPC	786210082660

### Certificates and Declarations (Document Number)

Data Sheet, Technical Information	TBM0750
Instructions and Manuals	TBM0750

### Classifications

ETIM 6	EC000217 - Shrink tubing
ETIM 7	EC000217 - Shrink tubing
UNSPSC	39121723
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5073 >> Heat shrinkable tube

### Categories

Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Identification & Heat Shrink

