



PRODUCT-DETAILS

TBM0950

MEDIUM WALL 3:1 ADH.LINED



General Information

Extended Product Type	TBM0950
Product ID	7TCA017410R0008
EAN	5414363172352
Catalog Description	MEDIUM WALL 3:1 ADH.LINED
Long Description	Heat Shrink Tubing, Rated for 600 Volts, 90 Degree C, Continuous Use, RoHS Compliance, 25mm Expanded, 3 Per Bag, Black, Medium Wall, Adhesive Liner

Ordering

E-Number (Finland)	5240647
EAN	5414363172352

Dimensions

Product Net Weight	.17 lb 77.098 g
--------------------	--------------------

Container Information

Package Level 1 Units	3 piece
Package Level 1 Width	51.2 in 1300 mm
Package Level 1 Height	19.3 in

	490 mm
Package Level 1 Depth / Length	6.7 in 170 mm
Package Level 2 Units	90 piece
Package Level 2 Width	102 in 2591 mm
Package Level 2 Height	40 in 1016 mm
Package Level 2 Depth / Length	13 in 330 mm

Additional Information

Brand / Label	Shrink-Kon
Color	Black
Flammability Hazard Rating	Flame Retardant
Number of Batteries	0
Process Temperature Rating	-67 to +230 °F -55 to +110 °C
Product Name	PLASTIC CONDUIT
Product Type	Heat Shrinkable Tubing
Shrink Ratio	3:1
Shrink Temperature	248 °F 120 °C
UPC	786210980836

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	TBM0950
Instructions and Manuals	TBM0950

Classifications

ETIM 6	EC000217 - Shrink tubing
ETIM 7	EC000217 - Shrink tubing
UNSPSC	39121723
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5073 >> Heat shrinkable tube

Categories

Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Identification & Heat Shrink

