



Main

Accessory / separate part category	Communication accessory
Accessory / separate part type	Wireless access point
Accessory / separate part destination	Smart phone Phablet Variable speed drive PC Tablet PLC

Complementary

Range compatibility	Modicon M251 Altivar Process ATV600 Modicon M580 Altivar Process ATV900
Kit composition	Battery USB cable Power adaptor Ethernet cable Quick start guide
Function available	Automatic detection of Schneider-Electric products and other devices on Ethernet
Connector type	Female RJ45 automatic negotiation of 10/100 Mbit/s Micro USB type A female
Communication port protocol	DHCP PPPoE (Point-to-Point Protocol over Ethernet) Ethernet TCP/IP ICMP
Method of access	CSMA/CA CSMA/CD
Operating system	Windows 7 Mac iOS Android Windows XP Windows 8 Windows Vista
System requirements	Google Chrome Microsoft internet explorer Apple Safari Firefox
Supply	Rechargeable internal battery

Local signalling	1 LED (green, orange and red)battery status: 1 LEDEthernet port activity: 1 LEDwireless function status: 1 LEDscan status:
Product weight	0.35 kg

Environment

IP degree of protection	IP20
Ambient air temperature for operation	0...40 °C
Ambient air temperature for storage	-40...70 °C
Relative humidity	10...90 % for operation, without condensation conforming to IEC 60068-2-3 5...90 % for storage, without condensation conforming to IEC 60068-2-3
Standards	IEEE 802.11g IEEE 802.11n IEEE 802.1x IEEE 802.3 IEEE 802.3x IEEE 802.3u IEEE 802.11b
Product certifications	FCC CE

Offer Sustainability

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration

Contractual warranty

Warranty	18 months
----------	-----------