



Main

Range of product	ConneXium
Product or component type	Ethernet TCP/IP unmanaged switch
Concept	Transparent Ready
Communication port protocol	Ethernet TCP/IP
Port Ethernet	10BASE-T/100BASE-TX - 7 port(s) copper cable 100BASE-FX - 2 port(s) fibre optic
Maximum number of switches in cascade	Unlimited

Complementary

Integrated connection type	Shielded RJ45 copper cable Port fiber optic
Transmission support medium	Twisted shielded pairs cable CAT 5E for copper cable Single mode optical fiber for fiber optic
Maximum cable distance between devices	100 m copper cable
Ethernet service	Automatic negotiation of 10/100 Mbit/s and duplex mode Auto MDI/MDX Automatic change of polarity Storage and re-routing of received data
[Us] rated supply voltage	24 V
Supply voltage limits	9.6...32 V DC SELV
Power consumption in W	6.9 W
Electrical connection	Removable connector 6 ways power supply
Mounting support	35 mm symmetrical DIN rail
Marking	CE
Local signalling	1 LED per channelcopper port activity: 1 LEDpower supply: 1 LED per channel10 or 100 Mbit/s data rate:
Ethernet cabling system	TF switches
Width	56 mm
Height	135 mm
Depth	113 mm
Product weight	0.510 kg

Environment

Ambient air temperature for operation	-40...70 °C
Relative humidity	0...95 % without condensation
IP degree of protection	IP40
Standards	CSA C22.2 No 142 CUL 508
Product certifications	CE

Contractual warranty

Warranty	18 months
----------	-----------

Dimensions

