



Main

Range of product	Modicon M238 logic controller
Product or component type	Analog input module
Analogue input number	8
Analogue input type	Voltage 0...10 V non differential Current 4...20 mA non differential
Cross talk	<= 1 LSB

Complementary

Range compatibility	Advantys OTB Twido
Analogue input resolution	10 bits
LSB value	9.7 mV voltage 19.5 μ A current
Permissible continuous overload	40 mA current 13 V voltage
Input impedance	≥ 10 kOhm voltage 470 Ohm current
Sampling duration	≤ 160 ms
Acquisition period	160 ms per channel + 1 controller cycle time
Measurement error	± 0.2 % of full scale 25 °C
Temperature coefficient	± 0.01 %FS/°C
Repeat accuracy	± 0.4 %FS
Non-linearity	± 0.002 %FS
Total error	± 1 %FS
Type of cable	Shielded cable
Insulation between channel and internal logic	Photocoupler
Supply	External supply
[Us] rated supply voltage	24 V DC
Supply voltage limits	20.4...28.8 V
Electrical connection	1 removable screw terminal block sensors 1 removable screw terminal block power supply
Current consumption	60 mA 5 V DC internal 45 mA 24 V DC external
Product weight	0.085 kg

Environment


Dielectric strength	2500 V between the I/O and internal logic
Width	23.5 mm
Depth	70 mm
Height	90 mm

Offer Sustainability

Sustainable offer status	Green Premium product
Product environmental profile	Available  Download Product Environmental
Product end of life instructions	Available  Download End Of Life Manual


Analog Input Module (8-channel, Voltage/Current)

Dimensions



NOTE: * 8.5 mm (0.33 in) when the clip-on lock is pulled out.

DIN Rail Mounting




Rail depth	Catalogue part number
15 mm (0.59 in.)	AM1DE200
7,5 mm (0.30 in.)	AM1DP200

NOTE: Do not use AM1ED200 and DZ5MB200

Module Mounting on a Panel Surface

Mounting Hole Layout



Wiring Requirements

Cable Types and Wire Sizes for Removable Screw Terminal Block

							
mm ²	0,14...1,5	0,25...0,5	0,25...1,5	0,14...0,5	0,14...0,75	0,25...0,34	0,5
AWG	26...16	24...20	24...16	26...20	26...18	24...22	20

Analog Input Module (8-channel, Voltage/Current)

Wiring Diagram

