

TS9281




Temperature cable sensor with process connection

TS-250KCKD6-...../US/

Status Archive

TS9289



Application

Measuring element	1 x Pt 100; (to DIN EN 60751, class A)
Media	liquids and gases
Minimum installation depth [mm]	15

Electrical data

Protection class	III
------------------	-----

Measuring/setting range

Measuring range	-40...150 °C	-40...302 °F
-----------------	--------------	--------------

Accuracy / deviations

Accuracy [K]	$\pm (0,15 K + 0,002 \times t)$
--------------	-----------------------------------

Response times

Dynamic response T05 / T09 [s]	3 / 10; (to DIN EN 60751)
--------------------------------	---------------------------

Operating conditions

Protection	IP 67
------------	-------

Tests / approvals

MTTF [years]	22831
--------------	-------

Mechanical data

Weight [g]	125
Dimensions [mm]	Ø 6
Materials	stainless steel (1.4571/316Ti); FKM
Materials (wetted parts)	stainless steel (1.4571/316Ti)
Probe diameter [mm]	6

Remarks

Remarks	The values for accuracy apply to flowing water.
Notes	discontinued article
Pack quantity	1 pcs.

Electrical connection

Cable: 2.5 m, FKM

Connector: 1 x M12

TS9281




Temperature cable sensor with process connection

TS-250KCKD6.-...../US/



Connection



Status Archive

TS9289