



Main

Range of product	Modicon TSX Micro automation platform
Product or component type	Discrete input module
Discrete input number	8 screw terminal block
Discrete input voltage	170...264 V 200...240 V AC
Frequency measurement range	47...63 Hz
Discrete input current	12 mA 60 Hz 10 mA 50 Hz
Input voltage limits	< 40 V at state 0 >= 120 V at state 1
Input current limits	>= 6 mA at state 1 <= 5 mA at state 0
Response time	10...22 ms at state 1 to state 0 60 Hz 11...24 ms at state 1 to state 0 50 Hz 9...16 ms at state 0 to state 1 60 Hz 11...18 ms at state 0 to state 1 50 Hz

Complementary

Standards	IEC 1131-2 Type 1
Input compatibility	2-wire proximity sensor
Discrete input type	Capacitive
Current consumption	20 mA
Power dissipation in W	1.4 W
Isolation voltage	1500 V AC 1 s

Environment

Product weight	0.23 kg
----------------	---------


Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Will not be Compliant

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Sensors/Inputs Connections

Wiring Diagram



FU1 = 0.5A fuse with rapid fusion.