



Main

Range of product	Modicon Premium Automation platform
Product or component type	Discrete output module
Discrete output number	8
Discrete output type	Relay protected
Discrete output voltage	24...48 V DC conforming to EN/IEC 61131-2 19...60 V 24...240 V AC conforming to EN/IEC 61131-2 20...264 V

Complementary

[I _{th}] conventional free air thermal current	5 A
Response time	< 15 ms deactivation < 10 ms activation
Contacts type and composition	2 x 2 C/O + 2 x 2 NO
Output overvoltage protection	RC circuit and Ge-Mov
Output overload protection	6.3 A, interchangeable fuse per common fast blow
Short-circuit protection	6.3 A, interchangeable fuse per common fast blow
Isolation resistance	> 10 MOhm 500 V
Power dissipation	(0.25 W + 0.24 W x No of outputs at state 1)
Electrical durability	700000 cycles AC-12 100 VA 24 V resistive 5000000 cycles AC-15 20 VA 48 V inductive 5000000 cycles AC-14 20 VA 48 V inductive 500000 cycles AC-15 50 VA 24 V inductive 500000 cycles AC-14 50 VA 24 V inductive 500000 cycles AC-12 440 VA 100...120 V resistive 500000 cycles AC-12 200 VA 48 V resistive 3000000 cycles AC-15 110 VA 220...240 V inductive 3000000 cycles AC-14 110 VA 220...240 V inductive 2000000 cycles AC-15 50 VA 48 V inductive 2000000 cycles AC-14 50 VA 48 V inductive 1500000 cycles AC-15 110 VA 100...120 V inductive 1500000 cycles AC-14 110 VA 100...120 V inductive 150000 cycles AC-15 220 VA 100...120 V inductive 150000 cycles AC-14 220 VA 100...120 V inductive 10000000 cycles AC-15 20 VA 220...240 V inductive 10000000 cycles AC-15 20 VA 100...120 V inductive 10000000 cycles AC-14 20 VA 100...120 V inductive 1000000 cycles AC-15 220 VA 220...240 V inductive 1000000 cycles AC-14 220 VA 220...240 V inductive 1000000 cycles AC-12 440 VA 220...240 V resistive 1000000 cycles AC-12 220 VA 100...120 V resistive 1000000 cycles AC-12 100 VA 48 V resistive 100000 cycles AC-15 440 VA 220...240 V inductive 100000 cycles AC-14 440 VA 220...240 V inductive 300000 cycles DC-12 50 W 24 V resistive 300000 cycles DC-12 100 W 48 V resistive 2000000 cycles DC-3 24 W 48 V inductive 2000000 cycles DC-3 10 W 24 V inductive 1000000 cycles DC-3 50 W 48 V inductive 1000000 cycles DC-3 24 W 24 V inductive 1000000 cycles DC-12 50 W 48 V resistive 1000000 cycles DC-12 24 W 24 V resistive
Marking	CE
Electrical connection	Screw terminal block

Current consumption	80 mA 24 V DC rack 55 mA 5 V DC
Module format	Standard
Product weight	0.42 kg

Environment


Dielectric strength	2000 V 50/60 Hz 60 s
Standards	73/23/EEC 89/336/EEC 92/31/EEC 93/68/EEC CSA 22-2 No 142 CSA 22-2 No 213 Class I Division 2 Group A CSA 22-2 No 213 Class I Division 2 Group B CSA 22-2 No 213 Class I Division 2 Group C CSA 22-2 No 213 Class I Division 2 Group D IEC 61131-2 UL 508
Product certifications	ABS BV DNV GL LR RINA RMRS
Ambient air temperature for operation	0...60 °C
Ambient air temperature for storage	-25...70 °C
Relative humidity	5...95 % without condensation for storage 10...95 % without condensation for operation
Operating altitude	0...2000 m
Protective treatment	TC
IP degree of protection	IP20
Pollution degree	2

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS	Compliant - since 0908 - Schneider Electric declaration of conformity download declaration of conformity

Standard and Extendable Racks for Modules Mounting

Dimensions of Modules and Racks



(1) With screw terminal block modules.

(2) Maximum depth for all types of modules and their associated connectors.

Discrete Relay Output 8-Channel Module for 5 A Thermal Current

Wiring Diagram

